



P-Channel JFETs

PRODUCT SUMMARY

Part Number	$V_{GS(off)}$ (V)	$r_{DS(on)}$ Max (Ω)	$I_{D(off)}$ Typ (pA)	t_{ON} Max (ns)
2N5114	5 to 10	75	-10	16
2N5115	3 to 6	100	-10	30
2N5116	1 to 4	150	-10	42

FEATURES

- Low On-Resistance: 2N5114 <75 Ω
- Fast Switching— t_{ON} : 16 ns
- High Off-Isolation— $I_{D(off)}$: -10 pA
- Low Capacitance: 6 pF
- Low Insertion Loss

BENEFITS

- Low Error Voltage
- High-Speed Analog Circuit Performance
- Negligible "Off-Error," Excellent Accuracy
- Good Frequency Response
- Eliminates Additional Buffering


APPLICATIONS

- Analog Switches
- Choppers
- Sample-and-Hold
- Normally "On" Switches
- Current Limiters

DESCRIPTION

The 2N5114 series consists of p-channel JFET analog switches designed to provide low on-resistance, good off-isolation, and fast switching. These JFETs are optimized for use in complementary switching applications with the Vishay Siliconix 2N4856A series.

The 2N5114 series is available with JAN, JANTX, or JANTXV level processing, (see 2N5114 JAN series data sheet).



ABSOLUTE MAXIMUM RATINGS

Gate-Drain Voltage 30 V
Gate-Source Voltage 30 V
Gate Current -50 mA
Storage Temperature -65 to 200°C
Operating Junction Temperature -55 to 200°C

Lead Temperature ($1/16$ " from case for 10 sec.) 300°C
Power Dissipation^a 500 mW

Notes

a. Derate 3 mW/°C above 25°C







For applications information see AN104.







SPECIFICATIONS (T _A = 25 °C UNLESS OTHERWISE NOTED)											
Parameter	Symbol	Test Conditions		Typ ^a	Limits						Unit
					2N5114		2N5115		2N5116		
					Min	Max	Min	Max	Min	Max	
Static											
Gate-Source Breakdown Voltage	V _{(BR)GSS}	I _G = 1 μA , V _{DS} = 0 V		45	30		30		30		V
Gate-Source Cutoff Voltage	V _{GS(off)}	V _{DS} = -15 V, I _D = -1 nA			5	10	3	6	1	4	
Saturation Drain Current ^b	I _{DSS}	V _{GS} = 0 V	V _{DS} = -18 V		-30	-90					mA
			V _{DS} = -15 V				-15	-60	-5	-25	
Gate Reverse Current	I _{GSS}	V _{GS} = 20 V, V _{DS} = 0 V		5		500		500		500	pA
		T _A = 150 °C		0.01		1		1		1	μA
Gate Operating Current ^c	I _G	V _{DG} = -15 V, I _D = -1 mA		-5							
Drain Cutoff Current	I _{D(off)}	V _{DS} = -15 V	V _{GS} = 12 V	-10		-500					pA
			V _{GS} = 7 V	-10			-500				
			V _{GS} = 5 V	-10					-500		
		V _{DS} = -15 V T _A = 150 °C	V _{GS} = 12 V	-0.02		-1					μA
			V _{GS} = 7 V	-0.02			-1				
			V _{GS} = 5 V	-0.02					-1		
Drain-Source On-Voltage	V _{DS(on)}	V _{GS} = 0 V	I _D = -15 mA	-1.0		-1.3					V
			I _D = -7 mA	-0.7				-0.8			
			I _D = -3 mA	-0.5						-0.6	
Drain-Source On-Resistance	r _{DS(on)}	V _{GS} = 0 V, I _D = -1 mA				75		100		150	Ω
Gate-Source Forward Voltage	V _{GS(F)}	I _G = -1 mA , V _{DS} = 0 V		-0.7		-1		-1		-1	V
Dynamic											
Common-Source Forward Transconductance ^c	g _{fs}	V _{DS} = -15 V, I _D = -1 mA f = 1 kHz		4.5							mS
Common-Source Output Conductance ^c	g _{os}			20							μS
Drain-Source On-Resistance	r _{ds(on)}	V _{GS} = 0 V, I _D = 0 mA , f = 1 kHz				75		100		150	Ω
Common-Source Input Capacitance	C _{iss}	V _{DS} = -15 V, V _{GS} = 0 V f = 1 MHz		20		25		25		25	pF
Common-Source Reverse Transfer Capacitance	C _{rss}	V _{DS} = 0 V f = 1 MHz	V _{GS} = 12 V	5		7					
			V _{GS} = 7 V	6			7				
			V _{GS} = 5 V	6						7	
Equivalent Input Noise Voltage ^c	e _n	V _{DS} = 10 V, I _D = 10 mA f = 1 kHz		20							nV/ √Hz
Switching											
Turn-On Time	t _{d(on)}	See Switching Circuit				6		10		12	ns
	t _r					10		20		30	
Turn-Off Time	t _{d(off)}					6		8		10	
	t _f					15		30		50	

Notes

- a. Typical values are for DESIGN AID ONLY, not guaranteed nor subject to production testing.
b. Pulse test: $PW \leq 300\ \mu\text{s}$ duty cycle $\leq 3\%$.
c. This parameter not registered with JEDEC.





PSCIA

**TYPICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ UNLESS OTHERWISE NOTED)****On-Resistance and Drain Current vs. Gate-Source Cutoff Voltage****Forward Transconductance and Output Conductance vs. Gate-Source Cutoff Voltage****On-Resistance vs. Drain Current****On-Resistance vs. Temperature****Turn-On Switching****Turn-Off Switching**

TYPICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ UNLESS OTHERWISE NOTED)



TYPICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ UNLESS OTHERWISE NOTED)



SWITCHING TIME TEST CIRCUIT

	2N5114	2N5115	2N5116
V_{DD}	-10 V	-6 V	-6 V
V_{GG}	20 V	12 V	8 V
R_L^*	430 Ω	910 Ω	2 k Ω
R_G^*	100 Ω	220 Ω	390 Ω
$I_{D(on)}$	-15 mA	-7 mA	-3 mA
$V_{GS(H)}$	0 V	0 V	0 V
$V_{GS(L)}$	-11 V	-7 V	-5 V

*Non-inductive

INPUT PULSE

Rise Time < 1 ns
Fall Time < 1 ns
Pulse Width 100 ns
PRF 1 MHz

SAMPLING SCOPE

Rise Time 0.4 ns
Input Resistance 10 M Ω
Input Capacitance 1.5 pF

See Typical Characteristics curves for changes.

