




Glass Passivated Ultrafast Rectifier

DO-204AC (DO-15)

Reverse Voltage 50 to 400 V
Forward Current 2.0 A

*Glass Encapsulation technique is covered by
Patent No. 3,996,602, brazed-lead assembly to Patent No. 3,930,306

Features

- Plastic package has Underwriters Laboratories Flammability Classification 94V-0
- Cavity-free glass passivated junction
- Ultrafast recovery time for high efficiency
- Low forward voltage, high current capability
- Low leakage current
- High surge current capability
- High temperature metallurgically bonded construction
- High temperature soldering guaranteed:
300°C/10 seconds, 0.375" (9.5mm) lead length,
5 lbs. (2.3kg) tension

Mechanical Data

Case: JEDEC DO-204AC, molded plastic over solid glass body

Terminals: Plated axial leads, solderable per MIL-STD-750, Method 2026

Polarity: Color band denotes cathode end

Mounting Position: Any

Weight: 0.015 oz., 0.4 g

Maximum Ratings & Thermal Characteristics Ratings at 25°C ambient temperature unless otherwise specified.

Parameter	Symbol	EGP20A	EGP20B	EGP20C	EGP20D	EGP20F	EGP20G	Unit
Maximum repetitive peak reverse voltage	V _{RRM}	50	100	150	200	300	400	V
Maximum RMS voltage	V _{RMS}	35	70	105	140	210	280	V
Maximum DC blocking voltage	V _{DC}	50	100	150	200	300	400	V
Maximum average forward rectified current 0.375" (9.5mm) lead length at T _A = 55°C	I _{F(AV)}	2.0						A
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load	I _{FSM}	75						A
Typical thermal resistance (Note 1)	R _{θJA}	40						°C/W
	R _{θJL}	15						
Operating and storage temperature range	T _J ,T _{STG}	−65 to +150						°C

Electrical Characteristics Ratings at 25°C ambient temperature unless otherwise specified.

Parameter	Symbol	EGP20A	EGP20B	EGP20C	EGP20D	EGP20F	EGP20G	Unit
Maximum instantaneous forward voltage at 2.0A	V _F	0.95				1.25		V
Maximum DC reverse current at rated DC blocking voltage T _A = 25°C T _A = 125°C	I _R	5.0 100						μA
Maximum reverse recovery time at I _F = 0.5A, I _R = 1.0A, I _{rr} = 0.25A	t _{rr}	50						ns
Typical junction capacitance at 4.0V, 1MHz	C _J	70				45		pF

Note: (1) Thermal resistance from junction to ambient, and from junction to lead at 0.375" (9.5mm) lead length, P.C.B. mounted

Ratings and Characteristic Curves ($T_A = 25^\circ\text{C}$ unless otherwise noted)

Fig. 1 – Maximum Forward Current Derating Curve




Fig. 2 – Maximum Non-Repetitive Peak Forward Surge Current




Fig. 3 – Typical Instantaneous Forward Characteristics




Fig. 4 – Typical Reverse Characteristics




Fig. 5 – Typical Junction Capacitance




Fig. 6 – Typical Transient Thermal Impedance

