

## Features

- Single, dual, and quad topologies
- 3mA supply current (per amplifier)
- 250MHz -3dB bandwidth
- 1200V/ $\mu$ s slew rate
- Tiny package options (SOT23, LPP)
- Low cost
- Single- and dual-supply operation down to  $\pm 1.5V$
- 0.05%/0.05° diff. gain/diff. phase into 150 $\Omega$

## Applications

- Low power/battery applications
- HDSL amplifiers
- Video amplifiers
- Cable drivers
- RGB amplifiers
- Test equipment amplifiers
- Current to voltage converters

## Ordering Information

| Part No      | Package     | Tape & Reel | Outline # |
|--------------|-------------|-------------|-----------|
| EL2180CN     | 8-Pin PDIP  | -           | MDP0031   |
| EL2180CS     | 8-Pin SO    | -           | MDP0027   |
| EL2180CS-T7  | 8-Pin SO    | 7"          | MDP0027   |
| EL2180CS-T13 | 8-Pin SO    | 13"         | MDP0027   |
| EL2180CW-T7  | 5-Pin SOT23 | 7"          | MDP0038   |
| EL2180CW-T13 | 5-Pin SOT23 | 13"         | MDP0038   |
| EL2280CN     | 8-Pin PDIP  | -           | MDP0031   |
| EL2280CS     | 8-Pin SO    | -           | MDP0027   |
| EL2280CS-T7  | 8-Pin SO    | 7"          | MDP0027   |
| EL2280CS-T13 | 8-Pin SO    | 13"         | MDP0027   |
| EL2480CN     | 14-Pin PDIP | -           | MDP0031   |
| EL2480CS     | 14-Pin SO   | -           | MDP0027   |
| EL2480CS-T7  | 14-Pin SO   | 7"          | MDP0027   |
| EL2480CS-T13 | 14-Pin SO   | 13"         | MDP0027   |
| EL2480CL     | 24-Pin LPP  | -           | MDP0046   |
| EL2480CL-T7  | 24-Pin LPP  | 7"          | MDP0046   |
| EL2480CL-T13 | 24-Pin LPP  | 13"         | MDP0046   |



## General Description

The EL2180C/EL2280C/EL2480C are single/dual/quad current-feed-back operational amplifiers that achieve a -3dB bandwidth of 250MHz at a gain of +1 while consuming only 3mA of supply current per amplifier. They will operate with dual supplies ranging from  $\pm 1.5V$  to  $\pm 6V$  or from single supplies ranging from +3V to +12V. In spite of their low supply current, the EL2480C and the EL2280C can output 55mA while swinging to  $\pm 4V$  on  $\pm 5V$  supplies. The EL2180C can output 100mA with similar output swings. These attributes make the EL2180C/EL2280C/EL2480C excellent choices for low power and/or low voltage cable driver, HDSL, or RGB applications.

For applications where board space is extremely critical, the EL2180C is available in the tiny 5-pin SOT23 package, with a footprint size 28% of an 8-pin SO. The EL2480C is also available in a 24-pin LPP package. All are specified for operation over the full -40°C to +85°C temperature range.

Single, dual, and triple versions are also available with the enable function (EL2186C, EL2286C, and EL2386C).

## Connection Diagrams



**Note:** All information contained in this data sheet has been carefully checked and is believed to be accurate as of the date of publication; however, this data sheet cannot be a "controlled document". Current revisions, if any, to these specifications are maintained at the factory and are available upon your request. We recommend checking the revision level before finalization of your design documentation.

# EL2180C/EL2280C/EL2480C-Preliminary

250MHz / 3mA Current Mode Feedback Amplifiers

## Absolute Maximum Ratings (T<sub>A</sub> = 25°C)

|                                                     |                                    |                                |                 |
|-----------------------------------------------------|------------------------------------|--------------------------------|-----------------|
| Supply Voltage between V <sub>S+</sub> and GND      | +12.6V                             | Operating Junction Temperature |                 |
| Voltage between V <sub>S+</sub> and V <sub>S-</sub> | +12.6V                             | Plastic Packages               | 150°C           |
| Common-Mode Input Voltage                           | V <sub>S-</sub> to V <sub>S+</sub> | Output Current (EL2180C)       | ±120mA          |
| Differential Input Voltage                          | ±6V                                | Output Current (EL2280C)       | ±60mA           |
| Current into +IN or -IN                             | ±7.5mA                             | Output Current (EL2480C)       | ±60mA           |
| Internal Power Dissipation                          | See Curves                         | Storage Temperature Range      | -65°C to +150°C |
| Operating Ambient Temperature Range                 | -40°C to +85°C                     |                                |                 |

### Important Note:

All parameters having Min/Max specifications are guaranteed. Typ values are for information purposes only. Unless otherwise noted, all tests are at the specified temperature and are pulsed tests, therefore: T<sub>J</sub> = T<sub>C</sub> = T<sub>A</sub>.

## DC Electrical Characteristics

V<sub>S</sub> = ±5V, R<sub>L</sub> = 150Ω, T<sub>A</sub> = 25°C unless otherwise specified.

| Parameter         | Description                           | Conditions                                         | Min  | Typ  | Max | Unit  |
|-------------------|---------------------------------------|----------------------------------------------------|------|------|-----|-------|
| V <sub>OS</sub>   | Input Offset Voltage                  |                                                    |      | 2.5  | 10  | mV    |
| TCV <sub>OS</sub> | Average Input Offset Voltage Drift    | Measured from T <sub>MIN</sub> to T <sub>MAX</sub> |      | 5    |     | μV/°C |
| dV <sub>OS</sub>  | V <sub>OS</sub> Matching              | EL2280C, EL2480C only                              |      | 0.5  |     | mV    |
| +I <sub>IN</sub>  | +Input Current                        |                                                    |      | 1.5  | 15  | μA    |
| d+I <sub>IN</sub> | +I <sub>IN</sub> Matching             | EL2280C, EL2480C only                              |      | 20   |     | nA    |
| -I <sub>IN</sub>  | -Input Current                        |                                                    |      | 16   | 40  | μA    |
| d-I <sub>IN</sub> | -I <sub>IN</sub> Matching             | EL2280C, EL2480C only                              |      | 2    |     | μA    |
| CMRR              | Common Mode Rejection Ratio           | V <sub>CM</sub> = ±3.5V                            | 45   | 50   |     | dB    |
| -ICMR             | -Input Current Common Mode Rejection  | V <sub>CM</sub> = ±3.5V                            |      | 5    | 30  | μA/V  |
| PSRR              | Power Supply Rejection Ratio          | V <sub>S</sub> is moved from ±4V to ±6V            | 60   | 70   |     | dB    |
| -IPSR             | -Input Current Power Supply Rejection | V <sub>S</sub> is moved from ±4V to ±6V            |      | 1    | 15  | μA/V  |
| R <sub>OL</sub>   | Transimpedance                        | V <sub>OUT</sub> = ±2.5V                           | 120  | 300  |     | kΩ    |
| +R <sub>IN</sub>  | +Input Resistance                     | V <sub>CM</sub> = ±3.5V                            | 0.5  | 2    |     | MΩ    |
| +C <sub>IN</sub>  | +Input Capacitance                    |                                                    |      | 1.2  |     | pF    |
| CMIR              | Common Mode Input Range               |                                                    | ±3.5 | ±4.0 |     | V     |
| V <sub>O</sub>    | Output Voltage Swing                  | V <sub>S</sub> = ±5                                | ±3.5 | ±4.0 |     | V     |
|                   |                                       | V <sub>S</sub> = +5 Single-supply, high            |      | 4.0  |     | V     |
|                   |                                       | V <sub>S</sub> = +5 Single-supply, low             |      | 0.3  |     | V     |
| I <sub>O</sub>    | Output Current                        | EL2180C only                                       | 80   | 100  |     | mA    |
|                   |                                       | EL2280C only, per amplifier                        | 50   | 55   |     | mA    |
|                   |                                       | EL2480C only, per amplifier                        | 50   | 55   |     | mA    |
| I <sub>S</sub>    | Supply Current                        | Per amplifier                                      |      | 3    | 6   | mA    |

## AC Electrical Characteristics

V<sub>S</sub> = ±5V, R<sub>F</sub> = R<sub>G</sub> = 750Ω for PDIP and SO packages, R<sub>F</sub> = R<sub>G</sub> = 560Ω for SOT23-5 package, R<sub>L</sub> = 150Ω, T<sub>A</sub> = 25°C unless otherwise specified

| Parameter                       | Description        | Conditions                                    | Min | Typ  | Max | Unit |
|---------------------------------|--------------------|-----------------------------------------------|-----|------|-----|------|
| -3dB BW                         | -3dB Bandwidth     | A <sub>V</sub> = +1                           |     | 250  |     | MHz  |
| -3dB BW                         | -3dB Bandwidth     | A <sub>V</sub> = +2                           |     | 180  |     | MHz  |
| 0.1dB BW                        | 0.1dB Bandwidth    | A <sub>V</sub> = +2                           |     | 50   |     | MHz  |
| SR                              | Slew Rate          | V <sub>OUT</sub> = ±2.5V, A <sub>V</sub> = +2 | 600 | 1200 |     | V/μs |
| t <sub>R</sub> , t <sub>F</sub> | Rise and Fall Time | V <sub>OUT</sub> = ±500 mV                    |     | 1.5  |     | ns   |

# EL2180C/EL2280C/EL2480C-Preliminary

## 250MHz / 3mA Current Mode Feedback Amplifiers

EL2180C/EL2280C/EL2480C-Preliminary




### AC Electrical Characteristics

$V_S = \pm 5V$ ,  $R_F = R_G = 750\Omega$  for PDIP and SO packages,  $R_F = R_G = 560\Omega$  for SOT23-5 package,  $R_L = 150\Omega$ ,  $T_A = 25^\circ C$  unless otherwise specified

| Parameter | Description        | Conditions                                    | Min | Typ  | Max | Unit |
|-----------|--------------------|-----------------------------------------------|-----|------|-----|------|
| $t_{PD}$  | Propagation Delay  | $V_{OUT} = \pm 500\text{ mV}$                 |     | 1.5  |     | ns   |
| OS        | Overshoot          | $V_{OUT} = \pm 500\text{ mV}$                 |     | 3.0  |     | %    |
| $t_s$     | 0.1% Settling      | $V_{OUT} = \pm 2.5V$ , $A_V = -1$             |     | 15   |     | ns   |
| dG        | Differential Gain  | $A_V = +2$ , $R_L = 150\Omega$ <sup>[1]</sup> |     | 0.05 |     | %    |
| dP        | Differential Phase | $A_V = +2$ , $R_L = 150\Omega$ <sup>[1]</sup> |     | 0.05 |     | °    |
| dG        | Differential Gain  | $A_V = +1$ , $R_L = 500\Omega$ <sup>[1]</sup> |     | 0.01 |     | %    |
| dP        | Differential Phase | $A_V = +1$ , $R_L = 500\Omega$ <sup>[1]</sup> |     | 0.01 |     | °    |
| CS        | Channel Separation | EL2280C, EL2480C only, $f = 5\text{ MHz}$     |     | 85   |     | dB   |

1. DC offset from 0V to 0.714V, AC amplitude 286mV<sub>P-P</sub>,  $f = 3.58\text{MHz}$


### Connection Diagrams (Continued)



# **EL2180C/EL2280C/EL2480C-Preliminary**


250MHz / 3mA Current Mode Feedback Amplifiers

## **Test Circuit (Per Amplifier)**



\* Note: EL2180C or  
1/2 EL2280C or  
1/4 EL2480C

## **Simplified Schematic (Per Amplifier)**












# EL2180C/EL2280C/EL2480C-Preliminary

## 250MHz / 3mA Current Mode Feedback Amplifiers










EL2180C/EL2280C/EL2480C-Preliminary

### Typical Performance Curves



# **EL2180C/EL2280C/EL2480C-Preliminary** 250MHz / 3mA Current Mode Feedback Amplifiers

## **Typical Performance Curves**












# EL2180C/EL2280C/EL2480C-Preliminary

## 250MHz / 3mA Current Mode Feedback Amplifiers




EL2180C/EL2280C/EL2480C-Preliminary

### Typical Performance Curves




# **EL2180C/EL2280C/EL2480C-Preliminary** 250MHz / 3mA Current Mode Feedback Amplifiers





## **Typical Performance Curves**



**Small-Signal Step Response**



**Large-Signal Step Response**











# EL2180C/EL2280C/EL2480C-Preliminary

## 250MHz / 3mA Current Mode Feedback Amplifiers

EL2180C/EL2280C/EL2480C-Preliminary

### Typical Performance Curves



# ***EL2180C/EL2280C/EL2480C-Preliminary***

***250MHz / 3mA Current Mode Feedback Amplifiers***

## **Applications Information**

### **Product Description**

The EL2180C/EL2280C/EL2480C are current-feedback operational amplifiers that offer a wide -3dB bandwidth of 250MHz and a low supply current of 3mA per amplifier. All of these products also feature high output current drive. The EL2180C can output 100mA, while the EL2280C and the EL2480C can output 55mA per amplifier. The EL2180C/EL2280C/EL2480C work with supply voltages ranging from a single 3V to  $\pm 6V$  and they are also capable of swinging to within 1V of either supply on the input and the output. Because of their current-feedback topology, the EL2180C/EL2280C/EL2480C do not have the normal gain-bandwidth product associated with voltage-feedback operational amplifiers. This allows their -3dB bandwidth to remain relatively constant as closed-loop gain is increased. This combination of high bandwidth and low power, together with aggressive pricing make the EL2180C/EL2280C/EL2480C the ideal choice for many low-power/high-bandwidth applications such as portable computing, HDSL, and video processing.

For applications where board space is extremely critical, the EL2180C is available in the tiny 5-pin SOT23 package, which has a footprint 28% the size of an 8-pin SO. The EL2480C is available in the 24-pin LPP package, offering board space savings and better power dissipation compared to the SO and PDIP packages. The EL2180C/EL2280C/EL2480C are each also available in industry-standard pinouts in PDIP and SO packages.

For single, dual, and triple applications with disable, consider the EL2186C (8-pin single), EL2286C (14-pin dual), and EL2386C (16-pin triple). If lower power is required, refer to the EL2170C/EL2176C family which provides singles, duals, and quads with 70MHz of bandwidth while consuming 1mA of supply current per amplifier.

### **Power Supply Bypassing and Printed Circuit Board Layout**

As with any high-frequency device, good printed circuit board layout is necessary for optimum performance. Ground plane construction is highly recommended. Lead lengths should be as short as possible. The power

supply pins must be well bypassed to reduce the risk of oscillation. The combination of a 4.7 $\mu F$  tantalum capacitor in parallel with a 0.1 $\mu F$  capacitor has been shown to work well when placed at each supply pin.

For good AC performance, parasitic capacitance should be kept to a minimum especially at the inverting input (see the Capacitance at the Inverting Input section). Ground plane construction should be used, but it should be removed from the area near the inverting input to minimize any stray capacitance at that node. Carbon or Metal-Film resistors are acceptable with the Metal-Film resistors giving slightly less peaking and bandwidth because of their additional series inductance. Use of sockets, particularly for the SO package, should be avoided if possible. Sockets add parasitic inductance and capacitance which will result in some additional peaking and overshoot.

### **Capacitance at the Inverting Input**

Any manufacturer's high-speed voltage- or current-feedback amplifier can be affected by stray capacitance at the inverting input. For inverting gains this parasitic capacitance has little effect because the inverting input is a virtual ground, but for non-inverting gains this capacitance (in conjunction with the feedback and gain resistors) creates a pole in the feedback path of the amplifier. This pole, if low enough in frequency, has the same destabilizing effect as a zero in the forward open-loop response. The use of large value feedback and gain resistors further exacerbates the problem by further lowering the pole frequency.

The experienced user with a large amount of PC board layout experience may find in rare cases that the EL2180C/EL2280C/EL2480C have less bandwidth than expected.

The reduction of feedback resistor values (or the addition of a very small amount of external capacitance at the inverting input, e.g. 0.5pF) will increase bandwidth as desired. Please see the curves for Frequency Response for Various  $R_F$  and  $R_G$ , and Frequency Response for Various  $C_{IN}$ .

# ***EL2180C/EL2280C/EL2480C-Preliminary***

## ***250MHz / 3mA Current Mode Feedback Amplifiers***

EL2180C/EL2280C/EL2480C-Preliminary

### **Feedback Resistor Values**

The EL2180C/EL2280C/EL2480C have been designed and specified at gains of +1 and +2 with  $R_F = 750\Omega$  in PDIP and SO packages and  $R_F = 560\Omega$  in 5-pin SOT23 package. These values of feedback resistors give 250MHz of -3dB bandwidth at  $A_V = +1$  with about 2.5dB of peaking, and 180MHz of -3dB bandwidth at  $A_V = +2$  with about 0.1dB of peaking. The 5-pin SOT23 package is characterized with a smaller value of feedback resistor, for a given bandwidth, to compensate for lower parasitics within both the package itself and the printed circuit board where it will be placed. Since the EL2180C/EL2280C/EL2480C are current-feedback amplifiers, it is also possible to change the value of  $R_F$  to get more bandwidth. As seen in the curve of Frequency Response For Various  $R_F$  and  $R_G$ , bandwidth and peaking can be easily modified by varying the value of the feedback resistor.

Because the EL2180C/EL2280C/EL2480C are current-feedback amplifiers, their gain-bandwidth product is not a constant for different closed-loop gains. This feature actually allows the EL2180C/EL2280C/EL2480C to maintain about the same -3dB bandwidth, regardless of closed-loop gain. However, as closed-loop gain is increased, bandwidth decreases slightly while stability increases. Since the loop stability is improving with higher closed-loop gains, it becomes possible to reduce the value of  $R_F$  below the specified 560 $\Omega$  and 750 $\Omega$  and still retain stability, resulting in only a slight loss of bandwidth with increased closed-loop gain.

### **Supply Voltage Range and Single-Supply Operation**

The EL2180C/EL2280C/EL2480C have been designed to operate with supply voltages having a span of greater than 3V, and less than 12V. In practical terms, this means that the EL2180C/EL2280C/EL2480C will operate on dual supplies ranging from  $\pm 1.5V$  to  $\pm 6V$ . With a single-supply, the EL2180C/EL2280C/EL2480C will operate from +3V to +12V.

As supply voltages continue to decrease, it becomes necessary to provide input and output voltage ranges that can get as close as possible to the supply voltages. The EL2180C/EL2280C/EL2480C have an input voltage range that extends to within 1V of either supply. So, for

example, on a single +5V supply, the EL2180C/EL2280C/EL2480C have an input range which spans from 1V to 4V. The output range of the EL2180C/EL2280C/EL2480C is also quite large, extending to within 1V of the supply rail. On a  $\pm 5V$  supply, the output is therefore capable of swinging from -4V to +4V. Single-supply output range is even larger because of the increased negative swing due to the external pull-down resistor to ground. On a single +5V supply, output voltage range is about 0.3V to 4V.

### **Video Performance**

For good video performance, an amplifier is required to maintain the same output impedance and the same frequency response as DC levels are changed at the output. This is especially difficult when driving a standard video load of 150 $\Omega$ , because of the change in output current with DC level. Until the EL2180C/EL2280C/EL2480C, good Differential Gain could only be achieved by running high idle currents through the output transistors (to reduce variations in output impedance). These currents were typically comparable to the entire 3mA supply current of each EL2180C/EL2280C/EL2480C amplifier! Special circuitry has been incorporated in the EL2180C/EL2280C/EL2480C to reduce the variation of output impedance with current output. This results in dG and dP specifications of 0.05% and 0.05° while driving 150 $\Omega$  at a gain of +2.

Video Performance has also been measured with a 500 $\Omega$  load at a gain of +1. Under these conditions, the EL2180C/EL2280C/EL2480C have dG and dP specifications of 0.01% and 0.01° respectively while driving 500 $\Omega$  at  $A_V = +1$ .

### **Output Drive Capability**

In spite of its low 3mA of supply current, the EL2180C is capable of providing a minimum of  $\pm 80mA$  of output current. Similarly, each amplifier of the EL2280C and the EL2480C is capable of providing a minimum of  $\pm 50mA$ . These output drive levels are unprecedented in amplifiers running at these supply currents. With a minimum  $\pm 80mA$  of output drive, the EL2180C is capable of driving 50 $\Omega$  loads to  $\pm 4V$ , making it an excellent choice for driving isolation transformers in telecommunications applications. Similarly, the  $\pm 50mA$  minimum

## EL2180C/EL2280C/EL2480C-Preliminary

250MHz / 3mA Current Mode Feedback Amplifiers

output drive of each EL2280C and EL2480C amplifier allows swings of  $\pm 2.5V$  into  $50\Omega$  loads.

### Driving Cables and Capacitive Loads

When used as a cable driver, double termination is always recommended for reflection-free performance. For those applications, the back-termination series resistor will decouple the EL2180C/EL2280C/EL2480C from the cable and allow extensive capacitive drive. However, other applications may have high capacitive loads without a back-termination resistor. In these applications, a small series resistor (usually between  $5\Omega$  and  $50\Omega$ ) can be placed in series with the output to eliminate most peaking. The gain resistor ( $R_G$ ) can then be chosen to make up for any gain loss which may be created by this additional resistor at the output. In many cases it is also possible to simply increase the value of the feedback resistor ( $R_F$ ) to reduce the peaking.

### Current Limiting

The EL2180C/EL2280C/EL2480C have no internal current-limiting circuitry. If any output is shorted, it is possible to exceed the Absolute Maximum Ratings for output current or power dissipation, potentially resulting in the destruction of the device.

### Power Dissipation

With the high output drive capability of the EL2180C/EL2280C/EL2480C, it is possible to exceed the  $150^\circ C$  Absolute Maximum junction temperature under certain very high load current conditions. Generally speaking, when  $R_L$  falls below about  $25\Omega$ , it is important to calculate the maximum junction temperature ( $T_{JMAX}$ ) for the application to determine if power-supply voltages, load conditions, or package type need to be modified for the EL2180C/EL2280C/EL2480C to remain in the safe operating area. These parameters are calculated as follows:

$$T_{JMAX} = T_{MAX} + (\theta_{JA} \times n \times PD_{MAX})$$

where:

$T_{MAX}$  = Maximum Ambient Temperature

$\theta_{JA}$  = Thermal Resistance of the Package

$n$  = Number of Amplifiers in the Package

$PD_{MAX}$  = Maximum Power Dissipation of Each Amplifier in the Package

$PD_{MAX}$  for each amplifier can be calculated as follows:

$$PD_{MAX} = (2 \times V_S \times I_{SMAX}) + (V_S - V_{OUTMAX}) \times \frac{V_{OUTMAX}}{R_L}$$

where:

$V_S$  = Supply Voltage

$I_{SMAX}$  = Maximum Supply Current of 1 Amplifier

$V_{OUTMAX}$  = Maximum Output Voltage of the Application

$R_L$  = Load Resistance

# EL2180C/EL2280C/EL2480C-Preliminary

250MHz / 3mA Current Mode Feedback Amplifiers

EL2180C/EL2280C/EL2480C-Preliminary

## Typical Application Circuits





Figure 1. Inverting 200mA Output Current Distribution Amplifier




\* Note: 1/2 EL2280C or  
1/4 EL2480C

Figure 2. Fast-Settling Precision Amplifier

# **EL2180C/EL2280C/EL2480C-Preliminary**

250MHz / 3mA Current Mode Feedback Amplifiers

## **Typical Application Circuits (Continued)**



\* Note: EL2180 or  
 ½ EL2280C or  
 ¼ EL2480C

**Figure 3. Differential Line Driver/Receiver**

### 250MHz / 3mA Current Mode Feedback Amplifiers

## EL2180C/EL2280C/EL2480C Macromodel

```


* EL2180 Macromodel
* Revision A, March 1995
* AC characteristics used: Rf = Rg = 750 ohms
* Connections:      +input
*                   |
*                   | -input
*                   |
*                   | +Vsupply
*                   |
*                   | -Vsupply
*                   |
*                   | output
*                   |
* .subckt EL2180/el 3      2      7      4      6
*
* Input Stage
*
e1 10 0 3 0 1.0
vis 10 9 0V
h2 9 12 vxx 1.0
r1 2 11 400
l1 11 12 25nH
iinp 3 0 1.5uA
iinm 2 0 3uA
r12 3 0 2Meg
*
* Slew Rate Limiting
*
h1 13 0 vis 600
r2 13 14 1K
d1 14 0 dclamp
d2 0 14 dclamp
*
* High Frequency Pole
*
e2 30 0 14 0 0.001666666666
l3 30 17 150nH
c5 17 0 0.8pF
r5 17 0 165
*
* Transimpedance Stage
*
g1 0 18 17 0 1.0
rol 18 0 450K
cdp 18 0 0.675pF
*
* Output Stage
*
q1 4 18 19 qp
q2 7 18 20 qn
q3 7 19 21 qn
q4 4 20 22 qp
r7 21 6 4
r8 22 6 4
ios1 7 19 1mA
ios2 20 4 1mA
*
* Supply Current
*
ips 7 4 0.2mA
*
* Error Terms
*
ivos 0 23 0.2mA
vxx 23 0 0V
e4 24 0 3 0 1.0

```

# EL2180C/EL2280C/EL2480C-Preliminary

250MHz / 3mA Current Mode Feedback Amplifiers

```
e5 25 0 7 0 1.0
e6 26 0 4 0 -1.0
r9 24 23 316
r10 25 23 3.2K
r11 26 23 3.2K
*
* Models
*
.model qn npn(is=5e-15 bf=200 tf=0.01nS)
*.model qp pnp(is=5e-15 bf=200 tf=0.01nS)
.model dclamp d(is=1e-30 ibv=0.266
+ bv=0.71v n=4)
.ends
```



***EL2180C/EL2280C/EL2480C-Preliminary******250MHz / 3mA Current Mode Feedback Amplifiers*****General Disclaimer**

Specifications contained in this data sheet are in effect as of the publication date shown. Elantec, Inc. reserves the right to make changes in the circuitry or specifications contained herein at any time without notice. Elantec, Inc. assumes no responsibility for the use of any circuits described herein and makes no representations that they are free from patent infringement.

***élantec***  
HIGH PERFORMANCE ANALOG INTEGRATED CIRCUITS
**Elantec Semiconductor, Inc.**

675 Trade Zone Blvd.  
 Milpitas, CA 95035  
 Telephone: (408) 945-1323  
                   (888) ELANTEC  
 Fax: (408) 945-9305  
 European Office: +44-118-977-6020  
 Japan Technical Center: +81-45-682-5820

**WARNING - Life Support Policy**

Elantec, Inc. products are not authorized for and should not be used within Life Support Systems without the specific written consent of Elantec, Inc. Life Support systems are equipment intended to support or sustain life and whose failure to perform when properly used in accordance with instructions provided can be reasonably expected to result in significant personal injury or death. Users contemplating application of Elantec, Inc. Products in Life Support Systems are requested to contact Elantec, Inc. factory headquarters to establish suitable terms & conditions for these applications. Elantec, Inc.'s warranty is limited to replacement of defective components and does not cover injury to persons or property or other consequential damages.