


Valpey Fisher VF315

- Industry Standard Footprint
- Competitive Prices
- Industrial Temperature Range Available
- Output Enable



Parameter	VF315	Notes
Frequency Range	1.50MHz to 70.0MHz	
Frequency Stability	+/-100ppm (C) +/-50ppm (B) +/-25ppm (A)	Standard Option Option
Supply Voltage	5V +/-5% 3.3V +/-5%	Standard Option
Supply Current	16mA 22mA 32mA 56mA	No Load
Load	10TTL gates or 50pF	
Duty Cycle	40 / 60 45/55	Standard Option
Rise & Fall Times	5nS max	
Logic "1" Level	0.9Vcc min	
Logic "0" Level	0.1Vcc max	
Tri-state Function	Input HIGH (>2.5V) or floating ACTIVE Input LOW (<0.5V) INFINITE IMPEDANCE	
Start-up Time	10mS max	2mS Typ
Operating Temp	-10°C to +70°C (-45° to +85°C) Available	

Environmental & Mechanical	
Mechanical Shock	Mil STD 202 Method 213 Cond E
Thermal Shock	Mil STD 883 Method 1011 Cond A
Vibration	MIL-STD-883 Method 2007 Cond A
Soldering Condition	260°C for 10s max: 230°C for 90s max
Hermetic Seal	Leak rate less than 5x10 ⁻⁸ Atm.cc/s of helium



Part Numbering : VF315P H L 6.0M A 1

Type _____
Duty Cycle H=45/55
Blank = Standard
Supply Voltage
L=3.3V Blank =5.0V
Frequency
Stability
A=25ppm B=50ppm C=100ppm
Temperature Range
1= -40°C to +85°C Blank = Standard

Pin	1	2	3	4
Function	Tristate	GND/ Case	O/P	Vcc

A	B	C	D	E	F	G
14.22	9.80	4.70	8.65	5.08	5.08	1.52

H	J	K	L
3.00	5.80	1.27	3.81

Dimensions in mm

ECM Electronics Limited, Penmaen House, Ashington, West Sussex, RH20 3JR, UK
Tel: +44(0)1903 892810: Fax: +44(0)1903 892738. Email: ecm@ecmelectronics.co.uk

Although we have attempted to accurately reflect the products we market. ECM reserve the right without prior notice to discontinue any product or make design changes we believe necessary.