

SOUND IF AMPLIFIER


- QUADRATURE INTERCARRIER DEMODULATOR
- VERY HIGH INPUT SENSITIVITY
- GOOD SIGNAL TO NOISE RATIO
- FAST AVERAGING AGC
- IF AMPLIFIER CAN BE SWITCHED OFF FOR VTR MODE
- GOOD AM SUPPRESSION
- OUTPUT SIGNAL STABILIZED AGAINST SUPPLY VOLTAGE VARIATIONS
- VERY FEW EXTERNAL COMPONENTS

DESCRIPTION

TDA4445A:
Sound IF amplifier, with FM processing for quasi parallel sound system.

TDA4445B:
Sound IF amplifier, with FM processing and AM demodulator, for multi-standard sound TV appliances.


TDA4445B additionnal :
Bistandard applications (B/G and L)
No adjustment of the AM demodulator
Low AM distortion



DIP16
(Plastic Package)


ORDER CODE : TDA4445A - TDA4445B

PIN CONNECTIONS



4445-01EPS

BLOCK DIAGRAMS



4445-02.EPS / 4445-03.EPS

GENERAL DESCRIPTION

This circuit includes the following functions :

- Three symmetrical and gain controlled wide band amplifier stages, which are extremely stable by quasi DC coupling without feedback.
- Averaging AGC with discharge control circuit
- AGC voltage generator

Quasi parallel sound operation :

- High phase accuracy of the carrier signal processing, independent from AM

essing, independent from AM

- Linear quadrature demodulator
- Sound-IF-amplifier stage with impedance converter

AM-Demodulation (only TDA4445B) :

- Carrier controlled demodulator
- Audio frequency stage with impedance converter
- Averaging low pass AGC

ABSOLUTE MAXIMUM RATINGS

Symbol	Parameter	Value	Unit
V_{CC}	Supply Voltage Range Pin 11	15	V
I_{CC}	Supply Current Pin 11	70	mA
V_{ext}	External Voltages Pin 3 Pin 12	12 8	V V
V_{ext}	External Voltages TDA4445A - TDA4445B TDA4445B Pin 5 Pin 6	8 8	V V
P_{tot}	Power Dissipation	1	W
T_j	Junction Temperature	125	°C
T_{amb}	Ambient Temperature Range	0, + 70	°C
T_{stg}	Storage Temperature Range	- 25, + 125	°C

4445-01.TBL

THERMAL DATA

Symbol	Parameter	Value	Unit
$R_{th(j-a)}$	Junction-ambient Thermal Resistance	70	°C/W

4445-02.TBL

ELECTRICAL OPERATING CHARACTERISTICS

 $T_{amb} = + 25^{\circ}\text{C}$, $V_{CC} = 12\text{V}$ (unless otherwise specified)

Symbol	Parameter	Min.	Typ.	Max.	Unit
--------	-----------	------	------	------	------

DC CHARACTERISTICS

V_{CC}	Supply Voltage Pin 13	10	12	15	V
I_{CC}	Supply Current ($V_3 = 3.5\text{V}$) Pin 11		45	60	mA
V_O	DC Output Voltage ($V_3 = 3.5\text{V}$) Pin 12	4.25	5	5.75	V
I	Output DC Current ($V_3 = 3.5\text{V}$, $V_{11} = 12\text{V}$) Pin 12	1		2	mA
R	Input Impedance Pins 1-16		2		k Ω
C	Input Impedance Pins 1-16		2		pF
V	Switch off Control Voltage for VTR Mode Pin 3	9		10	V
I	Switch off Control Current for VTR Mode Pin 3			150	μA

AGC CHARACTERISTICS

Δ_{GIF}	IF AGC Range		62		dB
----------------	--------------	--	----	--	----

QUASI PARALLEL SOUND OPERATION

 $(f_{PC} = 38.9\text{MHz}$, $f_{SC1} = 33.4\text{MHz}$, $f_{SC2} = 33.16\text{MHz}$, $PC/SC_1 = 13\text{dB}$, $PC/SC_2 = 20\text{dB}$, PC unmodulated)

V_i	Min. Input Voltage (5.5MHz - Output Signal - 3dB) Pins 1-16		70		μV_{eff}
V_i	Max. Input Voltage (5.5MHz - Output Signal + 1dB) Pins 1-16		90		mV_{eff}
V_O	Sound-IF-output Voltage ($V_{1-16} = 20\text{mV}_{eff}$ SC unmodulated) 5.5MHz Output Voltage 5.74MHz Output Voltage Pin 12	200 100		400 300	mV_{eff} mV_{eff}
$\frac{S+N}{N}$	Signal to noise ratio measured according to CCIR 468-2 Picture Modulation Ratio 90%, Reference signal ($V_{1-16} = 10\text{mV}$), FM-frequency deviation 30kHz $\rightarrow$ Out 1 350mVRMS $f_{mod} = 1\text{kHz}$, measured at audio-output Out 2 350mVRMS Pin 12				
	Black Screen (1. Channel/2. Channel) Grid Screen (1. Channel/2. Channel)		55/50 45/40		dB dB


AM DEMODULATION (TDA4445B only) ($f_{SC} = 39.2\text{MHz}$, $m = 80\%$, $f_{mod} = 1\text{kHz}$)

V_i	Min. Input Voltage (Audio Output Signal - 3dB) Pins 1-16		70		μV_{eff}
V_O	Output DC Voltage ($V_{1-16} = 10\text{mV}_{eff}$ unmodulated) Pin 6	3.3		4.5	V
I	Output DC Current ($V_6 = 7.5\text{V}$, $V_3 = 3.5\text{V}$) Pin 6	0.3		1.2	mA
d	Distortion ($V_{1-16} = 10\text{mV}$, $f_{mod} = 1\text{kHz}$, $m = 80\%$) Pin 6		2.5	4	%
V_O	AF Output Voltage ($V_{1-16} = 100\text{mV}_{eff}$, $m = 50\%$, $f_{mod} = 10\text{kHz}$) Pin 6	500	700	900	mV_{eff}

4445-03.TBL

TYPICAL APPLICATION


Figure 1 : Quasi Parallel Sound Operation



4445-04.TIF

TYPICAL APPLICATION

Figure 2 : Bistandard Operation (FM stereo sound + AM sound)




4445-05.TIF

TDA4445A - TDA4445B

PACKAGE MECHANICAL DATA

16 PINS - PLASTIC DIP



PM-DIP16.EPS

Dimensions	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
a1	0.51			0.020		
B	0.77		1.65	0.030		0.065
b		0.5			0.020	
b1		0.25			0.010	
D			20			0.787
E		8.5			0.335	
e		2.54			0.100	
e3		17.78			0.700	
F			7.1			0.280
i			5.1			0.201
L		3.3			0.130	
Z			1.27			0.050

DIP16.TBL

Information furnished is believed to be accurate and reliable. However, SGS-THOMSON Microelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No licence is granted by implication or otherwise under any patent or patent rights of SGS-THOMSON Microelectronics. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. SGS-THOMSON Microelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of SGS-THOMSON Microelectronics.

© 1994 SGS-THOMSON Microelectronics - All Rights Reserved

Purchase of I²C Components of SGS-THOMSON Microelectronics, conveys a license under the Philips I²C Patent. Rights to use these components in a I²C system, is granted provided that the system conforms to the I²C Standard Specifications as defined by Philips.

SGS-THOMSON Microelectronics GROUP OF COMPANIES

Australia - Brazil - China - France - Germany - Hong Kong - Italy - Japan - Korea - Malaysia - Malta - Morocco
The Netherlands - Singapore - Spain - Sweden - Switzerland - Taiwan - Thailand - United Kingdom - U.S.A.