





Rectifiers, General Purpose

1.0 to 250 Amperes

50 to 1600 Volts

I_O (AMPS)	1.0				
@ T_A (°C)	75	75	75	55	100
I_{FSM} (AMPS)	30	50	50	50	50
CASE	 GPR-1A	 DO-41*		 GPR-1A	 DO-41 Glass
V_{RRM} (VOLTS)					
50		1N4001	1N4001GPP**		
100		1N4002	1N4002GPP**		
200	1N3611	1N4003	1N4003GPP**	1N4245	1N4383
400	1N3612	1N4004	1N4004GPP**	1N4246	1N4384
600	1N3613	1N4005	1N4005GPP**	1N4247	1N4385
800	1N3614	1N4006	1N4006GPP**	1N4248	1N4585
1000	1N3957	1N4007	1N4007GPP**	1N4249	1N4586

V_F MAX @ $I_F=I_O$	1.1V	1.1V	1.1V	1.2V	1.1V
-----------------------	------	------	------	------	------

I_R MAX @ V_{RRM}	1.0 μ A	5.0 μ A	5.0 μ A	1.0 μ A	10 μ A
-----------------------	-------------	-------------	-------------	-------------	------------

* Also available in DO-41SP Case (0.6mm lead diameter) with Radial Tape and Reel (DO-41SP-RPCU), See pages 239 thru 240.

** Device utilizes glass passivated chip for high reliability.

Central
Semiconductor Corp.

www.centrasemi.com