

CentralTM Semiconductor Corp.

145 Adams Avenue, Hauppauge, NY 11788 USA

Tel: (631) 435-1110 • Fax: (631) 435-1824

Manufacturers of World Class Discrete Semiconductors

2N5771
PN5910

2N5910

JEDEC TO-92

JEDEC TO-106

PNP SILICON SWITCHING TRANSISTORS

DESCRIPTION

The CENTRAL SEMICONDUCTOR 2N5771, 2N/PN5910 Series types are Silicon PNP Transistors designed for ultra high speed switching applications.

MAXIMUM RATINGS ($T_A=25^{\circ}\text{C}$)

	SYMBOL	2N5771	2N/PN5910	UNIT
Collector-Base Voltage	V_{CB0}	15	-	V
Collector-Emitter Voltage	V_{CES}	-	20	V
Collector-Emitter Voltage	V_{CEO}	15	20	V
Emitter-Base Voltage	V_{EBO}	4.5	4.5	V
Collector Current	I_C	50	50	mA
		<u>2N5771/PN5910</u>	<u>2N5910</u>	
Power Dissipation	P_D	625	310	mW
Operating and Storage				
Junction Temperature	T_J, T_{stg}	-65 TO +150		$^{\circ}\text{C}$

ELECTRICAL CHARACTERISTICS ($T_A=25^{\circ}\text{C}$)

SYMBOL	TEST CONDITIONS	2N5771		2N/PN5910		UNIT
		MIN	MAX	MIN	MAX	
I_{CBO}	$V_{CB}=8.0\text{V}$		10	-		nA
I_{CES}	$V_{CE}=8.0\text{V}$		10	-		nA
I_{CES}	$V_{CE}=10\text{V}$		-	10		nA
I_{EBO}	$V_{EB}=4.5\text{V}$		1.0	-		μA
I_{EBO}	$V_{EB}=4.0\text{V}$		-	100		μA
I_B	$V_{CE}=6.0\text{V}, V_{EB}=0$		-	10		nA
BV_{CBO}	$I_C=100\mu\text{A}$	15		20		V
BV_{CES}	$I_C=100\mu\text{A}$	15		20		V
BV_{CEO}	$I_C=3.0\text{mA}$	15		20		V
BV_{EBO}	$I_E=100\mu\text{A}$	4.5		4.5		V
$V_{CE}(\text{SAT})$	$I_C=1.0\text{mA}, I_B=0.1\text{mA}$		0.15		-	V
$V_{CE}(\text{SAT})$	$I_C=10\text{mA}, I_B=1.0\text{mA}$		0.18		0.15	V
$V_{CE}(\text{SAT})$	$I_C=50\text{mA}, I_B=5.0\text{mA}$		0.6		0.5	V
$V_{BE}(\text{SAT})$	$I_C=1.0\text{mA}, I_B=0.1\text{mA}$		0.8		-	V
$V_{BE}(\text{SAT})$	$I_C=10\text{mA}, I_B=1.0\text{mA}$	0.8	0.95	0.75	0.95	V
$V_{BE}(\text{SAT})$	$I_C=50\text{mA}, I_B=5.0\text{mA}$		1.5		1.5	V
h_{FE}	$V_{CE}=0.5\text{V}, I_C=1.0\text{mA}$	35		15		-
h_{FE}	$V_{CE}=0.3\text{V}, I_C=10\text{mA}$	50	120	30	120	-
h_{FE}	$V_{CE}=1.0\text{V}, I_C=50\text{mA}$	40		30		-
f_T	$V_{CE}=10\text{V}, I_C=10\text{mA}, f=100\text{MHz}$	850		700		MHz
C_{cb}	$V_{CB}=5.0\text{V}, f=140\text{kHz}$		3.0		3.0	pF
C_{eb}	$V_{EB}=0.5\text{V}, f=140\text{kHz}$		3.5		3.5	pF
t_{on}	$I_C=10\text{mA}, I_{B1}=1.0\text{mA}$		15		15	ns
t_{off}	$I_C=10\text{mA}, I_{B1}=I_{B2}=1.0\text{mA}$		20		20	ns
τ_s	$I_C=10\text{mA}, I_{B1}=I_{B2}=10\text{mA}$		20		20	ns