


CXT2907A
SURFACE MOUNT
PNP SILICON TRANSISTOR



SOT-89 CASE

CentralTM
Semiconductor Corp.

DESCRIPTION:

The CENTRAL SEMICONDUCTOR CXT2907A type is an PNP silicon transistor manufactured by the epitaxial planar process, epoxy molded in a surface mount package, designed for small signal general purpose and switching applications.

MAXIMUM RATINGS ($T_A=25^{\circ}\text{C}$)

	SYMBOL		UNITS
Collector-Base Voltage	V_{CBO}	60	V
Collector-Emitter Voltage	V_{CEO}	60	V
Emitter-Base Voltage	V_{EBO}	5.0	V
Collector Current	I_C	600	mA
Power Dissipation	P_D	1.2	W
Operating and Storage Junction Temperature	T_J, T_{stg}	-65 to +150	$^{\circ}\text{C}$
Thermal Resistance	θ_{JA}	104	$^{\circ}\text{C/W}$

ELECTRICAL CHARACTERISTICS ($T_A=25^{\circ}\text{C}$ unless otherwise noted)

SYMBOL	TEST CONDITIONS	MIN	MAX	UNITS
I_{CBO}	$V_{CB}=50\text{V}$		10	nA
I_{CBO}	$V_{CB}=50\text{V}, T_A=125^{\circ}\text{C}$		10	μA
I_{CEV}	$V_{CE}=30\text{V}, V_{BE}=0.5\text{V}$		50	nA
BV_{CBO}	$I_C=10\text{mA}$	60		V
BV_{CEO}	$I_C=10\text{mA}$	60		V
BV_{EBO}	$I_E=10\text{mA}$	5.0		V
$V_{CE(SAT)}$	$I_C=150\text{mA}, I_B=15\text{mA}$		0.4	V
$V_{CE(SAT)}$	$I_C=500\text{mA}, I_B=50\text{mA}$		1.6	V
$V_{BE(SAT)}$	$I_C=150\text{mA}, I_B=15\text{mA}$		1.3	V
$V_{BE(SAT)}$	$I_C=500\text{mA}, I_B=50\text{mA}$		2.6	V
h_{FE}	$V_{CE}=10\text{V}, I_C=0.1\text{mA}$	75		
h_{FE}	$V_{CE}=10\text{V}, I_C=1.0\text{mA}$	100		
h_{FE}	$V_{CE}=10\text{V}, I_C=10\text{mA}$	100		
h_{FE}	$V_{CE}=10\text{V}, I_C=150\text{mA}$	100	300	


R3 (19-December 2001)

**SURFACE MOUNT
PNP SILICON TRANSISTOR**

ELECTRICAL CHARACTERISTICS (Continued)

SYMBOL	TEST CONDITIONS	MIN	MAX	UNITS
h_{FE}	$V_{CE}=10V$, $I_C=500mA$	50		
f_T	$V_{CE}=20V$, $I_C=50mA$, $f=100MHz$	200		MHz
C_{ob}	$V_{CB}=10V$, $I_E=0$, $f=1.0MHz$		8.0	pF
C_{ib}	$V_{BE}=2.0V$, $I_C=0$, $f=1.0MHz$		30	pF
t_{on}	$V_{CC}=30V$, $V_{BE}=0.5$, $I_C=150mA$, $I_{B1}=15mA$		45	ns
t_d	$V_{CC}=30V$, $V_{BE}=0.5$, $I_C=150mA$, $I_{B1}=15mA$		10	ns
t_r	$V_{CC}=30V$, $V_{BE}=0.5$, $I_C=150mA$, $I_{B1}=15mA$		40	ns
t_{off}	$V_{CC}=6.0V$, $I_C=150mA$, $I_{B1}=I_{B2}=15mA$		100	ns
t_s	$V_{CC}=6.0V$, $I_C=150mA$, $I_{B1}=I_{B2}=15mA$		80	ns
t_f	$V_{CC}=6.0V$, $I_C=150mA$, $I_{B1}=I_{B2}=15mA$		30	ns

SOT-89 CASE - MECHANICAL OUTLINE



BOTTOM VIEW

LEAD CODE:

- 1) EMITTER
- 2) COLLECTOR
- 3) BASE

DIMENSIONS				
SYMBOL	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	0.055	0.067	1.40	1.70
B	4°		4°	
C	0.016	0.018	0.40	0.46
D	0.173	0.185	4.40	4.70
E	0.070	0.074	1.79	1.87
F	0.146	0.177	3.70	4.50
G	0.094	0.106	2.40	2.70
H	0.028	0.051	0.70	1.30
J	0.015	0.019	0.38	0.48
K	0.019	0.023	0.48	0.58
L	0.059		1.50	
M	0.118		3.00	

SOT-89 (REV: R3)