

# 1N6638US, 1N6642US, 1N6643US

## Features

- AVAILABLE IN AXIAL LEADED AND SURFACE MOUNT CONFIGURATIONS
- ULTRA FAST RECOVERY TIME
- VERY LOW CAPACITANCE
- METALLURGICALLY BONDED
- NON-CAVITY GLASS PACKAGE
- AVAILABLE AS JANTX AND JANTXV PER MIL-S-19500/578
- AVAILABLE AS JANS
- REPLACEMENTS FOR 1N4148, 1N4148-1, 1N4150, 1N4150-1, AND 1N914

## Maximum Ratings @ 25°C

| TYPE NUMBER | REVERSE VOLTAGE<br>$V_R$ | WORKING PEAK REVERSE VOLTAGE<br>$V_{RWM}$ | OPERATING CURRENT<br>$I_O$<br>(Note 1)<br>(mA) | PEAK FORWARD SURGE CURRENT<br>$I_{FSM}$<br>(Note 2)<br>(A) | $R_{\theta JL}$<br>$L = .375"$<br>(°C/W) | $R_{\theta JEC}$<br>(°C/W) | $T_{OP}$<br>$T_{stg}$<br>(°C) |
|-------------|--------------------------|-------------------------------------------|------------------------------------------------|------------------------------------------------------------|------------------------------------------|----------------------------|-------------------------------|
| 1N6638      | 150                      | 125                                       | 300                                            | 2.5                                                        | 160                                      | 50                         | -65 to +175                   |
| 1N6638US    | 150                      | 125                                       | 300                                            | 2.5                                                        | 160                                      | 50                         | -65 to +175                   |
| 1N6642      | 100                      | 75                                        | 300                                            | 2.5                                                        | 160                                      | 50                         | -65 to +175                   |
| 1N6642US    | 100                      | 75                                        | 300                                            | 2.5                                                        | 160                                      | 50                         | -65 to +175                   |
| 1N6643      | 75                       | 50                                        | 300                                            | 2.5                                                        | 160                                      | 50                         | -65 to +175                   |
| 1N6643US    | 75                       | 50                                        | 300                                            | 2.5                                                        | 160                                      | 50                         | -65 to +175                   |

Note 1: At maximum end cap temperature = 110°C for US suffix types. Derate at 4.6 mA/°C above end cap temperature = 110°C. Derate axial types at 3.0 mA/°C above ambient temperature = 25°C.

Note 2: Test pulse = 8.3ms, half sine wave.

## Electrical Characteristics @ 25°C

| TYPE<br>NUMBER | MAXIMUM<br>FORWARD<br>VOLTAGE<br>$V_F @ I_F$ |              | MAXIMUM D.C. REVERSE<br>CURRENT<br>$I_R$ |               |                    |                                     |
|----------------|----------------------------------------------|--------------|------------------------------------------|---------------|--------------------|-------------------------------------|
|                |                                              |              | $V_R=20V$                                | $V_R=V_{RWM}$ | $T_A=150^{\circ}C$ | $V_R=V_{RWM}$<br>$T_A=150^{\circ}C$ |
|                | $V @ mA$                                     |              | nA                                       | $\mu A$       | $\mu A$            | $\mu A$                             |
| 1N6638         | 0.8V @ 10mA                                  | 1.1V @ 200mA | 25                                       | 0.5           | 40                 | 100                                 |
| 1N6638US       | 0.8V @ 10mA                                  | 1.1V @ 200mA | 25                                       | 0.5           | 40                 | 100                                 |
| 1N6642         | 1.0V @ 10mA                                  | 1.2V @ 100mA | 25                                       | 0.5           | 50                 | 100                                 |
| 1N6642US       | 1.0V @ 10mA                                  | 1.2V @ 100mA | 25                                       | 0.5           | 50                 | 100                                 |
| 1N6643         | 1.0V @ 10mA                                  | 1.2V @ 100mA | 50                                       | 0.5           | 75                 | 160                                 |
| 1N6643US       | 1.0V @ 10mA                                  | 1.2V @ 100mA | 50                                       | 0.5           | 75                 | 160                                 |

| TYPE NUMBER | REVERSE RECOVERY TIME<br>$t_{rr}$<br>Note 1 | MAXIMUM FORWARD RECOVERY VOLTAGE AND TIME<br>$I_F = 50mA, t_F = 1ns$ |          | MAXIMUM JUNCTION CAPACITANCE<br>$f = 1MHz$<br>$V_{sig} = 50mV (p-p)$ |              |
|-------------|---------------------------------------------|----------------------------------------------------------------------|----------|----------------------------------------------------------------------|--------------|
|             |                                             | $V_{fr}$                                                             | $t_{fr}$ | $V_R = 0V$                                                           | $V_R = 1.5V$ |
|             | ns                                          | V                                                                    | ns       | pf                                                                   | pf           |
| 1N6638      | 4.5                                         | 5.0                                                                  | 20       | 2.0                                                                  | 1.4          |
| 1N6638US    | 4.5                                         | 5.0                                                                  | 20       | 2.0                                                                  | 1.4          |
| 1N6642      | 5.0                                         | 5.0                                                                  | 20       | 5.0                                                                  | 2.8          |
| 1N6642US    | 5.0                                         | 5.0                                                                  | 20       | 5.0                                                                  | 2.8          |
| 1N6643      | 6.0                                         | 5.0                                                                  | 20       | 5.0                                                                  | 2.8          |
| 1N6643US    | 6.0                                         | 5.0                                                                  | 20       | 5.0                                                                  | 2.8          |

NOTE 1: Reverse Recovery Time Test Conditions:

$I_F = I_R = 10mA$ ,  $I_{R(REC)} = 1.0mA$ ,  $C = 3pF$ ,  $R_L = 100 \text{ ohms}$




Figure 1B  
Package B  
Surface  
Mount

|   | Inch | MIN. | MAX.  | mm    | MIN. | MAX. |
|---|------|------|-------|-------|------|------|
| A | .165 | .185 | 4.191 | 4.699 |      |      |
| B | .019 | .028 | 0.483 | 0.711 |      |      |
| C | .003 | —    | 0.076 | —     |      |      |
| D | .070 | .075 | 1.778 | 1.905 |      |      |

# 1N6638, 1N6642, 1N6643

## COMPUTER SWITCHING DIODES




Figure 1A  
Package B  
Axial

## Mechanical Characteristics

### AXIAL LEADED DEVICES

**CASE:** Voidless Hermetically Sealed Hard Glass.

**LEAD MATERIAL:** Solder Dipped Copper Clad Steel.

**MARKING:** Body Painted, Alpha Numeric.

**POLARITY:** Cathode Band.

### SURFACE MOUNT DEVICES


**CASE:** Voidless Hermetically Sealed Hard Glass.

**END CAP MATERIAL:** Solid Silver.


**END CAP CONFIGURATION:** Square.

**POLARITY:** Cathode Dot on End Cap.


**1N6638US, 1N6642US, 1N6643US**  
**1N6638, 1N6642, 1N6643,**




**FIGURE 2**  
**1N6638 & US**  
Typical Forward Current  
vs Forward Voltage



**FIGURE 3**  
**1N6642, 1N6643, & US**  
Typical Forward Current  
vs Forward Voltage



**FIGURE 4**  
**1N6638, 1N6642, & US**  
Typical Reverse Current  
vs Reverse Voltage



**FIGURE 5**  
**1N6643 & US**  
Typical Reverse Current  
vs Reverse Voltage