

Schottky barrier diode

RB411D

●Applications

Low power rectification

For switching power supply


●Features

- 1) Small surface mounting type. (SMD3)
- 2) Low V_F . ($V_F=0.43V$ Typ. at 0.5A)
- 3) High reliability.


●Construction

Silicon epitaxial planar

●Circuit



●External dimensions (Units : mm)



●Absolute maximum ratings ($T_a = 25^\circ C$)

Parameter	Symbol	Limits	Unit
Peak reverse voltage	V_{RM}	40	V
DC reverse voltage	V_R	20	V
Mean rectifying current	I_o	0.5	A
Peak forward surge current *	I_{FSM}	3	A
Junction temperature	T_j	125	$^\circ C$
Storage temperature	T_{stg}	-40~+125	$^\circ C$

* 60Hz for 1 $\varnothing$

●Electrical characteristics ($T_a = 25^\circ C$)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Conditions
Forward voltage	V_{F1}	—	—	0.3	V	$I_F=10mA$
Forward voltage	V_{F2}	—	—	0.5	V	$I_F=500mA$
Reverse current	I_R	—	—	30	μA	$V_R=10V$
Capacitance between terminals	C_T	—	20	—	pF	$V_R=10V, f=1MHz$

Note) sensitive product handling required.

Diodes


●Electrical characteristic curves ($T_a = 25^\circ\text{C}$)

Fig. 1 Forward characteristics




Fig. 2 Reverse characteristics




Fig. 3 Capacitance between terminals characteristic