


Dual Series Schottky Barrier Diode

These Schottky barrier diodes are designed for high speed switching applications, circuit protection, and voltage clamping. Extremely low forward voltage reduces conduction loss. Miniature surface mount package is excellent for hand held and portable applications where space is limited.

- Extremely Fast Switching Speed
- Low Forward Voltage — 0.75 Volts (Typ)
@ $I_F = 10 \text{ mAdc}$

BAS70-04LT1



MAXIMUM RATINGS ($T_J = 150^\circ\text{C}$ unless otherwise noted)

Rating	Symbol	Value	Unit
Reverse Voltage	V_R	70	Volts
Forward Power Dissipation	P_F	225	mW
@ $T_A = 25^\circ\text{C}$ Derate above 25°C		1.8	mW/ $^\circ\text{C}$
Operating Junction and Storage Temperature Range	T_J, T_{stg}	-55 to +150	$^\circ\text{C}$

ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ unless otherwise noted)

Characteristic	Symbol	Min	Max	Unit
Reverse Breakdown Voltage ($I_R = 10 \mu\text{A}$)	$V_{(BR)R}$	70	—	Volts
Total Capacitance ($V_R = 1.0 \text{ V}$, $f = 1.0 \text{ MHz}$)	C_T	—	2.0	pF
Reverse Leakage ($V_R = 50 \text{ V}$)	I_R	—	0.1	μAdc
($V_R = 70\text{V}$)		—	10	
Forward Voltage ($I_F = 1.0 \text{ mAdc}$)	V_F	—	410	mVdc
Forward Voltage ($I_F = 10 \text{ mAdc}$)	V_F	—	750	mVdc
Forward Voltage ($I_F = 15 \text{ mAdc}$)	V_F	—	1.0	Vdc

BAS70-04LT1




Figure 1. Typical Forward Current




Figure 2. Reverse Current Versus Reverse Voltage




Figure 3. Typical Current