



# Dual Schottky Barrier Diode

## MMBD352WT1

These devices are designed primarily for UHF mixer applications but are suitable also for use in detector and ultra-fast switching circuits.

- Very Low Capacitance — Less Than 1.0 pF @ Zero Volts
- Low Forward Voltage — 0.5 Volts (Typ) @  $I_F = 10$  mA



### MAXIMUM RATINGS

| Rating                     | Symbol | Value | Unit     |
|----------------------------|--------|-------|----------|
| Continuous Reverse Voltage | $V_R$  | 7.0   | $V_{CC}$ |

### THERMAL CHARACTERISTICS

| Characteristic   | Symbol          | Max         | Unit                      |
|--|-----------------|-------------|---------------------------|
| Total Device Dissipation FR-5 Board <sup>(1)</sup><br>$T_A = 25^\circ\text{C}$<br>Derate above $25^\circ$                | $P_D$           | 200         | mW                        |
| Thermal Resistance, Junction to Ambient  | $R_{\theta JA}$ | 625         | $^\circ\text{C}/\text{W}$ |
| Total Device Dissipation<br>Alumina Substrate <sup>(2)</sup> $T_A = 25^\circ\text{C}$<br>Derate above $25^\circ\text{C}$ | $P_D$           | 300         | mW                        |
| Thermal Resistance, Junction to Ambient  | $R_{\theta JA}$ | 417         | $^\circ\text{C}/\text{W}$ |
| Junction and Storage Temperature   | $T_J, T_{stg}$  | -55 to +150 | $^\circ\text{C}$          |

### DEVICE MARKING

|                 |
|-----------------|
| MMBD352WT1 = M5 |
|-----------------|

### ELECTRICAL CHARACTERISTICS ( $T_A = 25^\circ\text{C}$ unless otherwise noted)



| Characteristic | Symbol | Min | Max | Unit |
|----------------|--------|-----|-----|------|
|----------------|--------|-----|-----|------|

### OFF CHARACTERISTICS

|   |       |   |            |               |
|---|-------|---|------------|---------------|
| Forward Voltage<br>( $I_F = 10$ mA dc)                                  | $V_F$ | — | 0.60       | V             |
| Reverse Voltage Leakage Current<br>( $V_R = 3.0$ V)<br>( $V_R = 7.0$ V) | $I_R$ | — | 0.25<br>10 | $\mu\text{A}$ |
| Capacitance<br>( $V_R = 0$ V, $f = 1.0$ MHz)                            | C     | — | 1.0        | pF            |

1. FR-5 =  $1.0 \times 0.75 \times 0.062$  in.

2. Alumina =  $0.4 \times 0.3 \times 0.024$  in. 99.5% alumina.

**MMBD352WT1**
**TYPICAL CHARACTERISTICS**

**Figure 1. Forward Voltage**

**Figure 2. Capacitance**