

a

2.5 V/3.3 V, 16 Bit, 2 Port  
Level Translator, Bus Switch

## Preliminary Technical Data

ADG3247

## FEATURES

175ps Propagation Delay through the switch

3.5  $\Omega$  Switch Connection between Ports

2.5 V/3.3 V Supply Operation

Selectable Level Shifting/Translation

Level Translation

3.3 V to 2.5 V

3.3 V to 1.8 V

2.5 V to 1.8 V

40 Lead 6 x 6mm Chip Scale and 38 Lead TSSOP  
Packages

## APPLICATIONS

3.3 V to 1.8 V Voltage Translation

3.3 V to 2.5 V Voltage Translation

2.5 V to 1.8 V Voltage Translation

Bus Switching


Bus Isolation

## GENERAL DESCRIPTION

The ADG3247 is a 2.5 V or 3.3 V 16 bit, 2 port digital switch. It is designed on our low voltage CMOS process which provides low power dissipation yet gives high switching speed and very low on resistance allowing inputs to be connected to the outputs without additional propagation delay or generating additional ground bounce noise.

The switches are enabled by means of the Bus Enable, (*BE*) input signal. These digital switches allow bi-directional signals to be switched when ON. In the OFF condition, signal levels up to the supplies are blocked. This device is ideal for applications requiring level translation. When operated from a 3.3 V supply, level translation from 3.3V inputs to 2.5V outputs is allowed. Similarly, if the device is operated from a 2.5 V supply and 2.5 V inputs are applied, the device will translate the outputs to 1.8 V. In addition to this, a level translating select pin (*SEL*) is included. When *SEL* is low,  $V_{CC}$  is reduced internally allowing for level translation between 3.3V inputs and 1.8V outputs. This makes the device suited to applications requiring level translation between different supplies, such as converter to DSP interfacing.

## FUNCTIONAL BLOCK DIAGRAM



## PRODUCT HIGHLIGHTS

1. 3.3 V or 2.5 V Supply Operation.
2. Extremely low Propagation Delay through switch.
3. 3.5  $\Omega$  Switches connect inputs to Outputs.
4. Level/Voltage Translation.
5. 40 Lead 6 x 6mm Chip Scale and 38 Lead TSSOP Packages

REV. PrC June 2002

Information furnished by Analog Devices is believed to be accurate and reliable. However, no responsibility is assumed by Analog Devices for its use, nor for any infringements of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Analog Devices.

One Technology Way, P.O. Box 9106, Norwood, MA 02062-9106, U.S.A.  
Tel: 781/329-4700 [www.analog.com](http://www.analog.com)  
Fax: 781/326-8703 Analog Devices, Inc., 2002

# PRELIMINARY TECHNICAL DATA

## ADG3247–SPECIFICATIONS<sup>1</sup>

( $V_{CC} = +2.3\text{ V to }+3.6\text{ V}$ ,  $GND = 0\text{ V}$ , All specifications  $T_{MIN}$  to  $T_{MAX}$  unless otherwise noted)

Parameter	Symbol	Conditions <sup>2</sup>	B Version			Units
			Min	Typ <sup>3</sup>	Max	
<b>DC ELECTRICAL CHARACTERISTICS</b>						
Input High Voltage	$V_{INH}$	$V_{CC} = 2.7\text{ V to }3.6\text{ V}$	2.0			V
	$V_{INH}$	$V_{CC} = 2.3\text{ V to }2.7\text{ V}$	1.7			V
Input Low Voltage	$V_{INL}$	$V_{CC} = 2.7\text{ V to }3.6\text{ V}$	-0.5		0.8	V
	$V_{INL}$	$V_{CC} = 2.3\text{ V to }2.7\text{ V}$	-0.5		0.7	V
Input Leakage Current	$I_I$	$0 \leq V_{IN} \leq 3.6\text{ V}$			$\pm 1$	$\mu\text{A}$
OFF State leakage Current	$I_{OZ}$	$0 \leq A, B \leq V_{CC}$		$\pm 0.001$	$\pm 1$	$\mu\text{A}$
ON State leakage Current		$0 \leq A, B \leq V_{CC}$		$\pm 0.001$	$\pm 1$	$\mu\text{A}$
Max Pass Voltage	$V_P$	$V_{IN} = V_{CC} = SEL = 3.3\text{ V}$ , $I_O = -5\mu\text{A}$	tbd	2.5	2.9	V
		$V_{IN} = V_{CC} = SEL = 2.5\text{ V}$ , $I_O = -5\mu\text{A}$		1.8		V
		$V_{IN} = V_{CC} = 3.3\text{ V}$ , $SEL = 0\text{ V}$ , $I_O = -5\mu\text{A}$		1.8		V
<b>CAPACITANCE<sup>4</sup></b>						
A Port Off Capacitance	$C_A\text{ OFF}$	$f = 1\text{ MHz}$		5		pF
B Port Off Capacitance	$C_B\text{ OFF}$	$f = 1\text{ MHz}$		5		pF
A, B Port On Capacitance	$C_A, C_B\text{ ON}$	$f = 1\text{ MHz}$		10		pF
Control Input Capacitance	$C_{IN}$	$f = 1\text{ MHz}$		3		pF
<b>SWITCHING CHARACTERISTICS<sup>3</sup></b>						
Propagation Delay A to B or B to A, $t_{PD}$ <sup>5</sup>	$t_{PHL}, t_{PLH}$	$C_L = 50\text{ pF}$ , $V_{CC} = 3.3\text{ V}$			0.175	ns
Propagation Delay Matching <sup>6</sup>					TBD	ps
Bus Enable Time <i>BE</i> to A or B	$t_{PZH}, t_{PZL}$	$C_L = 50\text{ pF}$ , $R_L = 500\ \Omega$ , $V_{CC} = 3.0\text{ V}$	tbd	6	9	ns
Bus Disable Time <i>BE</i> to A or B	$t_{PLZ}, t_{PLZ}$	$C_L = 50\text{ pF}$ , $R_L = 500\ \Omega$ , $V_{CC} = 3.0\text{ V}$	tbd	3	8	ns
Bus Enable Time <i>BE</i> to A or B	$t_{PZH}, t_{PZL}$	$C_L = 50\text{ pF}$ , $R_L = 500\ \Omega$ , $V_{CC} = 2.3\text{ V}$	tbd	6	9	ns
Bus Disable Time <i>BE</i> to A or B	$t_{PLZ}, t_{PLZ}$	$C_L = 50\text{ pF}$ , $R_L = 500\ \Omega$ , $V_{CC} = 2.3\text{ V}$	tbd	3	8	ns
Max Data Rate				TBD		Mbps
Channel Jitter				TBD		ps p-p
<b>DIGITAL SWITCH</b>						
On Resistance	$R_{ON}$	$V_{CC} = 3\text{ V}$ , $SEL = V_{CC}$ , $V_A = 0\text{ V}$ , $I_{IN} = 15\text{ mA}$		3.5	6	$\Omega$
		$V_{CC} = 3\text{ V}$ , $SEL = V_{CC}$ , $V_A = 2.4\text{ V}$ , $I_{IN} = 8\text{ mA}$		tbd	tbd	$\Omega$
		$V_{CC} = 2.3\text{ V}$ , $SEL = V_{CC}$ , $V_A = 0\text{ V}$ , $I_{IN} = 15\text{ mA}$		5	8	$\Omega$
		$V_{CC} = 2.3\text{ V}$ , $SEL = V_{CC}$ , $V_A = 1.7\text{ V}$ , $I_{IN} = 8\text{ mA}$		tbd	tbd	$\Omega$
		$V_{CC} = 3.3\text{ V}$ , $SEL = 0\text{ V}$ , $V_A = 0\text{ V}$ , $I_{IN} = 15\text{ mA}$		5	8	$\Omega$
		$V_{CC} = 3.3\text{ V}$ , $SEL = 0\text{ V}$ , $V_A = 1.7\text{ V}$ , $I_{IN} = 8\text{ mA}$		tbd	tbd	$\Omega$
On Resistance Matching	$\Delta R_{ON}$	$V_{CC} = 3.3\text{ V}$ , $SEL = V_{CC}$ , $V_A = 0\text{ V}$ , $I_{IN} = 15\text{ mA}$		tbd	tbd	$\Omega$
		$V_{CC} = 3.3\text{ V}$ , $SEL = V_{CC}$ , $V_A = 1.7\text{ V}$ , $I_{IN} = 8\text{ mA}$		tbd	tbd	$\Omega$
<b>POWER REQUIREMENTS</b>						
$V_{CC}$			2.3		3.6	V
Quiescent Power Supply Current	$I_{CC}$	Digital Inputs = 0 V or $V_{CC}$		0.001	1	$\mu\text{A}$
Increase in $I_{CC}$ per input <sup>5</sup>	$\Delta I_{CC}$	$V_{CC} = +3.6\text{ V}$ , One input at 3.0 V; Others at $V_{CC}$ or GND			50	$\mu\text{A}$

### NOTES

<sup>1</sup>Temperature range is as follows: B Version:  $-40^\circ\text{C}$  to  $+85^\circ\text{C}$ .

<sup>2</sup>See Test Circuits and Waveforms.

<sup>3</sup>Typical values are at  $+25^\circ\text{C}$  unless otherwise stated.

<sup>4</sup>Guaranteed by design, not subject to production test.

<sup>5</sup>The digital switch contributes no propagation delay other than the RC delay of the typical  $R_{ON}$  of the switch and the load capacitance when driven by an ideal voltage source. Since the time constant is much smaller than the rise/fall times of typical driving signals, it adds very little propagation delay to the system. Propagation Delay of the digital switch when used in a system is determined by the driving circuit on the driving side of the switch and its interaction with the load on the driven side.

<sup>6</sup>Propagation delay matching between channels is calculated from the On Resistance matching and load capacitance of 50pF.

<sup>7</sup>This current applies to the control pins only and represents the current required to switch internal capacitance at the specified frequency. The A and B ports contribute no significant AC or DC currents as they transition. This parameter is guaranteed by design, not subject to production test.

Specifications subject to change without notice.

### ABSOLUTE MAXIMUM RATINGS<sup>1</sup>

(T<sub>A</sub> = +25°C unless otherwise noted)

V <sub>CC</sub> to GND	-0.5 V to +4.6 V
Digital Inputs to GND	-0.5 V to +4.6 V
DC Input Voltage	-0.5 V to +4.6 V
DC Output Current	120mA
Operating Temperature Range	
Industrial (B Version)	-40°C to +85°C
Storage Temperature Range	-65°C to +150°C
Junction Temperature	+150°C
CSP Package	
θ <sub>JA</sub> Thermal Impedance	tbd°C/W
TSSOP Package	
θ <sub>JA</sub> Thermal Impedance	98°C/W
Lead Temperature, Soldering (10seconds)	300°C
IR Reflow, Peak Temperature (<20 seconds)	+235°C

### NOTES

<sup>1</sup>Stresses above those listed under “Absolute Maximum Ratings” may cause permanent damage to the device. This is a stress rating only and functional operation of the device at these or any other conditions above those listed in the operational sections of this specification is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability. Only one absolute maximum rating may be applied at any one time.

**Table 2. Pin Description**

Pin Mnemonic	Description
xBE	Bus Enable (Active Low)
SEL	Level Translation Select
Ax	Port A, Inputs or Outputs
Bx	Port B, Inputs or Outputs

**Table 2. Truth Table**

xBE	SEL	Function
L	L	A = B, 3.3 V to 1.8 V Level Shifting
L	H	A = B
H	X	Disconnect

### ORDERING GUIDE



Model	Temperature Range	Package Descriptions	Package Options
ADG3247BCP	-40°C to +85°C	Leaded Frame Chip Scale Package	CP-40
ADG3247BRU	-40°C to +85°C	Thin Shrink SOP	RU-38

### CAUTION

ESD (electrostatic discharge) sensitive device. Electrostatic charges as high as 4000 V readily accumulate on the human body and test equipment and can discharge without detection. Although the ADG3247 features proprietary ESD protection circuitry, permanent damage may occur on devices subjected to high energy electrostatic discharges. Therefore, proper ESD precautions are recommended to avoid performance degradation or loss of functionality.




### PIN CONFIGURATION 40 LEAD CSP & 38 LEAD TSSOP




ADG3247


TYPICAL PERFORMANCE CHARACTERISTICS




*TPC 1. On Resistance vs Input Voltage ( $V_{CC} = 3.3\text{ V}$ )*




*TPC 2. On Resistance vs Input Voltage ( $V_{CC} = 2.5\text{ V}$ )*




*TPC 3. Max Pass Voltage vs  $V_{CC}$*



*TPC 4.  $I_{CC}$  vs Enable Frequency*



*TPC 5. Output Low Characteristic*



*TPC 6. Output High Characteristic*




Figure 1. Load Circuit




Figure 2. Propagation Delay

Note

- 1. Pulse Generator for all pulses:  $t_R \leq 2.5\text{ns}$ ,  $t_F \leq 2.5\text{ns}$ , Frequency  $\leq 10\text{MHz}$
- $C_L$  = includes board, stray and load capacitances.
- $R_T$  is the termination resistor, should be equal to  $Z_{out}$  of the pulse generator

Table 3 Switch Position

TEST	S1
$t_{PLH}$ , $t_{PHL}$	OPEN
$t_{PLZ}$ , $t_{PZL}$	$2 \times V_{CC}$
$t_{PHZ}$ , $t_{PZH}$	GND




Figure 3. Enable and Disable Times

Test Conditions

Symbol	$V_{CC} = 3.3\text{ V} \pm 0.3\text{V}$	$V_{CC} = 2.5 \pm 0.2\text{V}$	$V_{CC} = 3.3 \pm 0.3\text{V} (SEL = 0\text{ V})$	Units
$R_L$	500	500	500	$\Omega$
$V_{\Delta}$	300	150	150	mV
$C_L$	50	30	30	pF
$V_T$	1.5	$V_{CC}/2$	1.5	V

ADG3247




Figure 4. 3.3 V to 2.5 V Voltage Translation,  $S = 3.3V$




Figure 5. 2.5 V to 1.8 V Voltage Translation,  $S = 2.5V$





Figure 6. 3.3 V to 1.8 V Voltage Translation,  $S = 0V$

### OUTLINE DIMENSIONS

Dimensions shown in inches and (mm).

#### 40-Lead Leaded Chip Scale Package (CP-40)



#### 38-Lead TSSOP Package (RU-38)

