

# 2SC3834

Silicon NPN Triple Diffused Planar Transistor (Switching Transistor)

Application : Humidifier, DC-DC Converter, and General Purpose

**Absolute maximum ratings** (Ta=25°C)

Symbol	2SC3834	Unit
V <sub>CB0</sub>	200	V
V <sub>CEO</sub>	120	V
V <sub>EB0</sub>	8	V
I <sub>c</sub>	7(Pulse14)	A
I <sub>B</sub>	3	A
P <sub>c</sub>	50(Tc=25°C)	W
T <sub>J</sub>	150	°C
T <sub>stg</sub>	-55 to +150	°C


**Electrical Characteristics** (Ta=25°C)

Symbol	Conditions	2SC3834	Unit
I <sub>CB0</sub>	V <sub>CB</sub> =200V	100max	μA
I <sub>EB0</sub>	V <sub>EB</sub> =8V	100max	μA
V <sub>(BR)CEO</sub>	I <sub>c</sub> =50mA	120min	V
h <sub>FE</sub>	V <sub>CE</sub> =4V, I <sub>c</sub> =3A	70to220	
V <sub>CE(sat)</sub>	I <sub>c</sub> =3A, I <sub>B</sub> =0.3A	0.5max	V
V <sub>BE(sat)</sub>	I <sub>c</sub> =3A, I <sub>B</sub> =0.3A	1.2max	V
f <sub>r</sub>	V <sub>CE</sub> =12V, I <sub>E</sub> =-0.5A	30typ	MHz
COB	V <sub>CB</sub> =10V, f=1MHz	110typ	pF


**Typical Switching Characteristics (Common Emitter)**

V <sub>CC</sub> (V)	R <sub>L</sub> (Ω)	I <sub>c</sub> (A)	V <sub>BB1</sub> (V)	V <sub>BB2</sub> (V)	I <sub>B1</sub> (A)	I <sub>B2</sub> (A)	t <sub>on</sub> (μs)	t <sub>stg</sub> (μs)	t <sub>f</sub> (μs)
50	16.7	3	10	-5	0.3	-0.6	0.5max	3.0max	0.5max


**External Dimensions MT-25(TO220)**




**I<sub>c</sub>-V<sub>CE</sub> Characteristics (Typical)**




**V<sub>CE(sat)</sub>-I<sub>B</sub> Characteristics (Typical)**




**I<sub>c</sub>-V<sub>BE</sub> Temperature Characteristics (Typical)**




**h<sub>FE</sub>-I<sub>c</sub> Characteristics (Typical)**




**h<sub>FE</sub>-I<sub>c</sub> Temperature Characteristics (Typical)**




**θ<sub>j-a</sub>-t Characteristics**



**f<sub>r</sub>-I<sub>E</sub> Characteristics (Typical)**



**Safe Operating Area (Single Pulse)**



**P<sub>c</sub>-T<sub>a</sub> Derating**

