

SPECIFICATION

MESSRS.

DEVICE TYPE NAME

Sanken Hybrid Voltage Regulator - STR30130


1. scope

The present specification shall only apply to **Sanken** Hybrid Voltage Regulator, type **STR30130**

2. Features

- a) Hybrid Voltage Regulator with a triple diffused planar **darlington** transistor.
- b) For Line-operated TV
- c) Fixed output voltage
- d) Plastic package (Transfer Mold)

3. Equivalent circuit



- 1. COMMON (-)
- 2. BASE
- 3. IN PUT
- 4. OUT PUT

4. Outline **drawings**, **dimention** and pin connections are as Fig-1.

5. The type number and lot number **shall** be marked clearly with white.

DATE ISSUED : Nov. 27 ,1992

PREPARED BY : *M. Yokota*

CHECKED BY : *Mitsuo Ueki*

APPROVED BY : *W. Sekine*

APPLICATION ENGINEERING
SEMICONDUCTOR DIVISION

SPECIFICATION NUMBER

SSE-19077E

6 Absolute Maximum Ratings($T_a=25^{\circ}\text{C}$)

Description	Symbol	Unit	Ratings	
Peak Input Voltage	V_{IN}	V	200	
Output Current	I_O	A	1.0	
Power Dissipation	P_D	W	27 ($T_c=100^{\circ}\text{C}$)	
Operating Temperature	T_{OP}	$^{\circ}\text{C}$	-20~+125 (T_c)	(Note1)
Storage Temperature	T_{stg}	$^{\circ}\text{C}$	-30~+125	
Power Transistor Junction Temperature	T_j	$^{\circ}\text{C}$	+150 $^{\circ}\text{C}$ Max	

7 Electrical Characteristics($T_a=25^{\circ}\text{C}$)

Description	Conditions	Ratings	
Fixed Output Voltage	$I_{IN}=6.9\text{mA}$, Test Circuit 2	$130 \pm 0.8\text{V}$	(Note2)
	$V_{IN}=16\text{V(D.C.)}$, $I_O=0.5\text{A}$ Test Circuit 1		
Line Regulation	$V_{IN}=145 \sim 170\text{V(D.C.)}$ $I_O=0.5\text{A}$, Test Circuit 1	$\Delta 2.4\text{V Max}$	
Load Regulation	$V_{IN}=16\text{V(D.C.)}$ $I_O=0.25\text{A} \sim 0.5\text{A}$, Test Circuit 1	$\Delta 0.5\text{V Max}$	
Output Voltage Temperature Coefficient	$V_{IN}=16\text{V(D.C.)}$, $I_O=0.5\text{A}$ $T_c=-20^{\circ}\text{C} \sim +100^{\circ}\text{C}$	$\pm 0\text{mV}/^{\circ}\text{C Typ}$	
In-Out Saturation Voltage : $V_{CE(sat)}$	$I_C=1.0\text{A}$, $I_B=10\text{mA}$	1.5V Max	
In-Out Breakdown Voltage : V_{CEO}	$I_{CEO}=10\text{mA}$, $I_B=0\text{A}$	200V Min	
DC Current Gain : h_{FE}	$I_C=1.0\text{A}$, $V_{CE}=4\text{V}$	1500~6500	
Power Transistor Thermal Resistance : θ_{jc}	between Junction and frame	1.8 $^{\circ}\text{C}/\text{W}$	
In-Gut Leak Current : I_{CEO}	3, 4 Terminal (V_{CE})=200V 1, 2 Terminal : Open	100 μA Max	
Output (Emitter) - Base Reverse Breakdown : $I_{EB(S/B)}$	$t=65\text{ms}$	300mA Min	

(Note1) Recommended Case Temperature : $T_{op}(T_c)=100^{\circ}\text{C}$ Max.

(Note2) Fixed Output Voltage is prescribed on 5 sec after Switch ON. In case a doubt should be occurred, Fixed Output Voltage is prescribed in Test Circuit 2.

Recommended screwing torque : 6-8 kg · f · cm

Recommended Silicone Grease :


G-746 (Shinetsu Chemical Industries Ltd.)

YG6260 (Toshiba Silicone Co.; Ltd.)

SC1 02 (Toray Silicone Co., Ltd.)

Since this product is developed and produced for general application, radiation ray design has not been considered.


Test Circuit 1



$R_1:1.0\Omega$, $R_2:2.2\Omega$, $R_3:12K\Omega$, $R_4:330K\Omega$, $R_5:47\Omega$, $R_6:220\Omega$

$C_1:470\mu\text{F}$, $C_2:33\mu\text{F}$, $C_3:33\mu\text{F}$

Test Circuit 2



STR30000 Series Derating Curves








Fig-1 Outline Drawings, Dimensions and Pin Connections
[Sanken lead forming LF500]



- a. Type number : 30130
- b. Lot number
- 1st digit : The last numerical figure of calendar year. 0 ~ 9
- 2nd digit : Month
- 1 to 9 for Jan. to Sep.
- 0 for Oct.
- N for Nov.
- D for Dec.
- 3rd , 4th digit : Date
- 01 ~ 31

Unit: m m

1. COMMON (-)
2. BASE
3. IN PUT
4. OUT PUT
5. BLANK



Remarks : The dimensions marked ※ is measured at the base of lead wires.