



PCM1717

Sound^{PLUS} Stereo Audio DIGITAL-TO-ANALOG CONVERTER

FEATURES


- ACCEPTS 16- OR 18-BIT INPUT DATA
- COMPLETE STEREO DAC:
 - 8X Oversampling Digital Filter
 - Multi-Level Delta-Sigma DAC
 - Analog Low Pass Filter
 - Output Amplifier
- HIGH PERFORMANCE:
 - 90dB THD+N
 - 96dB Dynamic Range
 - 100dB SNR
- SYSTEM CLOCK: 256fs or 384fs
- WIDE POWER SUPPLY: +2.7V to +5.5V
- SELECTABLE FUNCTIONS:
 - Soft Mute
 - Digital Attenuation (256 Steps)
 - Digital De-emphasis
 - Output Mode: L, R, Mono, Mute
- SMALL 20-PIN SSOP PACKAGE

DESCRIPTION

The PCM1717 is a complete low cost stereo, audio digital-to-analog converter, including digital interpolation filter, 3rd-order delta-sigma DAC, and analog output amplifiers. PCM1717 is fabricated on a highly advanced 0.6 μ CMOS process. PCM1717 accepts 16- or 18-bit normal input data format, or 16- or 18-bit IIS data format.

The digital filter performs an 8X interpolation function, as well as special functions such as soft mute, digital attenuation, and digital de-emphasis. The digital filter features -35dB stop band attenuation and ± 0.17 dB ripple in the pass band.

PCM1717 is suitable for a wide variety of cost-sensitive consumer applications where good performance is required. Its low cost, small size, and single +5V power supply make it ideal for automotive CD players, bookshelf CD players, BS tuners, keyboards, MPEG audio, MIDI applications, set-top boxes, CD-ROM drives, CD-Interactive, and CD-Karaoke systems.



International Airport Industrial Park • Mailing Address: P.O. Box 11400, Tucson, AZ 85734 • Street Address: 6730 S. Tucson Blvd., Tucson, AZ 85706 • Tel: (520) 746-1111 • Twx: 910-952-1111
Internet: <http://www.burr-brown.com/> • FAX Line: (800) 548-6133 (US/Canada Only) • Cable: BURROPP • Telex: 066-6491 • FAX: (520) 889-1510 • Immediate Product Info: (800) 548-6132


SPECIFICATIONS

All specifications at +25°C, +V_{CC} = +V_{DD} = +5V, f_s = 44.1kHz, and 16-bit input data, SYSCLK = 384fs, unless otherwise noted. Measurement bandwidth is 20kHz.

| PARAMETER | CONDITIONS | PCM1717E | | | UNITS |
|------------------------------------------------------------------|------------------------------------------------------|------------------------|----------------------------------------------|------------------------|----------|
| | | MIN | TYP | MAX | |
| RESOLUTION | | 16 | | 18 | Bits |
| DIGITAL INPUT/OUTPUT | | | CMOS | | |
| Logic Family | | | | | |
| Input Logic Level: | | | | | |
| V _{IH} ⁽²⁾ | | 70% of V _{DD} | | | V |
| V _{IL} ⁽²⁾ | | | | 30% of V _{DD} | V |
| V _{IH} ⁽³⁾ | | 70% of V _{DD} | | | V |
| V _{IL} ⁽³⁾ | | | | 30% of V _{DD} | V |
| V _{IH} ⁽⁴⁾ | | 64% of V _{DD} | | | V |
| V _{IL} ⁽⁴⁾ | | | | 28% of V _{DD} | V |
| Input Logic Current: | | | | | |
| I _{IH} ⁽⁵⁾ | | | | -6.0 | μA |
| I _{IL} ⁽⁵⁾ | | | | -120 | μA |
| I _{IH} ⁽⁶⁾ | | | | -2 | μA |
| I _{IL} ⁽⁶⁾ | | | | 0.02 | μA |
| I _{IH} ⁽⁴⁾ | V _{IN} = 3.2V | | | 40 | μA |
| I _{IL} ⁽⁴⁾ | V _{IN} = 1.4V | | | -40 | μA |
| Output Logic Level: (+V _{DD} = +5V) | | | | | |
| V _{OH} ⁽⁷⁾ | I _{OH} = -5mA | 3.8 | | | V |
| V _{OL} ⁽⁷⁾ | I _{OL} = +5mA | | | 1.0 | V |
| V _{OL} ⁽⁸⁾ | I _{OL} = +5mA | | | 1.0 | V |
| Interface Format | | | Selectable Normal, I ² S | | |
| Data Format | | | 16/18 Bits MSB First Binary Two's Complement | | |
| Sampling Frequency | | 32 | 44.1 | 48 | kHz |
| System Clock Frequency | 256fs/384fs | 8.192/12.288 | 11.2896/16.9344 | 12.288/18.432 | MHz |
| DC ACCURACY | | | | | |
| Gain Error | | | ±1.0 | ±5.0 | % of FSR |
| Gain Mismatch Channel-to-Channel | | | ±1.0 | ±5.0 | % of FSR |
| Bipolar Zero Error | V _O = 1/2 V _{CC} at Bipolar Zero | | ±30 | | mV |
| DYNAMIC PERFORMANCE⁽¹⁾ | V _{CC} = +5V, f = 991Hz | | | | |
| THD+N at FS (0dB) | | | -90 | -80 | dB |
| THD+N at -60dB | | | -34 | | dB |
| Dynamic Range | EIAJ, A-weighted | 90 | 96 | | dB |
| Signal-To-Noise Ratio | EIAJ, A-weighted | 92 | 100 | | dB |
| Channel Separation | | 90 | 97 | | dB |
| Level Linearity Error (-90dB) | | | ±0.5 | | dB |
| DYNAMIC PERFORMANCE⁽¹⁾ | V _{CC} = +3V, f = 991Hz | | | | |
| THD+N at FS (0dB) | | | -86 | | dB |
| Dynamic Range | EIAJ, A-weighted | | 91 | | dB |
| Signal-To-Noise Ratio | EIAJ, A-weighted | | 94 | | dB |
| DIGITAL FILTER PERFORMANCE | | | | | |
| Pass Band Ripple | | | | ±0.17 | dB |
| Stop Band Attenuation | | -35 | | | dB |
| Pass Band | | | | 0.445 | fs |
| Stop Band | | 0.555 | | | fs |
| De-emphasis Error | (f _s = 32kHz ~ 48kHz) | -0.2 | | +0.55 | dB |
| Delay Time (Latency) | | | 11.125/fs | | sec |
| ANALOG OUTPUT | | | | | |
| Voltage Range | FS (0dB) OUT | | 62% of V _{CC} | | Vp-p |
| Load Impedance | | 5 | | | kΩ |
| Center Voltage | | | 50% of V _{CC} | | V |
| POWER SUPPLY REQUIREMENTS | | | | | |
| Voltage Range: | +V _{CC} | +2.7 | | +5.5 | VDC |
| | +V _{DD} | +2.7 | | +5.5 | VDC |
| Supply Current: +I _{CC} +I _{DD} ⁽⁹⁾ | +V _{CC} = +V _{DD} = +5V | | 18.0 | 25.0 | mA |
| | +V _{CC} = +V _{DD} = +3V | | 9.0 | 15.0 | mA |
| Power Dissipation | +V _{CC} = +V _{DD} = +5V | | 90 | 125 | mW |
| | +V _{CC} = +V _{DD} = +3V | | 27 | 45 | mW |
| TEMPERATURE RANGE | | | | | |
| Operation | | -25 | | +85 | °C |
| Storage | | -55 | | +100 | °C |

NOTES: (1) Tested with Shibasoku #725 THD. Meter 400Hz HPF, 30kHz LPF On, Average Mode with 20kHz bandwidth limiting. (2) Pins 4, 5, 6, 14: LRCIN, DIN, BCKIN, FORMAT. (3) Pins 15, 16, 17, 18: RSTB, DM0, DM1, MUTE (Schmitt trigger input). (4) Pin 1: XT1. (5) Pins 15, 16, 17, 18: RSTB, DM0, DM1, MUTE (if pull-up resistor is used). (6) Pins 4, 5, 6: LRCIN, DIN, BCKIN (if pull-up resistor is not used). (7) Pin 19: CLK0. (8) Pin 7: ZERO. (9) No load on pins 19 (CLK0) and 20 (XTO).

PIN CONFIGURATION



PACKAGE INFORMATION

| PRODUCT | PACKAGE | PACKAGE DRAWING NUMBER ⁽¹⁾ |
|----------|-------------|---------------------------------------|
| PCM1717E | 20-Pin SSOP | 334-1 |

NOTE: (1) For detailed drawing and dimension table, please see end of data sheet, or Appendix C of Burr-Brown IC Data Book.

ABSOLUTE MAXIMUM RATINGS

| | |
|-------------------------------------------------|-----------------------------------|
| Power Supply Voltage | +6.5V |
| +V _{CC} to +V _{DD} Difference | ±0.1V |
| Input Logic Voltage | -0.3V to (V _{DD} + 0.3V) |
| Power Dissipation | 200mW |
| Operating Temperature Range | -25°C to +85°C |
| Storage Temperature | -55°C to +125°C |
| Lead Temperature (soldering, 5s) | +260°C |
| Thermal Resistance, θ_{JA} | +70°C/W |



ELECTROSTATIC DISCHARGE SENSITIVITY

This integrated circuit can be damaged by ESD. Burr-Brown recommends that all integrated circuits be handled with appropriate precautions. Failure to observe proper handling and installation procedures can cause damage.

ESD damage can range from subtle performance degradation to complete device failure. Precision integrated circuits may be more susceptible to damage because very small parametric changes could cause the device not to meet its published specifications.

The information provided herein is believed to be reliable; however, BURR-BROWN assumes no responsibility for inaccuracies or omissions. BURR-BROWN assumes no responsibility for the use of this information, and all use of such information shall be entirely at the user's own risk. Prices and specifications are subject to change without notice. No patent rights or licenses to any of the circuits described herein are implied or granted to any third party. BURR-BROWN does not authorize or warrant any BURR-BROWN product for use in life support devices and/or systems.






PIN ASSIGNMENTS

| PIN | NAME | FUNCTION |
|---------------------------------------|-------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Data Input Interface Pins | | |
| 4 | LRCIN | Sample Rate Clock Input. Controls the update rate (fs). |
| 5 | DIN | Serial Data Input. MSB first, right justified (Sony format) or I ² S (Philips). Contains a frame of 16- or 18-bit data. |
| 6 | BCKIN | Bit Clock Input. Clocks in the data present on DIN input. |
| Mode Control and Clock Signals | | |
| 1 | XTI | Oscillator Input (External Clock Input). For an internal clock, tie XTI to one side of the crystal oscillator. For an external clock, tie XTI to the output of the chosen external clock. |
| 14 | MODE | Operation Mode Select. For Software Mode, tie Mode "HIGH". For Hardware Mode, tie Mode "LOW". |
| 16 | MD/DM0 | Mode Control for Data Input or De-emphasis. When "HIGH" MD is selected, and a "LOW" selects DM0. |
| 17 | MC/DM1 | Mode Control for BCKIN or De-emphasis. When "HIGH", MC is selected, and a "LOW" selects DM1. |
| 18 | ML/MUTE | Mode Control for Strobe Clock or Mute. When "HIGH", ML is selected, and a "LOW" selects mute. |
| 19 | CLKO | Buffered Output of Oscillator. Equivalent to XTI. |
| 20 | XTO | Oscillator Output. When using the internal clock, tie to the opposite side (from pin 1) of the crystal oscillator. When using an external clock, leave XTO open. |
| Operational Controls and Flags | | |
| 7 | ZERO | Infinite Zero Detection Flag, open drain output. When the zero detection feature is muting the output, ZERO is "LOW". When non-zero input data is present, ZERO is in a high impedance state. When the input data is continuously zero for 65.536 BCKIN cycles, zero will be low. |
| 15 | RSTB | Resets DAC operation with an active "LOW" pulse. |
| Analog Output Functions | | |
| 8 | D/C_R | Right Channel Output Amplifier Common. Bypass to ground with 10 μ F capacitor. |
| 9 | V _{OUTR} | Right Channel Analog Output. V _{OUT} max = 0.62 x V _{CC} . |
| 12 | V _{OUTL} | Left Channel Analog Output. V _{OUT} max = 0.62 x V _{CC} . |
| 13 | D/C_L | Left Channel Output Amplifier Common. Bypass to ground with 10 μ F capacitor. |
| Power Supply Connections | | |
| 2 | DGND | Digital Ground. |
| 3 | V _{DD} | Digital Power Supply (+5V). |
| 10 | AGND | Analog Ground. |
| 11 | V _{CC} | Analog Power Supply (+3V). |

TYPICAL PERFORMANCE CURVES

At $T_A = +25^\circ\text{C}$, $+V_{CC} = +V_{DD} = +5\text{V}$, $f_s = 44.1\text{kHz}$, and 16-bit input data, $\text{SYSCLK} = 384\text{fs}$, unless otherwise noted.









DYNAMIC PERFORMANCE



TYPICAL PERFORMANCE CURVES

At $T_A = +25^\circ\text{C}$, $+V_{CC} = +V_{DD} = +5\text{V}$, $f_s = 44.1\text{kHz}$, and 16-bit input data, $\text{SYSCLK} = 384\text{fs}$, unless otherwise noted.

DIGITAL FILTER



SYSTEM CLOCK

The system clock for PCM1717 must be either $256f_s$ or $384f_s$, where f_s is the audio sampling frequency (typically 32kHz, 44.1kHz, or 48kHz). The system clock is used to operate the digital filter and the modulator.

The system clock can be either a crystal oscillator placed between XTI (pin 1) and XTO (pin 20), or an external clock input to XTI. If an external system clock is used, XTO is open (floating). Figure 1 illustrates the typical system clock connections.

PCM1717 has a system clock detection circuit which automatically senses if the system clock is operating at $256f_s$ or $384f_s$. The system clock should be synchronized with LRCIN (pin 4) clock. LRCIN (left-right clock) operates at the sampling frequency f_s . In the event these clocks are not synchronized, PCM1717 can compensate for the phase difference internally. If the phase difference between left-right

and system clocks is greater than 6 bit clocks (BCKIN), the synchronization is performed internally. While the synchronization is processing, the analog output is forced to a DC level at bipolar zero. The synchronization typically occurs in less than 1 cycle of LRCIN.

DATA INTERFACE FORMATS

Digital audio data is interfaced to PCM1717 on pins 4, 5, and 6—LRCIN (left-right clock), DIN (data input) and BCKIN (bit clock). PCM1717 can accept both normal and I²S data formats. Normal data format is MSB first, two's complement, right-justified. I²S data is compatible with Philips serial data protocol. In the I²S format, the data is 16- or 18-bit, selectable by bit 0 on Register 3 (Software Control Mode). In the Hardware Mode, PCM1717 can only function with 16-bit normal data. Figures 5 through 9 illustrate timing and input formats.




FIGURE 1. Internal Clock Circuit Diagram and Oscillator Connection.




FIGURE 2. External Clock Timing Requirements.

Reset

PCM1717 has both internal power on reset circuit and the RSTB-pin (pin 15) which accepts external forced reset by RSTB = LOW. For internal power on reset, initialize (reset) is done automatically at power on $V_{DD} > 2.2V$ (typ). During internal reset = LOW, the output of the DAC is invalid and the analog outputs are forced to $V_{CC}/2$. Figure 3 illustrates the timing of internal power on reset.

For the RSTB-pin, PSTB-pin accepts external forced reset by RSTB = L. During RSTB = L, the output of the DAC is invalid and the analog outputs are forced to $V_{CC}/2$ after internal initialize (1024 system clocks count after RSTB = H.) Figure 4 illustrates the timing of RSTB-pin reset.




FIGURE 3. Internal Power-On Reset Timing.




FIGURE 4. RSTB-Pin Reset Timing.

OPERATIONAL CONTROL

PCM1717 can be controlled in two modes. Software Mode allows the user to control operation with a 16-bit serial register. Hardware Mode allows the user to hard-wire operation of PCM1717 using four parallel wires. The MODE pin determines which mode PCM1717 is in; a LOW level on pin 14 places PCM1717 in Hardware Mode, and a HIGH on pin 14 places PCM1717 in Software Mode.

| MODE (Pin 14) | Selected Mode | Pin 16 | Pin 17 | Pin 18 |
|---------------|---------------|--------|--------|--------|
| "HIGH" | Software Mode | MD | MC | ML |
| "LOW" | Hardware Mode | DM0 | DM1 | MUTE |

Table I indicates which functions are selectable within the user's chosen mode. All of the functions shown are selectable in the Software Mode, but only soft mute and de-emphasis control may be selected in the Hardware Mode.

| FUNCTION | SOFTWARE MODE SELECTABLE | DEFAULT | HARDWARE MODE SELECTABLE | DEFAULT |
|-------------------------|--------------------------|-----------|--------------------------|-----------|
| Input Data Format | Yes | | No | |
| Normal Format | | Normal | Normal Only | Normal |
| I ² S Format | | | | |
| Input Resolution | Yes | | No | |
| 16 Bits | | 16 Bits | 16 Bits Only | 16 Bits |
| 18 Bits | | | | |
| LRCIN Polarity | Yes | | No | |
| L/R = High/Low | | L/R = H/L | L/R = H/L Only | L/R = H/L |
| L/R = Low/High | | | | |
| De-emphasis Control | Yes | | Yes | |
| 32kHz | | | | |
| 44.1kHz | | OFF | | OFF |
| 48kHz | | | | |
| OFF | | | | |
| Soft Mute | Yes | OFF | Yes | OFF |
| Digital Attenuation | Yes | 0dB | No | 0dB |
| Analog Output Mode | Yes | Stereo | No | Stereo |
| Infinite Zero Detection | Yes | Disabled | No | Disabled |
| DAC Operation Control | Yes | ON | No | ON |

TABLE I. Feature Selections by Mode.

HARDWARE MODE

(Pin 14 = "0")

This mode is controlled by logic levels present on pins 15, 16, 17 and 18. Hardware Mode allows for control of soft mute, digital de-emphasis and disable ONLY. Other functions such as attenuation, I/O format and infinite zero detect can only be controlled in the Software Mode.

SOFT MUTE (Pin 18)

A LOW level on pin 18 will force both channels to be muted; a HIGH level on pin 18 will allow for normal operation.

DIGITAL DE-EMPHASIS (Pins 16 and 17)

Pins 16 and 17 are used as a two-bit parallel register to control de-emphasis modes:

| PIN 16 | PIN 17 | MODE |
|--------|--------|--------------------------------|
| 0 | 0 | De-emphasis disabled |
| 1 | 0 | De-emphasis enabled at 48kHz |
| 0 | 1 | De-emphasis enabled at 44.1kHz |
| 1 | 1 | De-emphasis enabled at 32kHz |

RESET MODE (Pin 15)

A LOW level on pin 15 will force the digital filters, modulators and mode controls into a reset (disable) mode. While this pin is held low, the output of PCM1717 will be forced to $V_{CC}/2$ (Bipolar Zero). Bringing pin 15 HIGH will initialize all DAC functions, and allow for normal operation.

SOFTWARE MODE

(Pin 14 = "1")

The Software Mode uses a three-wire interface on pins 16, 17 and 18. Pin 17 (MC) is used to clock in the serial control data, pin 18 (ML) is used to synchronize the serial control data, and pin 16 (MD) is used to latch in the serial control register. There are four distinct registers, with bits 9 and 10 (of 16) determining which register is in use.

REGISTER CONTROL (Bits 9, 10)

| REGISTER | B9 (A0) | B10 (A1) |
|----------|---------|----------|
| 0 | 0 | 0 |
| 1 | 1 | 0 |
| 2 | 0 | 1 |
| 3 | 1 | 1 |

Control data timing is shown in Figure 6. ML is used to latch the data from the control registers. After each register's contents are checked in, ML should be taken low to latch in the data. A "res" in the register indicates that location is reserved for factory use. When loading the registers, the "res" bits should be set LOW.

REGISTER 0

| | | | | | | | | | | | | | | | |
|-----|-----|-----|-----|-----|-----|----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| B15 | B14 | B13 | B12 | B11 | B10 | B9 | B8 | B7 | B6 | B5 | B4 | B3 | B2 | B1 | B0 |
| res | res | res | res | res | A1 | A0 | LDL | AL7 | AL6 | AL5 | AL4 | AL3 | AL2 | AL1 | AL0 |

Register 0 is used to control left channel attenuation. Bits 0-7 (AL0-AL7) are used to determine the attenuation level. The level of attenuation is given by:

$$ATT = [20\log_{10} (ATT_DATA/255)] \text{ dB}$$

ATTENUATION DATA LOAD CONTROL

Bit 8 (LDL) is used to control the loading of attenuation data in B0:B7. When LDL is set to 0, attenuation data will be loaded into AL0:AL7, but it will not affect the attenuation level until LDL is set to 1. LDR in Register 1 has the same function for right channel attenuation. The attenuation level is given by:

$$ATT = 20 \log(y/256) \text{ (dB)}, \text{ where } y = x, \text{ when } 0 \leq x \leq 254$$

$$y = x + 1, \text{ when } x = 255$$

X is the user-determined step number, an integer value between 0 and 255.

Example:

let $x = 255$

$$ATT = 20 \log\left(\frac{255+1}{256}\right) = 0\text{dB}$$

let $x = 254$

$$ATT = 20 \log\left(\frac{254}{256}\right) = -0.068\text{dB}$$

let $x = 1$

$$ATT = 20 \log\left(\frac{1}{256}\right) = -48.16\text{dB}$$

let $x = 0$

$$ATT = 20 \log\left(\frac{0}{256}\right) = -\infty$$

REGISTER 1

| | | | | | | | | | | | | | | | |
|-----|-----|-----|-----|-----|-----|----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| B15 | B14 | B13 | B12 | B11 | B10 | B9 | B8 | B7 | B6 | B5 | B4 | B3 | B2 | B1 | B0 |
| res | res | res | res | res | A1 | A0 | LDR | AR7 | AR6 | AR5 | AR4 | AR3 | AR2 | AR1 | AR0 |

Register 1 is used to control right channel attenuation. As in Register 1, bits 0-7 (AR0-AR7) control the level of attenuation.

REGISTER 2

| | | | | | | | | | | | | | | | |
|-----|-----|-----|-----|-----|-----|----|-----|-----|-----|-----|-----|-----|-----|-----|------|
| B15 | B14 | B13 | B12 | B11 | B10 | B9 | B8 | B7 | B6 | B5 | B4 | B3 | B2 | B1 | B0 |
| res | res | res | res | res | A1 | A0 | res | res | res | res | IZD | OPE | DM1 | DM0 | MUTE |

Register 2 is used to control soft mute, digital de-emphasis, disable, and infinite zero detect. Bit 0 is used for soft mute; a HIGH level on bit 0 will cause the output to be muted. Bits 1 and 2 are used to control digital de-emphasis as shown below:

| BIT 1 (DM0) | BIT 2 (DM1) | DE-EMPHASIS |
|-------------|-------------|--------------------------------|
| 0 | 0 | De-emphasis disabled |
| 1 | 0 | De-emphasis enabled at 48kHz |
| 0 | 1 | De-emphasis enabled at 44.1kHz |
| 1 | 1 | De-emphasis enabled at 32kHz |

Bits 3 (OPE) and 4 (IZD) are used to control the infinite zero detection features. Tables II through IV illustrate the relationship between IZD, OPE, and RSTB (reset control):

| | DATA INPUT | DAC OUTPUT |
|---------|------------|------------------------------|
| IZD = 1 | Zero | Forced to BPZ ⁽¹⁾ |
| | Other | Normal |
| IZD = 0 | Zero | Zero ⁽²⁾ |
| | Other | Normal |

TABLE II. Infinite Zero Detection (IZD) Function.

| | DATA INPUT | DAC OUTPUT | SOFTWARE MODE INPUT |
|---------|------------|------------------------------|---------------------|
| OPE = 1 | Zero | Forced to BPZ ⁽¹⁾ | Enabled |
| | Other | Forced to BPZ ⁽¹⁾ | Enabled |
| OPE = 0 | Zero | Controlled by IZD | Enabled |
| | Other | Normal | Enabled |

TABLE III. Output Enable (OPE) Function.

| | DATA INPUT | DAC OUTPUT | SOFTWARE MODE INPUT |
|---------------|------------|------------------------------|---------------------|
| RSTB = "HIGH" | Zero | Controlled by OPE and IZD | Enabled |
| | Other | Controlled by OPE and IZD | Enabled |
| RSTB = "LOW" | Zero | Forced to BPZ ⁽¹⁾ | Disabled |
| | Other | Forced to BPZ ⁽¹⁾ | Disabled |

TABLE IV. Reset (RSTB) Function.

NOTE: (1) $\Delta\Sigma$ is disconnected from output amplifier. (2) $\Delta\Sigma$ is connected to output amplifier.

OPE controls the operation of the DAC: when OPE is "LOW", the DAC will convert all non-zero input data. If the input data is continuously zero for 65,536 cycles of BCKIN, the output will only be forced to zero only if IZD is "HIGH". When OPE is "HIGH", the output of the DAC will be forced to bipolar zero, irrespective of any input data.

IZD controls the operation of the zero detect feature: when IZD is "LOW", the zero detect circuit is off. Under this condition, no automatic muting will occur if the input is continuously zero. When IZD is "HIGH", the zero detect feature is enabled. If the input data is continuously zero for 65,536 cycle of BCKIN, the output will be immediately forced to a bipolar zero state ($V_{CC}/2$). The zero detection feature is used to avoid noise which may occur when the input is DC. When the output is forced to bipolar zero, there may be an audible click. PCM1717 allows the zero detect feature to be disabled so the user can implement an external muting circuit.

REGISTER 3

| | | | | | | | | | | | | | | | |
|-----|-----|-----|-----|-----|-----|----|-----|-----|-----|-----|-----|-----|----|-----|-----|
| B15 | B14 | B13 | B12 | B11 | B10 | B9 | B8 | B7 | B6 | B5 | B4 | B3 | B2 | B1 | B0 |
| res | res | res | res | res | A1 | A0 | res | PL3 | PL2 | PL1 | PL0 | ATC | IW | LRP | IIS |

Register 3 is used to select the I/O data formats. Bit 0 (IIS) is used to control the input data format. If the input data source is normal (16- or 18-bit, MSB first, right-justified), set bit 0 "LOW". If the input format is IIS, set bit 0 "HIGH".




FIGURE 5. “Normal” Data Input Timing.




FIGURE 6. “I2S” Data Input Timing.




FIGURE 7. Data Input Timing.

Bit 1 is used to select the polarity of LRCIN (sample rate clock). When bit 1 is LOW, a HIGH state on LRCIN is used for the left channel, and a LOW state on LRCIN is used for the right channel. When bit 1 is HIGH the polarity of LRCIN is reversed.

Bit 2 is used to select the input word length. When bit 2 is LOW, the input word length is set for 16 bits; when bit 2 is HIGH, the input word length is set for 18 bits.

Bit 3 is used as an attenuation control. When bit 3 is set HIGH, the attenuation data on Register 0 is used for both channels, and the data in Register 1 is ignored. When bit 3 is LOW, each channel has separate attenuation data.

Bits 4 through 7 are used to determine the output format, as shown in Table V:

| PL0 | PL1 | PL2 | PL3 | Lch OUTPUT | Rch OUTPUT | NOTE |
|-----|-----|-----|-----|------------|------------|---------|
| 0 | 0 | 0 | 0 | MUTE | MUTE | MUTE |
| 0 | 0 | 0 | 1 | MUTE | R | |
| 0 | 0 | 1 | 0 | MUTE | L | |
| 0 | 0 | 1 | 1 | MUTE | (L + R)/2 | |
| 0 | 1 | 0 | 0 | R | MUTE | |
| 0 | 1 | 0 | 1 | R | R | REVERSE |
| 0 | 1 | 1 | 0 | R | L | |
| 0 | 1 | 1 | 1 | R | (L + R)/2 | |
| 1 | 0 | 0 | 0 | L | MUTE | |
| 1 | 0 | 0 | 1 | L | R | STEREO |
| 1 | 0 | 1 | 0 | L | L | |
| 1 | 0 | 1 | 1 | L | (L + R)/2 | |
| 1 | 1 | 0 | 0 | (L + R)/2 | MUTE | |
| 1 | 1 | 0 | 1 | (L + R)/2 | R | |
| 1 | 1 | 1 | 0 | (L + R)/2 | L | |
| 1 | 1 | 1 | 1 | (L + R)/2 | (L + R)/2 | MONO |

TABLE V. PCM1717 Output Mode Control.

REGISTER RESET STATES

After reset, each register is set to a predetermined state:

| | |
|------------|---------------------|
| Register 0 | 0000 0000 1111 1111 |
| Register 1 | 0000 0010 1111 1111 |
| Register 2 | 0000 0100 0000 0000 |
| Register 3 | 0000 0110 1001 0000 |




FIGURE 8. Control Data Timing in Software Mode Control.




FIGURE 9. External Reset Timing.




FIGURE 10. Typical Connection Diagram of PCM1717.

POWER SUPPLY CONNECTIONS

PCM1717 has two power supply connections: digital (V_{DD}) and analog (V_{CC}). Each connection also has a separate ground. If the power supplies turn on at different times, there is a possibility of a latch-up condition. To avoid this condition, it is recommended to have a common connection between the digital and analog power supplies. If separate supplies are used without a common connection, the delta between the two supplies during ramp-up time must be less than 0.6V.

An application circuit to avoid a latch-up condition is shown in Figure 11.




FIGURE 11. Latch-up Prevention Circuit.

BYPASSING POWER SUPPLIES

The power supplies should be bypassed as close as possible to the unit. Refer to Figure 10 for optimal values of bypass capacitors.

THEORY OF OPERATION

The delta-sigma section of PCM1717 is based on a 5-level amplitude quantizer and a 3rd-order noise shaper. This section converts the oversampled input data to 5-level delta-sigma format.

A block diagram of the 5-level delta-sigma modulator is shown in Figure 12. This 5-level delta-sigma modulator has the advantage of stability and clock jitter sensitivity over the typical one-bit (2 level) delta-sigma modulator.

The combined oversampling rate of the delta-sigma modulator and the internal 8-times interpolation filter is $48f_s$ for a $384f_s$ system clock, and $64f_s$ for a $256f_s$ system clock. The theoretical quantization noise performance of the 5-level delta-sigma modulator is shown in Figure 13.




FIGURE 13. Quantization Noise Spectrum.




FIGURE 12. 5-Level $\Delta\Sigma$ Modulator Block Diagram.

APPLICATION CONSIDERATIONS

DELAY TIME

There is a finite delay time in delta-sigma converters. In A/D converters, this is commonly referred to as latency. For a delta-sigma D/A converter, delay time is determined by the order number of the FIR filter stage, and the chosen sampling rate. The following equation expresses the delay time of PCM1717:

$$T_D = 11.125 \times 1/f_s$$

For $f_s = 44.1\text{kHz}$, $T_D = 11.125/44.1\text{kHz} = 251.4\mu\text{s}$

Applications using data from a disc or tape source, such as CD audio, CD-Interactive, Video CD, DAT, Minidisc, etc., generally are not affected by delay time. For some professional applications such as broadcast audio for studios, it is important for total delay time to be less than 2ms.

INTERNAL RESET

When power is first applied to PCM1717, an automatic reset function occurs after 1,024 cycles of XTI clock. Refer to Table I for default conditions. During the first 1,024 cycles of XTI clock, PCM1717 cannot be programmed (Software Control). Data can be loaded into the control registers during this time, and after 1,204 cycles of XTI clock, a "LOW" on ML (pin 18) will initiate programming.

OUTPUT FILTERING

For testing purposes all dynamic tests are done on the PCM1717 using a 20kHz low pass filter. This filter limits the measured bandwidth for THD+N, etc. to 20kHz. Failure to use such a filter will result in higher THD+N and lower SNR and Dynamic Range readings than are found in the specifications. The low pass filter removes out of band noise. Although it is not audible, it may affect dynamic specification numbers.

The performance of the internal low pass filter from DC to 24kHz is shown in Figure 14. The higher frequency rolloff of the filter is shown in Figure 15. If the user's application has the PCM1717 driving a wideband amplifier, it is recommended to use an external low pass filter. A simple 3rd-order filter is shown in Figure 16. For some applications, a passive RC filter or 2nd-order filter may be adequate.




FIGURE 14. Low Pass Filter Frequency Response.




FIGURE 15. Low Pass Filter Frequency Response.




FIGURE 16. 3rd-Order LPF.




FIGURE 17. Test Block Diagram.

TEST CONDITIONS

Figure 17 illustrates the actual test conditions applied to PCM1717 in production. The 11th-order filter is necessary in the production environment for the removal of noise resulting from the relatively long physical distance between the unit and the test analyzer. In most actual applications, the 3rd-order filter shown in Figure 16 is adequate. Under normal conditions, THD+N typical performance is -70dB with a 30kHz low pass filter (shown here on the THD meter), improving to -89dB when the external 20kHz 11th-order filter is used.

EVALUATION FIXTURES

Three evaluation fixtures are available for PCM1717.

DEM-PCM1717

This evaluation fixture is primarily intended for quick evaluation of the PCM1717's performance. DEM-PCM1717 can accept either an external clock or a user-installed crystal oscillator. All of the functions can be controlled by on-board switches. DEM-PCM1717 does not contain a receiver chip or an external low pass filter. DEM-PCM1717 requires a single +5V power supply.

OUT-OF-BAND NOISE CONSIDERATIONS

Delta-sigma DACs are by nature very sensitive to jitter on the master clock. Phase noise on the clock will result in an increase in noise, ultimately degrading dynamic range. It is difficult to quantify the effect of jitter due to problems in synthesizing low levels of jitter. One of the reasons delta-sigma DACs are prone to jitter sensitivity is the large quantization noise when the modulator can only achieve two discrete output levels (0 or 1). The multi-level delta-sigma DAC has improved theoretical SNR because of multiple output states. This reduces sensitivity to jitter. Figure 18 contrasts jitter sensitivity between a one-bit PWM type DAC and multi-level delta-sigma DAC. The data was derived using a simulator, where clock jitter could be completely synthesized.




FIGURE 18. Simulation Results of Clock Jitter Sensitivity.




FIGURE 19. Simulation Method for Clock Jitter.