

SANYO	No.1599A	2SA1317/2SC3330
		PNP/ NPN Epitaxial Planar Silicon Transistors
AF Amp Applications		

Use

. Capable of being used in the low frequency to high frequency range.

Features

. Large current capacity and wide ASO.

(): 2SA1317

Absolute Maximum Ratings at Ta=25°C

			unit
Collector to Base Voltage	V _{CB0}	(-)60	V
Collector to Emitter Voltage	V _{CEO}	(-)50	V
Emitter to Base Voltage	V _{EB0}	(-)6	V
Collector Current	I _C	(-)200	mA
Collector Current (Pulse)	I _{CP}	(-)400	mA
Collector Dissipation	P _C	300	mW
Junction Temperature	T _J	150	°C
Storage Temperature	T _{stg}	-55 to +150	°C

Electrical Characteristics at Ta=25°C


		min	typ	max	unit
Collector Cutoff Current	I _{CB0}	V _{CB} = (-)40V, I _E = 0		(-)0.1	μA
Emitter Cutoff Current	I _{EB0}	V _{EB} = (-)5V, I _C = 0		(-)0.1	μA
DC Current Gain	h _{FE} (1)	V _{CE} = (-)6V, I _C = (-)1mA	100*	800*	
			(100)	(560)	
	h _{FE} (2)	V _{CE} = (-)6V, I _C = (-)0.1mA	70		
Gain-Bandwidth Product	f _T	V _{CE} = (-)6V, I _C = (-)10mA		200	MHz
Output Capacitance	C _{ob}	V _{CB} = (-)6V, f = 1MHz		3.0	pF
				(4.0)	

Continued on next page.

* The 2SA1317/2SC3330 are classified by 1mA h_{FE} as follows:

2SA1317	100	R	200	140	S	280	200	T	400	280	U	560			
2SC3330	100	R	200	140	S	280	200	T	400	280	U	560	400	V	800

Case Outline 2033
(unit:mm)



SANYO: SPA

B: Base
C: Collector
E: Emitter

Specifications and information herein are subject to change without notice.

SANYO Electric Co., Ltd. Semiconductor Business Headquarters
TOKYO OFFICE Tokyo Bldg., 1-10, 1 Chome, Ueno, Taito-ku, TOKYO, 110 JAPAN

Continued from preceding page.

		min	typ	max	unit
Collector to Emitter Saturation Voltage	$V_{CE(sat)}$	$I_C = (-)100mA, I_B = (-)10mA$		(-)0.3	V
Base to Emitter Saturation Voltage	$V_{BE(sat)}$	$I_C = (-)100mA, I_B = (-)10mA$		(-)1.0	V
Collector to Base Breakdown Voltage	$V_{(BR)CBO}$	$I_C = (-)10\mu A, I_E = 0$		(-)60	V
Collector to Emitter Breakdown Voltage	$V_{(BR)CEO}$	$I_C = (-)1mA, R_{BE} = \infty$		(-)50	V
Emitter to Base Breakdown Voltage	$V_{(BR)EBO}$	$I_E = (-)10\mu A, I_C = 0$		(-)6	V

