

<b>SANYO</b>	No.2020A	<b>2SB1141/2SD1681</b>
		PNP/NPN Epitaxial Planar Silicon Transistors <b>18V/1.2A Switching Applications</b>

**Applications**

- Converters, relay drivers, low-voltage and high power AF Amp.

**Features**

- Low saturation voltage and excellent linearity of  $h_{FE}$ .
- Wide ASO.

( ) : 2SB1141

**Absolute Maximum Ratings at Ta = 25°C**

			unit
Collector-to-Base Voltage	$V_{CBO}$	(- )20	V
Collector-to-Emitter Voltage	$V_{CEO}$	(- )18	V
Emitter-to-Base Voltage	$V_{EBO}$	(- )5	V
Collector Current	$I_C$	(- )1.2	A
Collector Current (Pulse)	$I_{CP}$	(- )2.0	A
Collector Dissipation	$P_C$	1.5	W
		10	W
Junction Temperature	$T_j$	150	°C
Storage Temperature	$T_{stg}$	- 55 to + 125	°C

$T_c = 25^\circ C$

**Electrical Characteristics at Ta = 25°C**


			min	typ	max	unit
Collector Cutoff Current	$I_{CBO}$	$V_{CB} = (-)15V, I_E = 0$			(- )100	nA
Emitter Cutoff Current	$I_{EBO}$	$V_{EB} = (-)4V, I_C = 0$			(- )100	nA
DC Current Gain	$h_{FE(1)}$	$V_{CE} = (-)2V, I_C = (-)100mA$	70*		400*	
	$h_{FE(2)}$	$V_{CE} = (-)2V, I_C = (-)1A$	40			
Gain-Bandwidth Product	$f_T$	$V_{CE} = (-)10V, I_C = (-)50mA$		150		MHz
Output Capacitance	$C_{ob}$	$V_{CB} = (-)10V, f = 1MHz$		(30)20		pF
C-E Saturation Voltage	$V_{CE(sat)}$	$I_C = (-)500mA, I_B = (-)50mA$		(- )170	(- )400	mV
				120	300	mV
B-E Saturation Voltage	$V_{BE(sat)}$	$I_C = (-)500mA, I_B = (-)50mA$		(- )0.85	(- )1.2	V
C-B Breakdown Voltage	$V_{(BR)CBO}$	$I_C = (-)10\mu A, I_E = 0$	(- )20			V
C-E Breakdown Voltage	$V_{(BR)CEO}$	$I_C = (-)1mA, R_{BE} = \infty$	(- )18			V
E-B Breakdown Voltage	$V_{(BR)EBO}$	$I_E = (-)10\mu A, I_C = 0$	(- )5			V

Continued on next page.

\* : The 2SB1141/2SD1681 are classified by 100mA  $h_{FE}$  as follows

70	Q	140	100	R	200	140	S	280	200	T	400
----	---	-----	-----	---	-----	-----	---	-----	-----	---	-----

**Package Dimensions 2042A**  
(unit : mm)




SANYO: TO126ML

2SB1141/2SD1681







Continued from preceding page.

		min	typ	max	unit
Turn-on Time	$t_{on}$		50		ns
Storage Time	$t_{stg}$		(60)200		ns
Fall Time	$t_f$		70		ns









Switching Time Test Circuit





Unit (Resistance :  $\Omega$ , Capacitance : F)  
 $I_C = 10I_{B1} = -10I_{B2} = 500\text{mA}$   
 (For PNP, the polarity is reversed).



2SB1141/2SD1681



2SB1141/2SD1681



- No products described or contained herein are intended for use in surgical implants, life-support systems, aerospace equipment, nuclear power control systems, vehicles, disaster/crime-prevention equipment and the like, the failure of which may directly or indirectly cause injury, death or property loss.
- Anyone purchasing any products described or contained herein for an above-mentioned use shall:
  - ① Accept full responsibility and indemnify and defend SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors and all their officers and employees, jointly and severally, against any and all claims and litigation and all damages, cost and expenses associated with such use:
  - ② Not impose any responsibility for any fault or negligence which may be cited in any such claim or litigation on SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors or any of their officers and employees jointly or severally.
- Information (including circuit diagrams and circuit parameters) herein is for example only; it is not guaranteed for volume production. SANYO believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.