

2SC1755, 1756, 1757

NPN Triple Diffused Planar Silicon Transistors
FOR CHROMA OUTPUT & AF OUTPUT OF COLOR TV
FOR VIDEO OUTPUT & AF OUTPUT OF B/W TV

These 2SC1755,1756,1757 are different only from their packages.

Absolute Maximum Ratings at Ta=25°C


Collector to Base Voltage	VCBO	300	V	
Collector to Emitter Voltage	VCEO	300	V	
Emitter to Base Voltage	VEBO	7	V	
Collector Current	IC	200	mA	
Peak Collector Current	icp	700	mA	
Collector Dissipation	PC	1.2	W	
	PC	Tc=25°C	15	W
Junction Temperature	Tj	150	°C	
Storage Temperature	Tstg	-40 to +150	°C	

Electrical Characteristics at Ta=25°C

Collector Cutoff Current	I_{CBO}	$V_{CB}=200V, I_E=0$	0.1	μA
Emitter Cutoff Current	I_{EBO}	$V_{EB}=5V, I_C=0$	0.1	μA
DC Current Gain	h_{FE}	$V_{CE}=10V, I_C=10mA$	40*	200*
Gain Bandwidth Product	f_T	$V_{CE}=30V, I_C=10mA$	50	MHz
Output Capacitance	c_{ob}	$V_{CB}=50V, f=1MHz$	5.3	pF
C-E Saturation Voltage	$V_{CE(sat)}$	$I_C=50mA, I_B=5mA$	2.0	V

* The 2SC1755, 1756, 1757 are classified as follows.







40	C	80	60	D	120	100	E	200
----	---	----	----	---	-----	-----	---	-----



These specifications are subject to change without notice.

SANYO ELECTRIC CO., LTD. SEMICONDUCTOR DIVISION
5-1-1 HIRUMI, SUTONANAKA, CHUO-KU, TOKYO 100, JAPAN

4157KI/3185MW, TS No. 429-1/2



Information furnished by SANYO is believed to be accurate and reliable. However, no responsibility is assumed by SANYO for its use; nor for any infringements of patents or other rights of third parties which may result from its use, and no license is granted by implication or otherwise under any patent or patent rights of SANYO.