

SANYO

No.2734

LA7320, 7320M

Monolithic Linear IC

VHS VTR Playback Head Amplifier
Recording Amplifier**Functions and Features**

(Functions) · 2-channel playback head amp

- 1-channel recording amp
- PB : 1 head select switch
- REC : 3 head select switches

(Features) · Designed for 2 heads

- On-chip driver transistor permitting direct recording (current type)
- On-chip head select switches (2 types) facilitating printed circuit pattern design of a set
- Load variations cause less recording current variations because of recording amp of constant-current type.

(Maximum recording current : 40mA_{p-p})**Maximum Ratings at Ta = 25°C**


			unit
Maximum Supply Voltage	V _{CC} max	(PB) 7.0	V
		(REC) 14.0	V
Allowable Power Dissipation	P _d max	(DIP) 750	mW
Operating Temperature	T _{opg}	-10 to +65	°C
Storage Temperature	T _{stg}	-40 to +125	°C

Operating Conditions at Ta = 25°C

			unit
Recommended Supply Voltage	V _{CC}	(PB) 5.0	V
		(REC) 12.0	V
Operating Voltage Range	V _{CC} op	(PB) 4.75 to 5.5	V
		(REC) 10 to 13	V

Case Outline 3059-D22SIC


(unit : mm) [LA7320]



SANYO: DIP22S

Case Outline 3108-M24IC

(unit : mm) [LA7320M]




SANYO: MFP24D

Specifications and information herein are subject to change without notice.

SANYO Electric Co., Ltd. Semiconductor Overseas Marketing Div.
 Natsume Bldg., 18-6, 2-chome, Yushima, Bunkyo ku, TOKYO 113 JAPAN

N228TA, TS No.2734-1/6

LA7320 Test Circuit

Operating Characteristics at $T_a = 25^\circ\text{C}$

Characteristic	Symbol	Test Conditions		min	typ	max	unit
		Input	Output				
(PB Mode)		T2		PB + 5V	RF	REC MUTE	
Current Dissipation	I_{ccp}	T2		Pin 2 flow-in current	1		nA
Voltage Gain	CH1 $G_{vp}(1)$	T19	T3	$V_i = 38\text{mVpp}$ $f = 1\text{MHz}$	1		dB
	CH2 $G_{vp}(2)$	T16	T3		1		
Voltage Gain Difference	ΔG_{vp}			$G_{vp}(1) - (2)$			dB
Equivalent Input Noise Voltage	CH1 $V_{Ni}(1)$		T3	V_{out} $G_{vp}(1), (2)$ after 1.1MHz L.P.F.	2		μV_{rms}
	CH2 $V_{Ni}(2)$		T3		1		
Frequency Characteristic	CH1 $\Delta V_{fp}(1)$	T19	T3	$V_i = 30\text{mVpp}$ $f = 100\text{kHz}, 7\text{MHz}$	2		dB
	CH2 $\Delta V_{fp}(2)$	T16	T3	100kHz output ratio	1		
2nd Harmonic Distortion	CH1 $V_{HDP}(1)$	T19	T3	$V_i = 38\text{mVpp}$ $f = 4\text{MHz}$	2		dB
	CH2 $V_{HDP}(2)$	T16	T3	8M component 4M component output ratio	1		
Maximum Output Level	CH1 $V_{OMP}(1)$	T19	T3	$V_i = 1\text{MHz}$ Output level when 3rd distortion is -30dB.	2		Vpp
	CH2 $V_{OMP}(2)$	T16	T3		1		
Crosstalk	CH1 $V_{CR}(1)$	T16	T3	$V_i = 38\text{mVpp}$ $f = 4\text{MHz}$	2		dB
	CH2 $V_{CR}(2)$	T19	T3	V_{out} $G_{vp}(1), (2)$ output ratio	1		
Output DC Offset	ΔV_{ONC}		Pin 3	Output pin DC voltage difference	2→1		mV

Continued on next page.

Continued from preceding page.

Characteristic		Symbol	Test Conditions		SW1	SW2	min	typ	max	unit
			Input	Output						
(REC Mode)			T11		REC + 12V	RF	REC MUTE			
Current Dissipation		I _{ccR}	T11		Pin 11 flow-in current		2	46.0	57.0	mA
Voltage Gain	C	G _{VR} (C)	T5	T13	V _i = 300mVpp f = 1MHz		2	-8.0	-6.0	-4.0
	Y	G _{VR} (Y)	T6	T13	V _i = 300mVpp f = 4MHz		2	-8.0	-6.0	-4.0
Frequency Characteristic	C	ΔV _m (C)	T5	T13	V _i = 300mVpp f = 1MHz, 7MHz		2			
	Y	ΔV _m (Y)	T6	T13	7M 1M output ratio		2	-2.0	-0.6	1.0
2nd Harmonic Distortion	C	V _{HDR} (C)	T5	T13	V _{out} = 30mApp f = 4MHz		2			
	Y	V _{HDR} (Y)	T6	T13	8M component 4M component output ratio		2	-46	-40	dB
Maximum Output Level	C	V _{OMP} (C)	T5	T13	f = 4MHz Output level when 2nd distortion is -40dB.		2	30	40	mApp
	Y	V _{OMP} (Y)	T6	T13			2			
Muting Attenuation	C	V _{MR} (C)	T5	T13	V _i = 300mVpp f = 1MHz, 4MHz		1			
	Y	V _{MR} (Y)	T6	T13	V _{out} G _{MR} (1)/(2) output ratio		1	-50	-45	dB
Cross Modulation Relative Level		VCY	T5 T6	T13	Input T5, V _{out} = 40mVpp, f = 629kHz Input T6, V _{out} = 150mVpp, f = 4MHz 4M ± 629K / 4MHz output ratio		2	-45	-40	dB
Y/C MIX Amp Voltage Gain	C	G(C)	T5	T9	V _i = 300mVpp f = 1MHz			8.0	10.5	13.0
	Y	G(Y)	T6	T9	V _i = 300mVpp f = 4MHz					dB
(Switch Tr) ON Resistance										
ON Resistance of SW turned ON at PB		R _{PON} (14)		Pin 14	PB mode ※1 Difference between DC voltage at 1mA flow-in and DC voltage at 2mA flow-in			6	10	Ω
ON Resistance of SW turned ON at REC	CH1	R _{RON} (19)		Pin 19	REC mode ※1 Difference between DC voltage at 1mA flow-in and DC voltage at 2mA flow-in			7	10	Ω
	CH2	R _{RON} (16)		Pin 19						
Switch Tr Leakage Current										
Leakage Current of SW Tr turned ON at PB		I _L (14)		Pin 14	REC mode Flow-in current when ±5V is applied			-2	0	2


Continued on next page.

Continued from preceding page.


Characteristic	Symbol						min	typ	max	unit	
		Input	Output	Test Conditions		SW1					SW2
Control Pin (Threshold Level)											
RF Switch (Threshold Level)	SW RF(1)	T1		CH1→CH2 changeover voltage			2.5		5.0	V	
	SW RF(2)			CH2→CH1 changeover voltage			0		0.8		
REC Muting Switch Threshold Level	SW MUTE(1)	T10		T10 voltage when T13 output waveform dis- appears			2.6		5.0	V	
	SW MUTE(2)			T10 voltage when T13 output waveform appears			0		0.8		

※1 Let the ON resistance to be obtained be x ,
 $2x(\text{mV})$ at 2mA flow-in $x(\text{mV})$ at 1mA flow-in
 Therefore, difference $2x - x = x$ is the ON resistance.









LA7320 (DIP22S) Block Diagram



LA7320M (MFP24) Block Diagram






Pin Description

Pin No.	Function	Standard Potential	Input/Output Configuration	Remarks
1	RF 30Hz control pin			"L": CH1 at open state or 0.8V or less "H": CH2 at 2.5 to 5.0V
2	PB +5V	5.0 (V)		12mA typ.
3	Preamp output	2.3 (V)		Connect R=2kΩ externally when the output line is routed around.
4	Preamp GND	0 (V)		
5	REC amp input	6.7 (V)		
6				
7	REC amp GND	0 (V)		
8	REC Y/C MIX amp feedback pin	5.9 (V)		The gain of Y/C MIX amp depends on R1. (Example) R1 : 180Ω = 10.5dB
9	REC Y/C MIX amp output			
10	REC muting control pin			"L": Muting OFF at open state or 0.8V or less "H": Muting ON at 2.5V to 5.0V
11	REC +12V	12.0 (V)		Typ.
12	REC current amp feedback pin	5.9 (V)		
13	REC current amp output pin	5.9 (V)		Max. REC current : 40mA p-p (2ch)
14	Pin for switch Tr turned ON at PB			ON resistance : 6 to 10kΩ

Continued on next page.

Continued from preceding page.

Pin No.	Function	Standard Potential	Input/Output Configuration	Remarks
15 22	Preamp bypass capacitor	1.9 (V)		
16 19	Preamp input	0.65 (V)		$R_{in} \approx 400\Omega$ $C_{in} \approx 25$ to $35p$
17	Pre GND	0 (V)		
18				Switch Tr ON resistance : 7 to 10Ω
21 22	N·C			

The application circuit diagrams and circuit constants herein are included as an example and provide no guarantee for designing equipment to be mass-produced.

The information herein is believed to be accurate and reliable. However, no responsibility is assumed by SANYO for its use; nor for any infringements of patents or other rights of third parties which may result from its use.