

LED display

3桁LED数字表示

3 Digits LED numeric display

Ta=25°C

字高 Character height	機 種 名 Type No.		ピーク発光波長 Peak-emission wavelength	絶対最大定格 Absolute maximum ratings					推奨動作電流 Recommend. If/seg	電気的光学的特性 Electro-optical characteristics				
				If/seg	I _F /seg	V _R /seg	P ₀	T _{opr}		V _F Typ.	I _F	Luminous intensity I _v Typ.	I _F	I _n Max.
mm	Com.-Anode	Com.-Cathode	nm (Color)	mA	mA	V	W	°C	mA	V	mA	μcd/seg	mA	(V _R =3V) μA/seg
7.62	SL-1341	SL-1342	700 (R)	20	40	3	1	-25~+70	3~10	1.9	5	350	5	10
	SL-2341	SL-2342	565 (G)	20	40	3	1.1	-25~+70	10~15	2.05	15	800	15	10
	SL-1341-20	SL-1342-20	700 (R)	20	40	3	1	-25~+70	3~10	1.9	5	350	5	10
	SL-2341-20	SL-2342-20	565 (G)	20	40	3	1.1	-25~+70	10~15	2.05	15	800	15	10
10.16	SL-1323-20	SL-1324-20	700 (R)	20	40	3	1	-25~+70	3~10	1.9	5	350	5	10
	SL-2323-20	SL-2324-20	565 (G)	20	40	3	1.1	-25~+70	10~15	2.05	15	800	15	10
14.3	SL-1351	SL-1352	700 (R)	20	40	3	1	-25~+70	3~10	1.9	5	400	5	10
	SL-2351	SL-2352	565 (G)	20	40	3	1.1	-25~+70	10~15	2.05	15	1500	15	10
	SL-1351-60	SL-1352-60	700 (R)	20	40	3	1	-25~+70	3~10	1.9	5	400	5	10
	SL-2351-60	SL-2352-60	565 (G)	20	40	3	1.1	-25~+70	10~15	2.05	15	1500	15	10

■外観図

Package dimensions

Tolerance : ±0.25
Unit : mm

