

D.P.P. (DARLINGTON POWER PACK) thick film hybrid ICCIRCUIT DRAWING
No.6001~6003**OUTPUT STAGE OF AF POWER AMP.****Features**

General output stage of power amplifier has a difficult and complex problem about heat sink designing and its setting. Sanyo's D.P.P. intends to decrease electronic parts and rationalize a manufacturing process by designing IC of only output stage of power amplifier.

- IMST system.
- Output stage for AF high power amplifier.
- Dual power supply.

- Darlington type pure / quasi-complementary circuit.
- These same pin assignment and pin interval lead to standardize a printed board.
- Metal substrate use IMST® makes good thermal stability.
- Able to design freely previous section of power amplifier. This leads tone control designing.

Type Number		Maximum Ratings at Ta=25°C								Operation Characteristics at Ta=25°C		
		Case Outline	Maximum Supply Voltage VCCmax.	Junction Temperature Tj	Storage Temperature Tstg	Thermal Resistance θ	Collector Current ICM	Allowable Latched Shorting Time tSL	Supply Voltage at Rated Power PRL	Output Power Po (f=20 to 20kHz)	Total Harmonic Distortion THD (f=20 to 20kHz)	Quiescent Current Icco
		Pure-Complementary Circuit	Quasi-Complementary Circuit	°C	°C	°C/W	A	sec	V	W	%	mA
1-Channel Darlington Power Pack (Without emitter resistance)												
STK0080		4006	±65	150	-30 to +105	1.3	10	—	±46	80 min.	0.1 max.	40 typ, 80 max.
STK0100		4006	±75	150	-30 to +105	1.1	12	—	±50	100 min.	0.1 max.	40 typ, 80 max.
1-Channel Darlington Power Pack (With emitter resistance)												
STK1030		4004	±40	150	-30 to +105	2.4	5	2	±28.5	30 min.	0.02 max.	40 typ, 80 max.
STK1040		4004	±48	150	-30 to +105	1.8	7	2	±33	40 min.	0.02 max.	40 typ, 80 max.
STK1050		4004	±53	150	-30 to +105	1.8	7	2	±36	50 min.	0.02 max.	40 typ, 80 max.
STK1060		4004	±56	150	-30 to +105	1.6	10	—	±40	60 min.	0.02 max.	40 typ, 80 max.
STK1070		4006	±60	150	-30 to +125	1.3	10	—	±43	70 min.	0.02 max.	40 typ, 80 max.
2-Channel Darlington Power Pack (With emitter resistance)												
STK2230		4015	±48	150	-30 to +105	2.1	4	2	±30	30x2 min.	0.01 max.	35 typ, 80 max.
STK2240		4015	±54	150	-30 to +105	1.8	5	2	±33.5	40x2 min.	0.01 max.	35 typ, 80 max.
STK2250		4015	±59	150	-30 to +105	1.8	5	2	±37	50x2 min.	0.01 max.	35 typ, 80 max.

STK075 SERIES

thick film hybrid IC

CIRCUIT DRAWING
No.6004**20 TO 35W MIN AF POWER AMP.**


4007

Features

- ©IMST, 1 Channel by 2 Power Supplies.
- AF output power STK 077: 20W min., STK 078: 24W min., STK 080: 30W min., STK 082: 35W min.
- Differential amp. constant current driving.
- Capable of tone controlling.
- STK 078-105 and STK 082-105 are for the use of Tc=105°C.

STK084,085-105 086

thick film hybrid IC

CIRCUIT DRAWING
No.6005**50 TO 70W MIN AF POWER AMP.**

4007(STK084,086)

4030(STK085-105)

Features

- ©IMST, 1 Channel by 2 Power Supply.
- AF Output Power STK 084: 50 Wmin. STK 085-105: 60 Wmin. STK 086: 70 Wmin.
- Capable of setting protector for load shorting and tone controller.