



T-1¼ Subminiature Lamps

Line No.	Part No. Wire Lead	Part No. Miniature Flanged	Part No. Bi-Pin	Volts	Amps	M.S.C.P.	Filament Type	Life Hours
13	2135	7302	7306	1.3	0.030	0.006	S-2	100
14	8631	8636	7636	1.35	0.060	0.006	C-2R	500
15	8655	8656	7307	2.5	0.400	0.55	C-2R	30
16	324	8637	7637	3.0	0.190	0.25	C-2R	350
17	8816	7305	7308	4.5	0.285	0.80	C-2R	100
18	580	3582	7580	5.0	0.060	0.03	C-2R	100,000
19	583	3585	7583	5.0	0.060	0.05	C-2R	100,000
20	515	3518	7515	5.0	0.115	0.15	C-2R	40,000
21	8661	8660	7660	6.0	0.040	0.06	C-2R	1,000
22	2114	8541	7309	6.0	0.060	0.13	C-2R	3,000
23	634	8628	7628	6.0	0.200	0.63	C-2R	1,000
24	8610	8551	7310	6.3	0.200	0.55	C-2R	5,000
25	8608	8609	7311	10.0	0.070	0.14	C-2F	10,000
26	8640	8646	7646	14.0	0.080	0.50	C-2F	1,000
27	8627	8632	7632	28.0	0.040	0.32	C-2F	1,000

