


# MICRO ELECTRONICS

2N5232

NPN SILICON  
TRANSISTOR

2N5232 is NPN silicon planar transistor use in general purpose applications.

TO-92B



ECB

### ABSOLUTE MAXIMUM RATINGS

Collector-Emitter Voltage	V <sub>CEO</sub>	50V
Collector-Base Voltage	V <sub>CB0</sub>	70V
Emitter-Base Voltage	V <sub>EB0</sub>	5V
Collector Current	I <sub>C</sub>	100mA
Total Power Dissipation	P <sub>tot</sub>	330mW
Operating Junction & Storage Temperature	T <sub>j</sub> , T <sub>stg</sub>	-55 to +150°C

### ELECTRICAL CHARACTERISTICS (T<sub>a</sub>=25°C)

PARAMETER	SYMBOL	MIN	MAX	UNIT	TEST CONDITIONS
Collector-Emitter Breakdown Voltage	LV <sub>CEO</sub>	50		V	I <sub>C</sub> =10mA IB=0
Collector-Base Breakdown Voltage	BV <sub>CB0</sub>	70		V	I <sub>C</sub> =100μA IE=0
Emitter-Base Breakdown Voltage	BV <sub>EB0</sub>	5		V	IE=100μA IC=0
Collector Cutoff Current	IC <sub>B0</sub>		30	nA	VCB=50V IE=0
Collector Cutoff Current	IC <sub>ES</sub>		30	nA	VCB=50V VEB=0
Emitter Cutoff Current	IE <sub>B0</sub>		50	nA	VEB=5V IC=0
D.C. Current Gain	H <sub>FE</sub>	250	500		I <sub>C</sub> =2mA VCE=10V
Base-Emitter Voltage	V <sub>BE</sub>		0.9	V	I <sub>C</sub> =2mA VCE=10V
Collector-Emitter Saturation Voltage	V <sub>CE(sat)</sub>		0.12	V	I <sub>C</sub> =10mA IB=1mA
Base-Emitter Saturation Voltage	V <sub>BE(sat)</sub>		0.78	V	I <sub>C</sub> =10mA IB=1mA
Output Capacitance	C <sub>ob</sub>		4	pF	VCB=10V f=1MHz

MICRO ELECTRONICS LTD. 美科有限公司

38, Hung To Road, Microtron Building, Kwun Tong, Kowloon, Hong Kong.  
Kwun Tong P.O. Box 69477 Hong Kong. Fax No. 341 0321 Telex: 43510 Micro Hx. Tel: 343 0181-5