


### Features


- Epitaxial Planar Die Construction
- Complementary PNP Types Available (DDTA)
- Built-In Biasing Resistor, R1 only
- Also Available in Lead Free Version

### Mechanical Data

- Case: SOT-323, Molded Plastic
- Case Material - UL Flammability Rating 94V-0
- Moisture sensitivity: Level 1 per J-STD-020A
- Terminals: Solderable per MIL-STD-202, Method 208
- Also Available in Lead Free Plating (Matte Tin Finish). Please see Ordering Information, Note 3, on Page 2
- Terminal Connections: See Diagram
- Marking: Date Code and Marking Code (See Diagrams & Page 2)
- Weight: 0.006 grams (approx.)
- Ordering Information (See Page 2)



| SOT-323              |              |      |
|----------------------|--------------|------|
| Dim                  | Min          | Max  |
| A                    | 0.25         | 0.40 |
| B                    | 1.15         | 1.35 |
| C                    | 2.00         | 2.20 |
| D                    | 0.65 Nominal |      |
| E                    | 0.30         | 0.40 |
| G                    | 1.20         | 1.40 |
| H                    | 1.80         | 2.20 |
| J                    | 0.0          | 0.10 |
| K                    | 0.90         | 1.00 |
| L                    | 0.25         | 0.40 |
| M                    | 0.10         | 0.18 |
| $\alpha$             | 0°           | 8°   |
| All Dimensions in mm |              |      |



SCHEMATIC DIAGRAM

| P/N        | R1 (NOM)      | MARKING |
|------------|---------------|---------|
| DDTC113TUA | 1K $\Omega$   | N01     |
| DDTC123TUA | 2.2K $\Omega$ | N03     |
| DDTC143TUA | 4.7K $\Omega$ | N07     |
| DDTC114TUA | 10K $\Omega$  | N12     |
| DDTC124TUA | 22K $\Omega$  | N16     |
| DDTC144TUA | 47K $\Omega$  | N19     |
| DDTC115TUA | 100K $\Omega$ | N23     |
| DDTC125TUA | 200K $\Omega$ | N25     |

### Maximum Ratings @ T<sub>A</sub> = 25°C unless otherwise specified

| Characteristic                                       | Symbol                            | Value       | Unit |
|------------------------------------------------------|-----------------------------------|-------------|------|
| Collector-Base Voltage                               | V <sub>CBO</sub>                  | 50          | V    |
| Collector-Emitter Voltage                            | V <sub>CEO</sub>                  | 50          | V    |
| Emitter-Base Voltage                                 | V <sub>EBO</sub>                  | 5           | V    |
| Collector Current                                    | I <sub>C</sub> (Max)              | 100         | mA   |
| Power Dissipation                                    | P <sub>d</sub>                    | 200         | mW   |
| Thermal Resistance, Junction to Ambient Air (Note 1) | R <sub>θJA</sub>                  | 833         | °C/W |
| Operating and Storage and Temperature Range          | T <sub>j</sub> , T <sub>STG</sub> | -55 to +150 | °C   |

Note: 1. Mounted on FR4 PC Board with recommended pad layout at <http://www.diodes.com/datasheets/ap02001.pdf>.

**Electrical Characteristics** @  $T_A = 25^\circ\text{C}$  unless otherwise specified


| Characteristic                       | Symbol        | Min | Typ | Max | Unit          | Test Condition                                                                                                                                                                                                                                                                                                                                                                                                  |
|--------------------------------------|---------------|-----|-----|-----|---------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Collector-Base Breakdown Voltage     | $BV_{CBO}$    | 50  | —   | —   | V             | $I_C = 50\mu\text{A}$                                                                                                                                                                                                                                                                                                                                                                                           |
| Collector-Emitter Breakdown Voltage  | $BV_{CEO}$    | 50  | —   | —   | V             | $I_C = 1\text{mA}$                                                                                                                                                                                                                                                                                                                                                                                              |
| Emitter-Base Breakdown Voltage       | $BV_{EBO}$    | 5   | —   | —   | V             | $I_E = 50\mu\text{A}$                                                                                                                                                                                                                                                                                                                                                                                           |
| Collector Cutoff Current             | $I_{CBO}$     | —   | —   | 0.5 | $\mu\text{A}$ | $V_{CB} = 50\text{V}$                                                                                                                                                                                                                                                                                                                                                                                           |
| Emitter Cutoff Current               | $I_{EBO}$     | —   | —   | 0.5 | $\mu\text{A}$ | $V_{EB} = 4\text{V}$                                                                                                                                                                                                                                                                                                                                                                                            |
| Collector-Emitter Saturation Voltage | $V_{CE(sat)}$ | —   | —   | 0.3 | V             | $I_C/I_B = 10\text{mA}/1\text{mA}$ DDTC113TUA<br>$I_C/I_B = 5\text{mA}/0.5\text{mA}$ DDTC123TUA<br>$I_C/I_B = 2.5\text{mA}/.25\text{mA}$ DDTC143TUA<br>$I_C/I_B = 1\text{mA}/.1\text{mA}$ DDTC114TUA<br>$I_C/I_B = 5\text{mA}/0.5\text{mA}$ DDTC124TUA<br>$I_C/I_B = 2.5\text{mA}/.25\text{mA}$ DDTC144TUA<br>$I_C/I_B = 1\text{mA}/0.1\text{mA}$ DDTC115TUA<br>$I_C/I_B = .5\text{mA}/.05\text{mA}$ DDTC125TUA |
| DC Current Transfer Ratio            | $h_{FE}$      | 100 | 250 | 600 | —             | $I_C = 1\text{mA}$ , $V_{CE} = 5\text{V}$                                                                                                                                                                                                                                                                                                                                                                       |
| Input Resistor ( $R_1$ ) Tolerance   | $\Delta R_1$  | -30 | —   | +30 | %             | —                                                                                                                                                                                                                                                                                                                                                                                                               |
| Gain-Bandwidth Product*              | $f_T$         | —   | 250 | —   | MHz           | $V_{CE} = 10\text{V}$ , $I_E = -5\text{mA}$ ,<br>$f = 100\text{MHz}$                                                                                                                                                                                                                                                                                                                                            |

\* Transistor - For Reference Only

**Ordering Information** (Note 2)

| Device        | Packaging | Shipping           |
|---------------|-----------|--------------------|
| DDTC1xxTUA-7  | SOT-323   | 3000/Tape & Reel   |
| DDTC1xxTUA-13 | SOT-323   | 10,000/Tape & Reel |

- Notes:
- For Packaging Details, go to our website at <http://www.diodes.com/datasheets/ap02007.pdf>.
  - For Lead Free version (with Lead Free terminal finish) part number, please add "-F" suffix to part number above.  
Example: DDTC125TUA-7-F.

**Marking Information**


XXX = Product Type Marking Code  
 See Sheet 1 Diagrams  
 YM = Date Code Marking  
 Y = Year ex: N = 2002  
 M = Month ex: 9 = September

**Date Code Key**

| Year | 2002 | 2003 | 2004 | 2005 | 2006 | 2007 | 2008 | 2009 |
|------|------|------|------|------|------|------|------|------|
| Code | N    | P    | R    | S    | T    | U    | V    | W    |

| Month | Jan | Feb | March | Apr | May | Jun | Jul | Aug | Sep | Oct | Nov | Dec |
|-------|-----|-----|-------|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| Code  | 1   | 2   | 3     | 4   | 5   | 6   | 7   | 8   | 9   | O   | N   | D   |

**TYPICAL CURVES - DDTC114TUA**
