2SD1892

Silicon NPN triple diffusion planar type Darlington

For power amplification
Complementary to 2SB1252



Features

- Optimum for 35W HiFi output
- High foward current transfer ratio h_{FE}: 5000 to 30000
- Low collector to emitter saturation voltage $V_{CE(sat)}$: <2.5V
- Full-pack package which can be installed to the heat sink with one screw

Absolute Maximum Ratings (T_C=25˚C)

Parameter		Symbol	Ratings	Unit
Collector to base voltage		V_{CBO}	120	V
Collector to emitter voltage		V_{CEO}	100	V
Emitter to base voltage		V_{EBO}	5	V
Peak collector current		I_{CP}	8	A
Collector current		I_C	5	A
Collector power dissipation	T_C=25°C	P_C	45	W
	Ta=25°C		2	
Junction temperature		T_j	150	˚C
Storage temperature		T_{stg}	–55 to +150	˚C

Internal Connection



Electrical Characteristics (T_C=25˚C)

Parameter	Symbol	Conditions	min	typ	max	Unit
Collector cutoff current	I_{CBO}	V_{CB} = 120V, I_E = 0			100	µA
	I_{CEO}	V_{CE} = 100V, I_B = 0			100	µA
Emitter cutoff current	I_{EBO}	V_{EB} = 5V, I_C = 0			100	µA
Collector to emitter voltage	V_{CEO}	I_C = 30mA, I_B = 0	100			V
Forward current transfer ratio	h_{FE1}	V_{CE} = 5V, I_C = 1A	2000			
	h_{FE2}*	V_{CE} = 5V, I_C = 4A	5000		30000	
Collector to emitter saturation voltage	$V_{CE(sat)}$	I_C = 4A, I_B = 4mA			2.5	V
Base to emitter saturation voltage	$V_{BE(sat)}$	I_C = 4A, I_B = 4mA			3.0	V
Transition frequency	f_T	V_{CE} = 10V, I_C = 0.5A, f = 1MHz		20		MHz
Turn-on time	t_{on}	I_C = 4A, I_{B1} = 4mA, I_{B2} = –4mA, V_{CC} = 50V		2.5		µs
Storage time	t_{stg}			3.5		µs
Fall time	t_f			1.0		µs

*h_{FE2} Rank classification

Rank	Q	P
h_{FE2}	5000 to 15000	8000 to 30000

P_C — Ta



I_C — V_{CE}



$V_{BE(sat)}$ — I_C



$V_{CE(sat)}$ — I_C



h_{FE} — I_C



C_{ob} — V_{CB}



t_{on}, t_{stg}, t_f — I_C



Area of safe operation (ASO)



$R_{th(t)}$ — t


Note: R_{th} was measured at Ta=25°C and under natural convection.
(1) P_T=10V × 0.2A (2W) and without heat sink
(2) P_T=10V × 1.0A (10W) and with a 100 × 100 × 2mm Al heat sink
Thermal resistance $R_{th}(t)$ (°C/W)
10000
1000
100
10
1
0.1
(1)
(2)
10^{-4}
10^{-3}
10^{-2}
10^{-1}
1
10
10^{2}
10^{3}
10^{4}
Time t (s)