



RGP30A THRU RGP30M

3.0 AMPS. Glass Passivated Junction Fast Recovery Rectifiers



Voltage Range
50 to 1000 Volts
Current
3.0 Amperes


Features

- ✧ High temperature metallurgically bonded constructed
- ✧ Plastic material used carries Underwriters Laboratory Classification 94V-0
- ✧ Glass passivated cavity-free junction
- ✧ Capable of meeting environmental standards of MIL-S-19500
- ✧ 3.0 ampere operation at $T_A=55^\circ\text{C}$ with no thermal runaway
- ✧ Typical I_R less than 0.2 uA
- ✧ High temperature soldering guaranteed:
350°C / 10 seconds, 0.375" (9.5mm) lead length, 5 lbs., (2.3kg) tension
- ✧ Fast switching for high efficiency

Mechanical Data

- ✧ Case: JEDEC DO-201AD molded plastic over glass body
- ✧ Lead: Plated Axial leads, solderable per MIL-STD-750, Method 2026
- ✧ Polarity: Color band denotes cathode end
- ✧ Mounting position: Any
- ✧ Weight: 0.048 ounce, 1.28 grams

DO-201AD



Dimensions in inches and (millimeters)

Maximum Ratings and Electrical Characteristics

Rating at 25°C ambient temperature unless otherwise specified.

Single phase, half wave, 60 Hz, resistive or inductive load.

For capacitive load, derate current by 20%

Type Number	Symbol	RGP 30A	RGP 30B	RGP 30D	RGP 30G	RGP 30J	RGP 30K	RGP 30M	Units
Maximum Recurrent Peak Reverse Voltage	V_{RRM}	50	100	200	400	600	800	1000	V
Maximum RMS Voltage	V_{RMS}	35	70	140	280	420	560	700	V
Maximum DC Blocking Voltage	V_{DC}	50	100	200	400	600	800	1000	V
Maximum Average Forward Rectified Current .375" (9.5mm) Lead Length @ $T_A = 55^\circ\text{C}$	$I_{(AV)}$	3.0							A
Peak Forward Surge Current, 8.3 ms Single Half Sine-wave Superimposed on Rated Load (JEDEC method)	I_{FSM}	125							A
Maximum Instantaneous Forward Voltage @ 3.0A	V_F	1.3							V
Maximum DC Reverse Current @ $T_A=25^\circ\text{C}$ at Rated DC Blocking Voltage @ $T_A=125^\circ\text{C}$	I_R	5.0 100							uA uA
Maximum Reverse Recovery Time (Note 1) $T_J=25^\circ\text{C}$	T_{rr}	150				250	500		nS
Typical Junction Capacitance (Note 2)	C_j	40							pF
Typical Thermal Resistance (Note 3)	$R_{\theta JA}$	30							°C/W
Operating & Storage Temperature Range	T_J/T_{STG}	-65 to + 175							°C

Notes: 1. Reverse Recovery Test Conditions: $I_F=0.5A$, $I_R=1.0A$ Recover to 0.25A.

2. Measured at 1.0 MHz and Applied Reverse Voltage of 4.0 Volts.

3. Mount on Cu-Pad Size 16mm x 16mm on P.C.B.

RATINGS AND CHARACTERISTIC CURVES (RGP30A THRU RGP30M)

FIG.1- REVERSE RECOVERY TIME CHARACTERISTIC AND TEST CIRCUIT DIAGRAM





FIG.2- MAXIMUM FORWARD CURRENT DERATING CURVE




FIG.5- TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG.3- MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




FIG.6- TYPICAL REVERSE CHARACTERISTICS




FIG.4- TYPICAL JUNCTION CAPACITANCE

