



SR502 THRU SR520

5.0 AMPS. Schottky Barrier Rectifiers



Voltage Range
20 to 100 Volts
Current
5.0 Amperes


Features

- ✧ Low forward voltage drop
- ✧ High current capability
- ✧ High reliability
- ✧ High surge current capability

Mechanical Data

- ✧ Cases: DO-201AD molded plastic
- ✧ Epoxy: UL 94V-O rate flame retardant
- ✧ Lead: Axial leads, solderable per MIL-STD-202, Method 208 guaranteed
- ✧ Polarity: Color band denotes cathode end
- ✧ High temperature soldering guaranteed: 260°C/10 seconds/.375", (9.5mm) lead lengths at 5 lbs., (2.3kg) tension
- ✧ Weight: 1.1 grams

DO-201AD



Dimensions in inches and (millimeters)

Maximum Ratings and Electrical Characteristics

Rating at 25°C ambient temperature unless otherwise specified.

Single phase, half wave, 60 Hz, resistive or inductive load.

For capacitive load, derate current by 20%

Type Number	Symbol	SR 502	SR 503	SR 504	SR 505	SR 506	SR 509	SR 510	SR 520	Units
Maximum Recurrent Peak Reverse Voltage	V _{RRM}	20	30	40	50	60	90	100	200	V
Maximum RMS Voltage	V _{RMS}	14	21	28	35	42	63	70	140	V
Maximum DC Blocking Voltage	V _{DC}	20	30	40	50	60	90	100	200	V
Maximum Average Forward Rectified Current See Fig. 1	I _(AV)	5.0								A
Peak Forward Surge Current, 8.3 ms Single Half Sine-wave Superimposed on Rated Load (JEDEC method)	I _{FSM}	200							150	A
Maximum Instantaneous Forward Voltage @5.0A	V _F	0.55			0.70		0.85		1.05	V
Maximum D.C. Reverse Current @ T _A =25°C at Rated DC Blocking Voltage @ T _A =100°C	I _R	0.5 50					0.2 10		0.010 10	mA mA
Typical Thermal Resistance (Note 1)	R _{θJA} R _{θJC}	35 5					10 2			°C/W
Typical Junction Capacitance (Note 2)	C _j	250			210		120			pF
Operating Junction Temperature Range	T _J	-65 to +125			-65 to +150					°C
Storage Temperature Range	T _{STG}	-65 to +150								°C

Notes: 1. Mount on Cu-Pad Size 16mm x 16mm on P.C.B.

2. Measured at 1 MHz and Applied Reverse Voltage of 4.0V D.C.

RATINGS AND CHARACTERISTIC CURVES (SR502 THRU SR520)

FIG.1- MAXIMUM FORWARD CURRENT DERATING CURVE




FIG.2- MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT




FIG.3- TYPICAL REVERSE CHARACTERISTICS




FIG.4- TYPICAL FORWARD CHARACTERISTICS




FIG.5- TYPICAL JUNCTION CAPACITANCE

