


SMALL SIGNAL PNP TRANSISTORS

Type	Marking
SO5401	P33

- SILICON EPITAXIAL PLANAR PNP TRANSISTORS
- MINIATURE PLASTIC PACKAGE FOR APPLICATION IN SURFACE MOUNTING CIRCUITS
- GENERAL PURPOSE AND HIGH VOLTAGE AMPLIFIER



ABSOLUTE MAXIMUM RATINGS

Symbol	Parameter	Value	Unit
V_{CBO}	Collector-Base Voltage ($I_E = 0$)	-160	V
V_{CEO}	Collector-Emitter Voltage ($I_B = 0$)	-150	V
V_{EBO}	Emitter-Base Voltage ($I_C = 0$)	-5	V
I_{CM}	Collector Peak Current	-0.6	A
P_{tot}	Total Dissipation at $T_c = 25\text{ }^\circ\text{C}$	200	mW
T_{stg}	Storage Temperature	-65 to 150	$^\circ\text{C}$
T_j	Max. Operating Junction Temperature	150	$^\circ\text{C}$

SO5401

THERMAL DATA

$R_{thj-amb}$ •	Thermal Resistance Junction-Ambient	Max	620	$^{\circ}\text{C}/\text{W}$
R_{thj-SR} •	Thermal Resistance Junction-Substrate	Max	400	$^{\circ}\text{C}/\text{W}$

• Mounted on a ceramic substrate area = 7 x 5 x 0.5 mm


ELECTRICAL CHARACTERISTICS ($T_{case} = 25^{\circ}\text{C}$ unless otherwise specified)

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
I_{CBO}	Collector Cut-off Current ($I_E = 0$)	$V_{CB} = -120\text{ V}$			-50	nA
I_{EBO}	Collector Cut-off Current ($I_C = 0$)	$V_{EB} = -3\text{ V}$			-50	nA
$V_{(BR)CBO}^*$	Collector-Emitter Breakdown Voltage ($I_E = 0$)	$I_C = -100\ \mu\text{A}$	-160			V
$V_{(BR)CEO}^*$	Collector-Emitter Breakdown Voltage ($I_B = 0$)	$I_C = -1\text{ mA}$	-150			V
$V_{(BR)EBO}$	Emitter-Base Breakdown Voltage ($I_C = 0$)	$I_C = -10\text{ nA}$	-5			V
$V_{CE(sat)}^*$	Collector-Emitter Saturation Voltage	$I_C = -10\text{ mA}$ $I_B = -1\text{ mA}$ $I_C = -50\text{ mA}$ $I_B = -5\text{ mA}$			-0.2 -0.5	V V
$V_{BE(sat)}^*$	Collector-Base Saturation Voltage	$I_C = -10\text{ mA}$ $I_B = -1\text{ mA}$ $I_C = -50\text{ mA}$ $I_B = -5\text{ mA}$			-1 -1	V V
h_{FE}^*	DC Current Gain	$I_C = -1\text{ mA}$ $V_{CE} = -5\text{ V}$ $I_C = -10\text{ mA}$ $V_{CE} = -5\text{ V}$ $I_C = -50\text{ mA}$ $V_{CE} = -5\text{ V}$	50 60 50	240		
f_T	Transition Frequency	$I_C = -10\text{ mA}$ $V_{CE} = -10\text{ V}$ $f = 1\text{ MHz}$	100		400	MHz
C_{CB}	Collector Base Capacitance	$I_E = 0$ $V_{CE} = -10\text{ V}$ $f = 1\text{ MHz}$			6	pF
NF	Noise Figure	$V_{CE} = -5\text{ V}$ $I_C = -0.25\text{ mA}$ $f = 1\text{ KHz}$ $\Delta f = 200\text{ Hz}$ $R_G = 1\text{ K}\Omega$		5		dB
h_{fe}^*	Small Signal Current Gain	$V_{CE} = -5\text{ V}$ $I_C = -1\text{ mA}$ $f = 1\text{ KHz}$	40		200	

* Pulsed: Pulse duration = 300 μs , duty cycle $\leq 2\%$

SOT-23 MECHANICAL DATA

DIM.	mm			mils		
	MIN.	TYP.	MAX.	MIN.	TYP.	MAX.
A	0.85		1.1	33.4		43.3
B	0.65		0.95	25.6		37.4
C	1.20		1.4	47.2		55.1
D	2.80		3	110.2		118
E	0.95		1.05	37.4		41.3
F	1.9		2.05	74.8		80.7
G	2.1		2.5	82.6		98.4
H	0.38		0.48	14.9		18.8
L	0.3		0.6	11.8		23.6
M	0		0.1	0		3.9
N	0.3		0.65	11.8		25.6
O	0.09		0.17	3.5		6.7



Information furnished is believed to be accurate and reliable. However, SGS-THOMSON Microelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of SGS-THOMSON Microelectronics. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. SGS-THOMSON Microelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of SGS-THOMSON Microelectronics.

© 1997 SGS-THOMSON Microelectronics - Printed in Italy - All Rights Reserved

SGS-THOMSON Microelectronics GROUP OF COMPANIES

Australia - Brazil - Canada - China - France - Germany - Hong Kong - Italy - Japan - Korea - Malaysia - Malta - Morocco - The Netherlands - Singapore - Spain - Sweden - Switzerland - Taiwan - Thailand - United Kingdom - U.S.A