

RF MOSFET Power Transistor, 80W, 28V

2 - 175 MHz

DU2880V


V2.00

Features

- N-Channel Enhancement Mode Device
- DMOS Structure
- Lower Capacitances for Broadband Operation
- High Saturated Output Power
- Lower Noise Figure Than Competitive Devices

Absolute Maximum Ratings at 25°C

Parameter	Symbol	Rating	Units
Drain-Source Voltage	V_{DS}	65	V
Gate-Source Voltage	V_{GS}	20	V
Drain-Source Current	I_{DS}	8*	A
Power Dissipation	P_D	206	W
Junction Temperature	T_J	200	°C
Storage Temperature	T_{STG}	-55 to +150	°C
Thermal Resistance	θ_{JC}	0.85	°C/W



Electrical Characteristics at 25°C

Parameter	Symbol	Min	Max	Units	Test Conditions
Drain-Source Breakdown Voltage	BV_{DSS}	65	-	V	$V_{GS}=0.0\text{ V}$, $I_{DS}=10.0\text{ mA}^*$
Drain-Source Leakage Current	I_{DSS}	-	2.0	mA	$V_{DS}=28.0\text{ V}$, $V_{GS}=0.0\text{ V}^*$
Gate-Source Leakage Current	I_{GSS}	-	2.0	μA	$V_{GS}=20.0\text{ V}$, $V_{DS}=0.0\text{ V}^*$
Gate Threshold Voltage	$V_{GS(TH)}$	2.0	6.0	V	$V_{DS}=10.0\text{ V}$, $I_{DS}=200.0\text{ mA}^*$
Forward Transconductance	G_M	1.0	-	S	$V_{DS}=10.0\text{ V}$, $I_{DS}=2000.0\text{ mA}$, $\Delta V_{GS}=1.0\text{ V}$, 80 μs Pulse*
Input Capacitance	C_{ISS}	-	90	pF	$V_{DS}=28.0\text{ V}$, $F=1.0\text{ MHz}^*$
Output Capacitance	C_{OSS}	-	80	pF	$V_{DS}=28.0\text{ V}$, $F=1.0\text{ MHz}^*$
Reverse Capacitance	C_{RSS}	-	16	pF	$V_{DS}=28.0\text{ V}$, $F=1.0\text{ MHz}^*$
Power Gain	G_p	13	-	dB	$V_{DD}=28.0\text{ V}$, $I_{DQ}=400\text{ mA}$, $P_{OUT}=80.0\text{ W}$, $F=175\text{ MHz}$
Drain Efficiency	η_D	60	-	%	$V_{DD}=28.0\text{ V}$, $I_{DQ}=400\text{ mA}$, $P_{OUT}=80.0\text{ W}$, $F=175\text{ MHz}$
Load Mismatch Tolerance	VSWR-T	-	30:1	-	$V_{DD}=28.0\text{ V}$, $I_{DQ}=400\text{ mA}$, $P_{OUT}=80.0\text{ W}$, $F=175\text{ MHz}$

* Per Side

Specifications Subject to Change Without Notice.





M/A-COM, Inc.

North America: Tel. (800) 366-2266
Fax (800) 618-8883

Asia/Pacific: Tel. +81 (03) 3226-1671
Fax +81 (03) 3226-1451

Europe: Tel. +44 (1344) 869 595
Fax +44 (1344) 300 020

Typical Broadband Performance Curves



Specifications Subject to Change Without Notice.

M/A-COM, Inc.

North America: Tel. (800) 366-2266
Fax (800) 618-8883■ Asia/Pacific: Tel. +81 (03) 3226-1671
Fax +81 (03) 3226-1451■ Europe: Tel. +44 (1344) 869 595
Fax +44 (1344) 300 020

Typical Device Impedance


Frequency (MHz)	Z_{IN} (OHMS)	Z_{LOAD} (OHMS)
30	4.5 - j 14.5	13.5 + j 4.5
100	3.0 - j 10.5	13.5 + j 6.0
175	2.0 - j 7.5	12.0 + j 4.5

$$V_{DD}=28 \text{ V}, I_{DQ}=400 \text{ mA}, P_{OUT}=80 \text{ Watts}$$

Z_{IN} is the series equivalent input impedance of the device from gate to gate.

Z_{LOAD} is the optimum series equivalent load impedance as measured from drain to drain.

RF Test Fixture



Specifications Subject to Change Without Notice.

MA-COM, Inc.

North America: Tel. (800) 366-2266
Fax (800) 618-8883

■ Asia/Pacific: Tel. +81 (03) 3226-1671
Fax +81 (03) 3226-1451

■ Europe: Tel. +44 (1344) 869 595
Fax +44 (1344) 300 020