


# UGF8HT AND UGF8JT

## ULTRAFAST SOFT RECOVERY RECTIFIER

**Reverse Voltage - 500 to 600 Volts    Forward Current - 8.0 Amperes**

### ITO-220AC



### FEATURES

- ♦ Plastic package has Underwriters Laboratories Flammability Classification 94V-0
- ♦ Ideally suited for freewheeling diode power factor correction applications
- ♦ Soft recovery characteristics
- ♦ Excellent high temperature switching
- ♦ Planar technology
- ♦ Optimized to reduce switching losses
- ♦ High temperature soldering guaranteed: 250°C, 0.25" (6.35mm) from case for 10 seconds



### MECHANICAL DATA

**Case:** ITO-220AC molded plastic body

**Terminals:** Plated leads, solderable per MIL-STD-750, Method 2026

**Polarity:** As marked

**Mounting Position:** Any

**Weight:** 0.08 ounce, 2.24 grams

**Mounting Torque:** 5 in. - lbs. max.

### MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.

|                                                                                                                                                    | SYMBOLS                        | UGF8HT               | UGF8JT | UNITS                                         |
|----------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------|----------------------|--------|-----------------------------------------------|
| Maximum repetitive peak reverse voltage                                                                                                            | $V_{RRM}$                      | 500                  | 600    | Volts                                         |
| Working peak reverse voltage                                                                                                                       | $V_{RWM}$                      | 400                  | 480    | Volts                                         |
| Maximum RMS voltage                                                                                                                                | $V_{RMS}$                      | 350                  | 420    | Volts                                         |
| Maximum DC blocking voltage                                                                                                                        | $V_{DC}$                       | 500                  | 600    | Volts                                         |
| Maximum average forward rectified current at $T_C=100^\circ\text{C}$                                                                               | $I_{(AV)}$                     | 8.0                  |        | Amps                                          |
| Peak forward surge current<br>8.3ms single half sine-wave superimposed<br>on rated load (JEDEC Method)                                             | $I_{FSM}$                      | 100.0                |        | Amps                                          |
| Maximum instantaneous forward voltage at $I_F=8\text{A}$ (NOTE 1)<br>$T_J=25^\circ\text{C}$<br>$T_J=125^\circ\text{C}$                             | $V_F$                          | 1.75<br>1.50         |        | Volts                                         |
| Maximum reverse leakage current<br>at working peak reverse voltage<br>$T_C=25^\circ\text{C}$<br>$T_C=100^\circ\text{C}$<br>$T_C=125^\circ\text{C}$ | $I_R$                          | 30.0<br>800.0<br>4.0 |        | $\mu\text{A}$<br>$\mu\text{A}$<br>$\text{mA}$ |
| Maximum reverse recovery time at $I_F=0.5\text{A}$ , $I_R=1.0\text{A}$ , $I_{rr}=0.25\text{A}$                                                     | $t_{rr}$                       | 25                   |        | ns                                            |
| Reverse recovery time at<br>$I_F=1.0\text{A}$ , $di/dt=50\text{A}/\mu\text{s}$ , $V_R=30\text{V}$ , $I_{rr}=0.1 I_{RM}$                            | Maximum<br>$t_{rr}$<br>Typical | 50<br>35             |        | ns                                            |
| Typical softness factor ( $t_b/t_a$ ) $I_F=8.0\text{A}$ , $di/dt=240\text{A}/\mu\text{s}$ , $V_R=400\text{V}$ , $I_{rr}=0.1 I_{RM}$                | $S$                            | 1.0                  |        | -                                             |
| Maximum reverse recovery current at<br>$I_F=8.0\text{A}$ , $di/dt=64\text{A}/\mu\text{s}$ , $V_R=400\text{V}$<br>$T_C=125^\circ\text{C}$           | $I_{RM}$                       | 5.5                  |        | Amps                                          |
| Typical reverse recovery current at<br>$I_F=8.0\text{A}$ , $di/dt=240\text{A}/\mu\text{s}$ , $V_R=400\text{V}$<br>$T_C=125^\circ\text{C}$          | $I_{RM}$                       | 10.0                 |        | Amps                                          |
| Peak forward recovery time at<br>$I_F=8\text{A}$ , $di/dt=64\text{A}/\mu\text{s}$ measured at $1.1 V_F$<br>Maximum<br>Typical                      | $t_{fr}$                       | 500<br>250           |        | ns                                            |
| Typical thermal resistance from junction to case                                                                                                   | $R_{\theta JC}$                | 5.0                  |        | $^\circ\text{C}/\text{W}$                     |
| Operating junction and storage temperature range                                                                                                   | $T_J$ , $T_{STG}$              | -55 to +150          |        | $^\circ\text{C}$                              |

**NOTE:** (1) Pulse test: 300 $\mu\text{s}$  pulse width, 1% duty cycle

**NOTICE:** Advanced product information is subject to change without notice

# RATINGS AND CHARACTERISTIC CURVES UGF8HT AND UGF8JT

FIG. 1 - FORWARD CURRENT DERATIVE CURVE




FIG. 2 - MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




FIG. 3 - TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG. 4 - TYPICAL REVERSE CHARACTERISTICS




FIG. 5 - TYPICAL JUNCTION CAPACITANCE




FIG. 6 - REVERSE SWITCHING CHARACTERISTICS

