19-1661; Rev 2; 2/02

MAXIM

Low-Voltage, 4Ω, Quad, SPST, CMOS Analog Switches

General Description

The MAX4651/MAX4652/MAX4653 quad analog switches feature 4Ω max on-resistance (R_{ON}) when operating from a single +5V supply. R_{ON} is matched between switches to 0.2Ω (max) and is flat (0.8Ω max) over the specified signal range. Each switch can handle Rail-to-Rail® analog signals. Off-leakage current is 0.1nA at +25°C. These switches are ideal in low-distortion applications and are the preferred solution over mechanical relays in automated test equipment or applications where current switching is required. They have low power requirements, require less board space, and are more reliable than mechanical relays.

The MAX4651/MAX4652/MAX4653 operate from a single +1.8V to +5.5V supply, making them ideal for use in battery-powered applications.

The MAX4651 has four normally closed (NC) switches, the MAX4652 has four normally open (NO) switches, and the MAX4653 has two NO and two NC switches. These devices are available in 16-pin QFN, TSSOP and SO packages, as well as 20-pin QFN package.

Applications

Battery-Powered Systems

Audio and Video Signal Routing

Low-Voltage Data-Acquisition Systems

Sample-and-Hold Circuits

Communications Circuits

Relay Replacement

Rail-to-Rail is a registered trademark of Nippon Motorola, Ltd.

Features

- **On-Resistance**
  4Ω max at 5V
  7Ω max at 3V
- **On-Resistance Flatness**
  0.8Ω max at 5V
  2.5Ω max at 3V
- **On-Resistance Matching**
  0.2Ω max (+2.7V to +5.5V)
- **+1.8V to +5.5V Single-Supply Voltage**
- **+1.8V Operation**
  On-Resistance 30Ω (typ) Over Temperature
  t_{ON} 20ns typ, t_{OFF} 12ns (typ)
- **TTL/CMOS-Logic Compatible**
- **Crosstalk**
  -100dB at 1MHz
- **Off-Isolation**
  -75dB at 1MHz
- **Rail-to-Rail Signal Range**

Ordering Information

PART	TEMP RANGE	PIN-PACKAGE
MAX4651EGE	-40°C to +85°C	16 QFN (4 × 4)
MAX4651EUE	-40°C to +85°C	16 TSSOP
MAX4651ESE	-40°C to +85°C	16 SO
MAX4651EGP	-40°C to +85°C	20 QFN (4 × 4)

Ordering Information continued at end of data sheet.

Pin Configurations/Functional Diagrams/Truth Tables

TOP VIEW



TSSOP/SO

MAX4651	
LOGIC	SWITCH
0	ON
1	OFF



TSSOP/SO

MAX4652	
LOGIC	SWITCH
0	OFF
1	ON

SWITCHES SHOWN FOR LOGIC "0" INPUT



TSSOP/SO

MAX4653		
LOGIC	SWITCHES 1, 4	SWITCHES 2, 3
0	OFF	ON
1	ON	OFF

Pin Configurations continued at end of data sheet.

For pricing, delivery, and ordering information, please contact Maxim/Dallas Direct! at 1-888-629-4642, or visit Maxim's website at www.maxim-ic.com.

Low-Voltage, 4Ω, Quad, SPST, CMOS Analog Switches

ABSOLUTE MAXIMUM RATINGS

V+ to GND .....-0.3 to +6V
IN_, COM_, NO_, NC_ to GND (Note 1).....-0.3V to (V+ + 0.3V)
Continuous Current (NO_, NC_, COM_).....±50mA
Peak Current (NO_, NC_, COM_, pulsed at 1ms 10% duty cycle).....±100mA

Continuous Power Dissipation (T_A = +70°C)
16-Pin QFN (derate 18.5mW/°C above +70°C) 1481mW
16-Pin TSSOP (derate 5.7mW/°C above +70°C) 457mW
16-Pin SO (derate 8mW/°C above +70°C).....640mW
20-Pin QFN (derate 20mW/°C above +70°C) 1600mW
Operating Temperature Range .....-40°C to +85°C
Storage Temperature Range .....-65°C to +150°C
Lead Temperature (soldering, 10s) .....+300°C

Note 1: Signals on NO_, NC_, COM_, or IN_ exceeding V+ or GND are clamped by internal diodes. Limit forward current to maximum current rating.

Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

ELECTRICAL CHARACTERISTICS—Single +5V Supply

(V+ = 4.5V to 5.5V, V_{IH} = 2.4V, V_{IL} = 0.8V, T_A = T_{MIN} to T_{MAX}, unless otherwise specified. Typical values are at V+ = 5V, T_A = +25°C.) (Note 2)

PARAMETER	SYMBOL	CONDITIONS		MIN	TYP	MAX	UNITS
ANALOG SWITCH							
Input Voltage Range	$V_{COM_}$, $V_{NO_}$, $V_{NC_}$			0		V+	V
COM_ to NO_ or NC_ On-Resistance	R_{ON}	I_{COM} = 10mA, $V_{NO_}$ or $V_{NC_}$ = 0 to V+, V+ = 4.5V	T_A = +25°C		2.5	4	Ω
			T_A = T_{MIN} to T_{MAX}			4.5	
COM_ to NO_ or NC_ On-Resistance Match Between Channels (Notes 3, 8)	ΔR_{ON}	I_{COM} = 10mA, $V_{NO_}$ or $V_{NC_}$ = 0 to V+, V+ = 4.5V	T_A = +25°C		0.05	0.2	Ω
			T_A = T_{MIN} to T_{MAX}			0.3	
On-Resistance Flatness (Note 4)	$R_{FLAT(ON)}$	I_{COM} = 10mA, $V_{NO_}$ or $V_{NC_}$ = 0 to V+, V+ = 4.5V	T_A = +25°C		0.5	0.8	Ω
			T_A = T_{MIN} to T_{MAX}			1	
Off-Leakage Current (NO_ or NC_) (Note 5)	$I_{NO_}$, $I_{NC_}$	V_{COM} = 1V, 4.5V; $V_{NO_}$ or $V_{NC_}$ = 4.5V, 1V; V+ = 5.5V	T_A = +25°C	-0.1	0.01	0.1	nA
			T_A = T_{MIN} to T_{MAX}	-0.2		0.2	
COM_ Off-Leakage Current (Note 5)	$I_{COM_(OFF)}$	V_{COM} = 1V, 4.5V; $V_{NO_}$ or $V_{NC_}$ = 4.5V, 1V; V+ = 5.5V	T_A = +25°C	-0.1	0.01	0.1	nA
			T_A = T_{MIN} to T_{MAX}	-0.2		0.2	
COM_ On-Leakage Current (Note 5)	$I_{COM_(ON)}$	V+ = 5.5V, V_{COM} = 1V, 4.5V; $V_{NO_}$ or $V_{NC_}$ = 1V, 4.5V or floating	T_A = +25°C	-0.1	0.01	0.1	nA
			T_A = T_{MIN} to T_{MAX}	-0.2		0.2	
LOGIC INPUT (IN_)							
Input High	V_{IH}			2.4			V
Input Low	V_{IL}					0.8	V
Logic Input Current	I_{IN}			-100	5	100	nA

ELECTRICAL CHARACTERISTICS—Single +5V Supply (continued)

(V+ = 4.5V to 5.5V, V_{IH} = 2.4V, V_{IL} = 0.8V, T_A = T_{MIN} to T_{MAX}, unless otherwise specified. Typical values are at V+ = 5V, T_A = +25°C.) (Note 2)

PARAMETER	SYMBOL	CONDITIONS		MIN	TYP	MAX	UNITS
SWITCH DYNAMIC CHARACTERISTICS							
Turn-On Time (Note 5)	t_{ON}	$V_{NO_}$ = $V_{NC_}$ = 3V, R_L = 300Ω, C_L = 35pF, Figure 2	T_A = +25°C		11	14	ns
			T_A = T_{MIN} to T_{MAX}			16	
Turn-Off Time (Note 5)	t_{OFF}	$V_{NO_}$ = $V_{NC_}$ = 3V, R_L = 300Ω, C_L = 35pF, Figure 2	T_A = +25°C		6	8	ns
			T_A = T_{MIN} to T_{MAX}			10	
Break-Before-Make (MAX4653 only) (Note 5)		$V_{NO_}$ = $V_{NC_}$ = 3V, R_L = 300Ω, C_L = 35pF	T_A = +25°C	1	6		ns
			T_A = T_{MIN} to T_{MAX}	1			
Charge Injection	Q	V_{GEN} = 2V, C_L = 1.0nF, R_{GEN} = 0, Figure 3			2		pC
NO_ or NC_ Off-Capacitance	C_{OFF}	$V_{NO_}$ = $V_{NC_}$ = GND, f = 1MHz, Figure 6			16		pF
COM_ Off-Capacitance	$C_{COM(OFF)}$	$V_{COM_}$ = GND, f = 1MHz, Figure 6			16		pF
COM_ On-Capacitance	$C_{COM(ON)}$	$V_{COM_}$ = $V_{NO_}$, $V_{NC_}$ = GND, f = 1MHz, Figure 7			32		pF
Off-Isolation (Note 6)	V_{ISO}	R_L = 50Ω, C_L = 5pF, f = 10MHz, Figure 4			-50		dB
		R_L = 50Ω, C_L = 5pF, f = 1MHz, Figure 4			-75		
Crosstalk (Note 7)	V_{CT}	R_L = 50Ω, C_L = 5pF, f = 10MHz, Figure 5			-80		dB
		R_L = 50Ω, C_L = 5pF, f = 1MHz, Figure 5			-100		
Total Harmonic Distortion	THD	R_L = 600Ω, f = 20Hz to 20kHz			0.02		%
POWER SUPPLY							
Positive Supply Current	I+	V+ = 5.5V, V_{IN} = 0 or V+			0.001	1.0	µA

ELECTRICAL CHARACTERISTICS—Single +3V Supply

(V+ = 2.7V to 3.3V, V_{IH} = 2.0V, V_{IL} = 0.4V, T_A = T_{MIN} to T_{MAX}, unless otherwise specified. Typical values are at V+ = 3V, T_A = +25°C.) (Note 2)

PARAMETER	SYMBOL	CONDITIONS		MIN	TYP	MAX	UNITS
ANALOG SWITCH							
Input Voltage Range	$V_{COM_}$, $V_{NO_}$, $V_{NC_}$			0		V+	V
COM_ to NO_ or NC_ On-Resistance	R_{ON}	V+ = 2.7V, I_{COM} = 10mA, $V_{NO_}$ or $V_{NC_}$ = 0 to V+	T_A = +25°C		5	7	Ω
			T_A = T_{MIN} to T_{MAX}			8	
COM_ to NO_ or NC_ On-Resistance Match Between Channels (Notes 3, 8)	ΔR_{ON}	V+ = 2.7V, I_{COM} = 10mA, $V_{NO_}$ or $V_{NC_}$ = 0 to V+	T_A = +25°C		0.1	0.2	Ω
			T_A = T_{MIN} to T_{MAX}			0.3	
On-Resistance Flatness (Note 4)	$R_{FLAT(ON)}$	V+ = 2.7V, I_{COM} = 10mA, $V_{NO_}$ or $V_{NC_}$ = 0 to V+	T_A = +25°C		1.2	2.5	Ω
			T_A = T_{MIN} to T_{MAX}			3	

Low-Voltage, 4Ω, Quad, SPST, CMOS Analog Switches

ELECTRICAL CHARACTERISTICS—Single +3V Supply (continued)

(V+ = 2.7V to 3.3V, V_{IH} = 2.0V, V_{IL} = 0.4V, T_A = T_{MIN} to T_{MAX}, unless otherwise specified. Typical values are at V+ = 3V, T_A = +25°C.) (Note 2)

PARAMETER	SYMBOL	CONDITIONS		MIN	TYP	MAX	UNITS
LOGIC INPUT (IN_)							
Input High	V_{IH}			2.0			V
Input Low	V_{IL}					0.4	V
Logic Input Current	I_{IN}			-100	5	100	nA
SWITCH DYNAMIC CHARACTERISTICS							
Turn-On Time (Note 5)	t_{ON}	$V_{NO_}$ = $V_{NC_}$ = 2V, R_L = 300Ω, C_L = 35pF, Figure 2	T_A = +25°C		13	16	ns
			T_A = T_{MIN} to T_{MAX}			20	
Turn-Off Time (Note 5)	t_{OFF}	$V_{NO_}$ = $V_{NC_}$ = 2V, R_L = 300Ω, C_L = 35pF, Figure 2	T_A = +25°C		7	10	ns
			T_A = T_{MIN} to T_{MAX}			12	
Break-Before-Make (MAX4653 only) (Note 5)		$V_{NO_}$ = $V_{NC_}$ = 2V, R_L = 300Ω, C_L = 35pF	T_A = +25°C	1	7		ns
			T_A = T_{MIN} to T_{MAX}	1			
Charge Injection	Q	V_{GEN} = 1.5V, C_L = 1.0nF, R_{GEN} = 0, Figure 3			2		pC
NO_ or NC_ Off-Capacitance	C_{OFF}	$V_{NO_}$ = $V_{NC_}$ = GND, f = 1MHz, Figure 6			16		pF
COM_ Off-Capacitance	$C_{COM(OFF)}$	$V_{COM_}$ = GND, f = 1MHz, Figure 6			16		pF
COM_ On-Capacitance	$C_{COM(ON)}$	$V_{COM_}$ = $V_{NO_}$, $V_{NC_}$ = GND, f = 1MHz, Figure 7			32		pF
Off-Isolation (Note 6)	V_{ISO}	R_L = 50Ω, C_L = 5pF, f = 10MHz, Figure 4			-50		dB
		R_L = 50Ω, C_L = 5pF, f = 1MHz, Figure 4			-75		
Crosstalk (Note 7)	V_{CT}	R_L = 50Ω, C_L = 5pF, f = 10MHz, Figure 5			-80		dB
		R_L = 50Ω, C_L = 5pF, f = 1MHz, Figure 5			-100		
Total Harmonic Distortion	THD	R_L = 600Ω, f = 20Hz to 20kHz			0.02		%
POWER SUPPLY							
Positive Supply Current	I+	V+ = 3.3V, V_{IN} = 0 or V+			0.001	1.0	µA

Note 2: The algebraic convention, where the most negative value is a minimum and the most positive value is a maximum, is used in this data sheet.

Note 3: $\Delta R_{ON} = R_{ON(MAX)} - R_{ON(MIN)}$.

Note 4: Flatness is defined as the difference between the maximum and the minimum value of on-resistance as measured over the specified analog signal ranges.

Note 5: Guaranteed by design.

Note 6: Off-Isolation = $20\log_{10}(V_{COM} / V_{NO})$, where V_{COM} = output and V_{NO} = input to off switch.

Note 7: Between any two switches.

Note 8: ΔR_{ON} matching specifications for QFN-packages parts are guaranteed by design.

Typical Operating Characteristics

(V+ = 5V, T_A = +25°C, unless otherwise noted.)

ON-RESISTANCE vs. V_{COM} AND SUPPLY VOLTAGE



ON-RESISTANCE vs. V_{COM} AND TEMPERATURE



ON-/OFF-LEAKAGE CURRENT vs. TEMPERATURE



SUPPLY CURRENT vs. SUPPLY VOLTAGE AND TEMPERATURE



TURN-ON/TURN-OFF TIMES vs. TEMPERATURE



TURN-ON/TURN-OFF TIMES vs. SUPPLY VOLTAGE



TURN-ON/TURN-OFF TIMES vs. V_{COM}



TURN-ON/TURN-OFF TIMES vs. V_{COM}



CHARGE INJECTION vs. V_{COM}



Low-Voltage, 4Ω, Quad, SPST, CMOS Analog Switches

Typical Operating Characteristics (continued)

(V+ = 5V, T_A = +25°C, unless otherwise noted.)

FREQUENCY RESPONSE



TOTAL HARMONIC DISTORTION vs. FREQUENCY



Pin Description

PIN									NAME	FUNCTION
MAX4651			MAX4652			MAX4653				
TSSOP/SO	16-PIN QFN	20-PIN QFN	TSSOP/SO	16-PIN QFN	20-PIN QFN	TSSOP/SO	16-PIN QFN	20-PIN QFN		
1	15	19	1	15	19	1	15	19	IN1	Digital Control Input 1
2	16	1	2	16	1	2	16	1	COM1	Analog Switch 1 Common Terminal
3	1	2	—	—	—	—	—	—	NC1	Analog Switch 1 Normally Closed Terminal
—	—	—	3	1	2	3	1	2	NO1	Analog Switch 1 Normally Open Terminal
4, 12	2, 10	6, 8, 10, 16, 18, 20	4, 12	2, 10	6, 8, 10, 16, 18, 20	4, 12	2, 10	6, 8, 10, 16, 18, 20	N.C.	No Connection. Not internally connected.
5	3	3	5	3	3	5	3	3	GND	Ground
6	4	4	—	—	—	—	—	—	NC4	Analog Switch 4 Normally Closed Terminal
—	—	—	6	4	4	6	4	4	NO4	Analog Switch 4 Normally Open Terminal
7	5	5	7	5	5	7	5	5	COM4	Analog Switch 4 Common Terminal
8	6	7	8	6	7	8	6	7	IN4	Digital Control Input 4
9	7	9	9	7	9	9	7	9	IN3	Digital Control Input 3
10	8	11	10	8	11	10	8	11	COM3	Analog Switch 3 Common Terminal
11	9	12	—	—	—	11	9	12	NC3	Analog Switch 3 Normally Closed Terminal
—	—	—	11	9	12	—	—	—	NO3	Analog Switch 3 Normally Open Terminal
13	11	13	13	11	13	13	11	13	V+	Positive-Supply Voltage Input
14	12	14	—	—	—	14	12	14	NC2	Analog Switch 2 Normally Closed Terminal
—	—	—	14	12	14	—	—	—	NO2	Analog Switch 2 Normally Open Terminal
15	13	15	15	13	15	15	13	15	COM2	Analog Switch 2 Common Terminal
16	14	17	16	14	17	16	14	17	IN2	Digital Control Input 2

Low-Voltage, 4Ω, Quad, SPST, CMOS Analog Switches

Detailed Description

The MAX4651/MAX4652/MAX4653 are low on-resistance, low-voltage analog switches that operate from a single +1.8V to +5.5V supply. CMOS switch construction allows processing analog signals that are within the supply voltage range (GND to V+).

Applications Information

Proper power-supply sequencing is recommended for all CMOS devices. Do not exceed the absolute maximum ratings because stresses beyond the listed ratings can cause permanent damage to the devices. Always sequence V+ on first, followed by the logic inputs, NO or COM. If power-supply sequencing is not possible, add two small signal diodes (D1, D2) in series with the supply pins for overvoltage protection (Figure 1). Adding these diodes reduces the analog signal by one diode drop below V+ and one diode drop above GND, but does not affect the devices' low switch resistance and low leakage characteristics. Device operation is unchanged, and the difference between V+ and GND should not exceed 6V.

Although it is not required, power-supply bypassing improves noise margin and prevents switching noise from propagating from the V+ supply to other components. A 0.1µF capacitor connected from V+ to GND is adequate for most applications.



Figure 1. Overvoltage Protection Using External Blocking Diodes

Chip Information

TRANSISTOR COUNT: 205

Timing Diagrams/Test Circuits



Figure 2. Switching-Time Test Circuit



Figure 3. Charge-Injection Test Circuit

Low-Voltage, 4Ω, Quad, SPST, CMOS Analog Switches

Timing Diagrams/Test Circuits (continued)



Figure 4. Off-Isolation Test Circuit/On-Channel Bandwidth



Figure 5. Crosstalk Test Circuit



Figure 6. Switch Off-Capacitance Test Circuit



Figure 7. Switch On-Capacitance Test Circuit

Pin Configurations (continued)



Ordering Information (continued)

PART	TEMP RANGE	PIN-PACKAGE
MAX4652EGE	-40°C to +85°C	16 QFN (4 × 4)
MAX4652EUE	-40°C to +85°C	16 TSSOP
MAX4652ESE	-40°C to +85°C	16 SO
MAX4652EGP	-40°C to +85°C	20 QFN (4 × 4)
MAX4653EGE	-40°C to +85°C	16 QFN (4 × 4)
MAX4653EUE	-40°C to +85°C	16 TSSOP
MAX4653ESE	-40°C to +85°C	16 SO
MAX4653EGP	-40°C to +85°C	20 QFN (4 × 4)

Low-Voltage, 4Ω, Quad, SPST, CMOS Analog Switches

Package Information

(The package drawing(s) in this data sheet may not reflect the most current specifications. For the latest package outline information, go to **www.maxim-ic.com/packages**.)

TSSOP.EPS



SYMBOL	COMMON DIMENSIONS			
	MILLIMETERS		INCHES	
	MIN.	MAX.	MIN.	MAX.
A	—	1.10		.043
A_1	0.05	0.15	.002	.006
A_2	0.85	0.95	.033	.037
b	0.19	0.30	.007	.012
b1	0.19	0.25	.007	.010
c	0.090	0.20	.0035	.008
c1	0.090	0.135	.0035	.0053
D	SEE VARIATIONS		SEE VARIATIONS	
E	4.30	4.50	.169	.177
e	0.65 BSC		.026 BSC	
H	6.25	6.50	.246	.256
L	0.50	0.70	.020	.028
N	SEE VARIATIONS		SEE VARIATIONS	
Y	2.85	3.15	.112	.124
α	0°	8°	0°	8°

JEDEC			VARIATIONS			
MO-153	N		MILLIMETERS		INCHES	
			MIN.	MAX.	MIN.	MAX.
AB	14	D	4.90	5.10	.193	.201
AC	16	D	4.90	5.10	.193	.201
AC-EP	16	D	4.90	5.10	.193	.201
		X	2.85	3.15	.112	.124
AD	20	D	6.40	6.60	.252	.260
AD-EP	20	D	6.40	6.60	.252	.260
		X	4.00	4.34	.157	.171
AE	24	D	7.70	7.90	.303	.311
AF	28	D	9.60	9.80	.378	.386
AF-EP		D	9.60	9.80	.378	.386
		X	5.35	5.65	.211	.222

NOTES:
1. DIMENSIONS D AND E DO NOT INCLUDE FLASH.
2. MOLD FLASH OR PROTRUSIONS NOT TO EXCEED .15 mm PER SIDE.
3. CONTROLLING DIMENSION: MILLIMETER.
4. MEETS JEDEC OUTLINE MO-153 VARIATIONS AB, AC, AD, AE, AF.
5. DIMENSIONS X AND Y APPLY TO EXPOSED PAD (EP) VERSIONS ONLY.
6. EXPOSED PAD FLUSH WITH BOTTOM OF PACKAGE WITHIN .002".

MAXIM
PROPRIETARY INFORMATION

TITLE: PACKAGE OUTLINE, TSSOP, 4.40mm BODY, 0.65mm PITCH

APPROVAL	DOCUMENT CONTROL NO.	REV	
	21-0066	C	1/1

Note: *The MAX4651/MAX4652/MAX4653 do not come in an exposed-pad package.*

Package Information (continued)

(The package drawing(s) in this data sheet may not reflect the most current specifications. For the latest package outline information, go to **www.maxim-ic.com/packages**.)



Low-Voltage, 4Ω, Quad, SPST, CMOS Analog Switches

Package Information (continued)

(The package drawing(s) in this data sheet may not reflect the most current specifications. For the latest package outline information, go to **www.maxim-ic.com/packages**.)

NOTES:

1. DIE THICKNESS ALLOWABLE IS 0.305mm MAXIMUM (.012 INCHES MAXIMUM)
2. DIMENSIONING & TOLERANCES CONFORM TO ASME Y14.5M. – 1994.
3. N IS THE NUMBER OF TERMINALS.
   Nd IS THE NUMBER OF TERMINALS IN X–DIRECTION &
   Ne IS THE NUMBER OF TERMINALS IN Y–DIRECTION.
4. DIMENSION b APPLIES TO PLATED TERMINAL AND IS MEASURED BETWEEN 0.20 AND 0.25mm FROM TERMINAL TIP.
5. THE PIN #1 IDENTIFIER MUST BE EXISTED ON THE TOP SURFACE OF THE PACKAGE BY USING INDENTATION MARK OR INK/ LASER MARKED.
6. EXACT SHAPE AND SIZE OF THIS FEATURE IS OPTIONAL.
7. ALL DIMENSIONS ARE IN MILLIMETERS.
8. PACKAGE WARPAGE MAX 0.05mm.
9. APPLIED FOR EXPOSED PAD AND TERMINALS.
   EXCLUDE EMBEDDED PART OF EXPOSED PAD FROM MEASURING.
10. MEETS JEDEC MO220.
11. THIS PACKAGE OUTLINE APPLIES TO ANVIL SINGULATION (STEPPED SIDES) AND TO SAW SINGULATION (STRAIGHT SIDES) QFN STYLES.

SYMBOL	COMMON DIMENSIONS			NOTE
	MIN.	NOM.	MAX.	
A	0.80	0.90	1.00	
A1	0.00	0.01	0.05	
A2	0.00	0.65	1.00	
A3		0.20 REF.		
D		5.00 BSC		
D1		4.75 BSC		
E		5.00 BSC		
E1		4.75 BSC		
θ	0°	–	12°	
P	0		0.60	
D2	1.25	–	3.25	
E2	1.25	–	3.25	

SYMBOL	PITCH VARIATION B			NOTE
	MIN.	NOM.	MAX.	
e		0.80 BSC		
N		16		3
Nd		4		3
Ne		4		3
L	0.35	0.55	0.75	
b	0.28	0.33	0.40	4

SYMBOL	PITCH VARIATION B			NOTE
	MIN.	NOM.	MAX.	
e		0.65 BSC		
N		20		3
Nd		5		3
Ne		5		3
L	0.35	0.55	0.75	
b	0.23	0.28	0.35	4

SYMBOL	PITCH VARIATION C			NOTE
	MIN.	NOM.	MAX.	
e		0.50 BSC		
N		28		3
Nd		7		3
Ne		7		3
L	0.35	0.55	0.75	
b	0.18	0.23	0.30	4

SYMBOL	PITCH VARIATION D			NOTE
	MIN.	NOM.	MAX.	
e		0.50 BSC		
N		32		3
Nd		8		3
Ne		8		3
L	0.30	0.40	0.50	
b	0.18	0.23	0.30	4

MAXIM

PROPRIETARY INFORMATION

TITLE: PACKAGE OUTLINE, 16,20,28,32L QFN, 5x5x0.90 MM

APPROVAL	DOCUMENT CONTROL NO.	REV	
	21-0091	G	2/2

Package Information (continued)

(The package drawing(s) in this data sheet may not reflect the most current specifications. For the latest package outline information, go to **www.maxim-ic.com/packages**.)



	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	0.053	0.069	1.35	1.75
A1	0.004	0.010	0.10	0.25
B	0.014	0.019	0.35	0.49
C	0.007	0.010	0.19	0.25
e	0.050		1.27	
E	0.150	0.157	3.80	4.00
H	0.228	0.244	5.80	6.20
h	0.010	0.020	0.25	0.50
L	0.016	0.050	0.40	1.27

	INCHES		MILLIMETERS			
	MIN	MAX	MIN	MAX	N	MS012
D	0.189	0.197	4.80	5.00	8	A
D	0.337	0.344	8.55	8.75	14	B
D	0.386	0.394	9.80	10.00	16	C

NOTES:
1. D&E DO NOT INCLUDE MOLD FLASH
2. MOLD FLASH OR PROTRUSIONS NOT TO EXCEED .15mm (.006")
3. LEADS TO BE COPLANAR WITHIN .102mm (.004")
4. CONTROLLING DIMENSION: MILLIMETER
5. MEETS JEDEC MS012-XX AS SHOWN IN ABOVE TABLE
6. N = NUMBER OF PINS

MAXIM 120 SAN GABRIEL DR SUNNYVALE CA 94086 FAX (408) 737 7194 PROPRIETARY INFORMATION

PACKAGE FAMILY OUTLINE: SOIC .150" (TITLE) | 1/1 | 21-0041 A (DOCUMENT CONTROL NUMBER) (REV)

Maxim cannot assume responsibility for use of any circuitry other than circuitry entirely embodied in a Maxim product. No circuit patent licenses are implied. Maxim reserves the right to change the circuitry and specifications without notice at any time.

© 2002 Maxim Integrated Products Printed USA MAXIM is a registered trademark of Maxim Integrated Products.