


LOW-POWER, PRECISION SINGLE-SUPPLY OPERATIONAL AMPLIFIERS

Check for Samples: [OPA2234M](#)

FEATURES

- **Wide Supply Range:**
 - **Single Supply:** $V_S = 2.7\text{ V to }36\text{ V}$
 - **Dual Supply:** $V_S = \pm 1.35\text{ V to } \pm 18\text{ V}$
- **Specified Performance:**
 - **2.7 V, 5 V, and $\pm 15\text{ V}$**
- **Low Quiescent Current:** $250\text{ }\mu\text{A/amp}$
- **Low Input Bias Current:** 35 nA Max
- **Low Offset Voltage:** $100\text{ }\mu\text{V Typ}$
- **High CMRR, PSRR, and A_{OL}**
- **Dual Versions**



DESCRIPTION

The OPA2234 series low-cost op amps are ideal for single-supply, low-voltage, low-power applications. The series provides lower quiescent current than older “1013”-type products and comes in current industry-standard packages and pinouts. The combination of low offset voltage, high common-mode rejection, high power-supply rejection, and a wide supply range provides excellent accuracy and versatility. Dual versions have identical specifications for maximum design flexibility. These general-purpose op amps are ideal for portable and battery-powered applications.

The OPA2234 series op amps operate from either single or dual supplies. In single-supply operation, the input common-mode range extends below ground and the output can swing to within 50mV of ground. Excellent phase margin makes the OPA2234 series ideal for demanding applications, including high load capacitance. Dual design features completely independent circuitry for lowest crosstalk and freedom from interaction.

Single and dual packages are in an SO-8 surface-mount and are specified for -55°C to 125°C operation.

ORDERING INFORMATION⁽¹⁾

PRODUCT	PACKAGE	PACKAGE MARKING
OPA2234MDR	SO-8 Surface-Mount	2234M

(1) For the most current package and ordering information, see the Package Option Addendum located at the end of this data sheet.



Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.

All trademarks are the property of their respective owners.

PRODUCTION DATA information is current as of publication date. Products conform to specifications per the terms of the Texas Instruments standard warranty. Production processing does not necessarily include testing of all parameters.

© 2011, Texas Instruments Incorporated



This integrated circuit can be damaged by ESD. Texas Instruments recommends that all integrated circuits be handled with appropriate precautions. Failure to observe proper handling and installation procedures can cause damage.

ESD damage can range from subtle performance degradation to complete device failure. Precision integrated circuits may be more susceptible to damage because very small parametric changes could cause the device not to meet its published specifications.

ABSOLUTE MAXIMUM RATINGS

over operating free-air temperature range (unless otherwise noted)

		VALUE	UNIT
Supply Voltage, V+ to V–			
Input Voltage		(V–) – 0.7 to (V+) + 0.7	V
Output Short-Circuit ⁽¹⁾		Continuous	
Operating Temperature		–55 to 125	°C
Storage Temperature		–55 to 125	°C
Junction Temperature	T _{JA}	150	°C/W
	T _{JC}	39	
Lead Temperature (soldering, 10 s)		300	°C

(1) Short-circuit to ground, one amplifier per package.

ELECTRICAL CHARACTERISTICS: $V_S = 5\text{ V}$

At $T_A = -55^\circ\text{C}$ to 125°C , $V_S = 5\text{ V}$, $R_L = 10\text{ k}\Omega$ connected to $V_S/2$, and $V_{OUT} = V_S/2$, unless otherwise noted.

PARAMETER	TEST CONDITIONS	MIN	TYP	MAX	UNIT
OFFSET VOLTAGE					
Input Offset Voltage V_{OS}	$T_A = 25^\circ\text{C}$, $V_{CM} = 2.5\text{ V}$		± 40	± 100	μV
	$V_{CM} = 2.5\text{ V}$			± 600	
vs Temperature ⁽¹⁾ dV_{OS}/dT	Operating Temperature Range		± 3		$\mu\text{V}/^\circ\text{C}$
vs Power Supply PSRR	$V_S = 2.7\text{ V}$ to 30 V , $V_{CM} = 1.7\text{ V}$		3	20	$\mu\text{V}/\text{V}$
vs Time			0.2		$\mu\text{V}/\text{mo}$
Channel Separation (Dual)			0.3		$\mu\text{V}/\text{V}$
INPUT BIAS CURRENT					
Input Bias Current ⁽²⁾ I_B	$V_{CM} = 2.5\text{ V}$		-15	-35	nA
Input Offset Current I_{OS}	$V_{CM} = 2.5\text{ V}$		± 1	± 12	nA
NOISE					
	$f = 1\text{ kHz}$				
Input Voltage Noise Density V_n			25		$\text{nV}/\sqrt{\text{Hz}}$
Current Noise Density I_n			80		$\text{fA}/\sqrt{\text{Hz}}$
INPUT VOLTAGE RANGE					
Common-Mode Voltage Range		0.5		$(V+) - 1$	V
Common-Mode Rejection CMRR	$V_{CM} = 0.5\text{ V}$ to 4 V	86	106		dB
INPUT IMPEDANCE					
Differential			$10^7 \parallel 5$		$\Omega \parallel \text{pF}$
Common-Mode	$V_{CM} = 2.5\text{ V}$		$10^{10} \parallel 6$		$\Omega \parallel \text{pF}$
OPEN-LOOP GAIN					
Open-Loop Voltage Gain A_{OL}	$R_L = 10\text{ k}\Omega$, $V_O = 0.25\text{ V}$ to 4 V	78	120		dB
	$R_L = 2\text{ k}\Omega$, $V_O = 0.5\text{ V}$ to 4 V	75	96		dB
FREQUENCY RESPONSE					
Gain-Bandwidth Product GBW	$C_L = 100\text{ pF}$		0.35		MHz
Slew Rate SR			0.2		$\text{V}/\mu\text{s}$
Settling Time:					
0.1%	$G = 1$, 3 V Step, $C_L = 100\text{ pF}$		15		μs
0.01%	$G = 1$, 3 V Step, $C_L = 100\text{ pF}$		25		μs
Overload Recovery Time	(V_{IN}) (Gain) = V_S		16		μs
OUTPUT					
Voltage Output:					
Positive	$R_L = 10\text{ k}\Omega$ to $V_S/2$	$(V+) - 1$	$(V+) - 0.65$		V
Negative	$R_L = 10\text{ k}\Omega$ to $V_S/2$	0.25	0.05		V
Positive	$R_L = 10\text{ k}\Omega$ to Ground	$(V+) - 1$	$(V+) - 0.65$		V
Negative	$R_L = 10\text{ k}\Omega$ to Ground	0.1	0.05		V
Short-Circuit Current I_{SC}			± 11		mA
Capacitive Load Drive (Stable Operation) ⁽³⁾	$G = 1$		1000		pF
POWER SUPPLY					
Specified Operating Voltage			5		V
Operating Voltage Range		2.7		36	V
Quiescent Current (per amplifier) I_Q	$I_O = 0$		250	550	μA

(1) Wafer-level tested to 95% confidence level.

(2) Positive conventional current flows into the input terminals.

(3) See *Small-Signal Overshoot vs Load Capacitance* typical curve.

ELECTRICAL CHARACTERISTICS: $V_S = 5\text{ V}$ (continued)

At $T_A = -55^\circ\text{C}$ to 125°C , $V_S = 5\text{ V}$, $R_L = 10\text{ k}\Omega$ connected to $V_S/2$, and $V_{OUT} = V_S/2$, unless otherwise noted.

PARAMETER	TEST CONDITIONS	MIN	TYP	MAX	UNIT
TEMPERATURE RANGE					
Specified Range		-55		125	$^\circ\text{C}$
Operating Range		-55		125	$^\circ\text{C}$
Storage		-55		125	$^\circ\text{C}$
Thermal Resistance θ_{JA}			150		$^\circ\text{C/W}$

ELECTRICAL CHARACTERISTICS: $V_S = 2.7\text{ V}$

At $T_A = -55^\circ\text{C}$ to 125°C , $V_S = 2.7\text{ V}$, $R_L = 10\text{ k}\Omega$ connected to $V_S/2$, and $V_{OUT} = V_S/2$, unless otherwise noted.

PARAMETER	TEST CONDITIONS	MIN	TYP	MAX	UNIT
OFFSET VOLTAGE					
Input Offset Voltage	V_{OS}	$T_A = 25^\circ\text{C}$, $V_{CM} = 1.35\text{ V}$	± 40	± 100	μV
		$V_{CM} = 1.35\text{ V}$		± 600	
vs Temperature ⁽¹⁾	dV_{OS}/dT	Operating Temperature Range	± 3		$\mu\text{V}/^\circ\text{C}$
vs Power Supply	PSRR	$V_S = 2.7\text{ V}$ to 30 V , $V_{CM} = 1.7\text{ V}$	3	20	$\mu\text{V}/\text{V}$
vs Time			0.2		$\mu\text{V}/\text{mo}$
Channel Separation (Dual)			0.3		$\mu\text{V}/\text{V}$
INPUT BIAS CURRENT					
Input Bias Current ⁽²⁾	I_B	$V_{CM} = 1.35\text{ V}$	-15	-35	nA
Input Offset Current	I_{OS}	$V_{CM} = 1.35\text{ V}$	± 1	± 12	nA
NOISE					
		$f = 1\text{ kHz}$			
Input Voltage Noise Density	V_n		25		$\text{nV}/\sqrt{\text{Hz}}$
Current Noise Density	I_n		80		$\text{fA}/\sqrt{\text{Hz}}$
INPUT VOLTAGE RANGE					
Common-Mode Voltage Range		0.5		$(V_+) - 1.1$	V
Common-Mode Rejection	CMRR	$V_{CM} = 0.5\text{ V}$ to 1.6 V	86	106	dB
INPUT IMPEDANCE					
Differential			$10^7 \parallel 5$		$\Omega \parallel \text{pF}$
Common-Mode		$V_{CM} = 1.35\text{ V}$	$10^{10} \parallel 6$		$\Omega \parallel \text{pF}$
OPEN-LOOP GAIN					
Open-Loop Voltage Gain	A_{OL}	$R_L = 10\text{ k}\Omega$, $V_O = 0.25\text{ V}$ to 1.7 V	78	125	dB
		$R_L = 2\text{ k}\Omega$, $V_O = 0.5\text{ V}$ to 1.7 V	69	96	dB
FREQUENCY RESPONSE					
Gain-Bandwidth Product	GBW	$C_L = 100\text{ pF}$	0.35		MHz
Slew Rate	SR		0.2		$\text{V}/\mu\text{s}$
Settling Time:					
0.1%		$G = 1$, 1 V Step, $C_L = 100\text{ pF}$	6		μs
0.01%		$G = 1$, 1 V Step, $C_L = 100\text{ pF}$	16		μs
Overload Recovery Time		(V_{IN}) (Gain) = V_S	8		μs
OUTPUT					
Voltage Output:					
Positive		$R_L = 10\text{ k}\Omega$ to $V_S/2$	$(V_+) - 1$	$(V_+) - 0.6$	V
Negative		$R_L = 10\text{ k}\Omega$ to $V_S/2$	0.25	0.05	V
Positive		$R_L = 10\text{ k}\Omega$ to Ground	$(V_+) - 1$	$(V_+) - 0.65$	V
Negative		$R_L = 10\text{ k}\Omega$ to Ground	0.1	0.05	V
Short-Circuit Current	I_{SC}		± 8		mA
Capacitive Load Drive (Stable Operation) ⁽³⁾		$G = 1$	1000		pF
POWER SUPPLY					
Specified Operating Voltage			2.7		V
Operating Voltage Range			2.7	36	V
Quiescent Current (per amplifier)	I_Q	$I_O = 0$	250	550	μA

(1) Wafer-level tested to 95% confidence level.

(2) Positive conventional current flows into the input terminals.

(3) See *Small-Signal Overshoot vs Load Capacitance* typical curve.

ELECTRICAL CHARACTERISTICS: $V_S = 2.7\text{ V}$ (continued)

At $T_A = -55^\circ\text{C}$ to 125°C , $V_S = 2.7\text{ V}$, $R_L = 10\text{ k}\Omega$ connected to $V_S/2$, and $V_{OUT} = V_S/2$, unless otherwise noted.

PARAMETER	TEST CONDITIONS	MIN	TYP	MAX	UNIT
TEMPERATURE RANGE					
Specified Range		–55		125	$^\circ\text{C}$
Operating Range		–55		125	$^\circ\text{C}$
Storage		–55		125	$^\circ\text{C}$
Thermal Resistance θ_{JA}			150		$^\circ\text{C/W}$

ELECTRICAL CHARACTERISTICS: $V_S = \pm 15\text{ V}$

At $T_A = -55^\circ\text{C}$ to 125°C , $V_S = \pm 15\text{ V}$, $R_L = 10\text{ k}\Omega$ connected to $V_S/2$, and $V_{OUT} = V_S/2$, unless otherwise noted.

PARAMETER	TEST CONDITIONS	MIN	TYP	MAX	UNIT
OFFSET VOLTAGE					
Input Offset Voltage V_{OS}	$T_A = 25^\circ\text{C}$, $V_{CM} = 0\text{ V}$		± 70	± 250	μV
	$V_{CM} = 0\text{ V}$			± 750	
vs Temperature ⁽¹⁾ dV_{OS}/dT	Operating Temperature Range		± 3		$\mu\text{V}/^\circ\text{C}$
vs Power Supply PSRR	$V_S = \pm 1.35\text{ V}$ to $\pm 18\text{ V}$, $V_{CM} = 0\text{ V}$		3	20	$\mu\text{V}/\text{V}$
vs Time			0.2		$\mu\text{V}/\text{mo}$
Channel Separation (Dual)			0.3		$\mu\text{V}/\text{V}$
INPUT BIAS CURRENT					
Input Bias Current ⁽²⁾ I_B	$V_{CM} = 0\text{ V}$		-12	-30	nA
Input Offset Current I_{OS}	$V_{CM} = 0\text{ V}$		± 1	± 12	nA
NOISE					
	$f = 1\text{ kHz}$				
Input Voltage Noise Density V_n			25		$\text{nV}/\sqrt{\text{Hz}}$
Current Noise Density I_n			80		$\text{fA}/\sqrt{\text{Hz}}$
INPUT VOLTAGE RANGE					
Common-Mode Voltage Range		$(V_-) + 1$		$(V_+) - 1$	V
Common-Mode Rejection CMRR	$V_{CM} = -14\text{ V}$ to 14 V	86	106		dB
INPUT IMPEDANCE					
Differential			$10^7 \parallel 5$		$\Omega \parallel \text{pF}$
Common-Mode	$V_{CM} = 0\text{ V}$		$10^{10} \parallel 6$		$\Omega \parallel \text{pF}$
OPEN-LOOP GAIN					
Open-Loop Voltage Gain A_{OL}	$V_O = -13.5\text{ V}$ to 13 V	87	120		dB
FREQUENCY RESPONSE					
Gain-Bandwidth Product GBW	$C_L = 100\text{ pF}$		0.35		MHz
Slew Rate SR			0.2		$\text{V}/\mu\text{s}$
Settling Time:					
0.1%	$G = 1$, 10 V Step , $C_L = 100\text{ pF}$		41		μs
0.01%	$G = 1$, 10 V Step , $C_L = 100\text{ pF}$		47		μs
Overload Recovery Time	(V_{IN}) (Gain) = V_S		22		μs
OUTPUT					
Voltage Output:					
Positive		$(V_+) - 2$	$(V_+) - 0.7$		V
Negative		$(V_-) + 1.5$	$(V_-) + 0.15$		V
Short-Circuit Current I_{SC}			± 22		mA
Capacitive Load Drive (Stable Operation) ⁽³⁾	$G = 1$		1000		pF
POWER SUPPLY					
Specified Operating Voltage			± 15		V
Operating Voltage Range		± 1.35		± 18	V
Quiescent Current (per amplifier) I_Q	$I_O = 0$		± 275	± 550	μA

(1) Wafer-level tested to 95% confidence level.

(2) Positive conventional current flows into the input terminals.







(3) See *Small-Signal Overshoot vs Load Capacitance* typical curve.

ELECTRICAL CHARACTERISTICS: $V_S = \pm 15\text{ V}$ (continued)







At $T_A = -55^\circ\text{C}$ to 125°C , $V_S = \pm 15\text{ V}$, $R_L = 10\text{ k}\Omega$ connected to $V_S/2$, and $V_{OUT} = V_S/2$, unless otherwise noted.

PARAMETER	TEST CONDITIONS	MIN	TYP	MAX	UNIT
TEMPERATURE RANGE					
Specified Range		-55		125	$^\circ\text{C}$
Operating Range		-55		125	$^\circ\text{C}$
Storage		-55		125	$^\circ\text{C}$
Thermal Resistance θ_{JA}			150		$^\circ\text{C/W}$

TYPICAL CHARACTERISTICS




TYPICAL CHARACTERISTICS (continued)



TYPICAL CHARACTERISTICS (continued)

SMALL-SIGNAL STEP RESPONSE


$G = 1$, $C_L = 100$ pF, $V_S = 5$ V



2 μs/div

SMALL-SIGNAL STEP RESPONSE


$G = 1$, $C_L = 10,000$ pF, $V_S = 5$ V



20 μs/div


LARGE-SIGNAL STEP RESPONSE

$G = 1$, $C_L = 100$ pF, $V_S = 5$ V




10 μs/div


SETTLING TIME vs CLOSED-LOOP GAIN





OUTPUT VOLTAGE SWING vs OUTPUT CURRENT



SMALL-SIGNAL OVERSHOOT vs LOAD CAPACITANCE



TYPICAL CHARACTERISTICS (continued)



APPLICATION INFORMATION

The OPA2234 series op amps are unity-gain stable and suitable for a wide range of general-purpose applications. Power-supply pins should be bypassed with 10 nF ceramic capacitors.

OPERATING VOLTAGE

The OPA2234 series op amps operate from single (2.7 V to 36 V) or dual (± 1.35 V to ± 18 V) supplies with excellent performance. Specifications are production tested with 2.7 V, 5 V, and ± 15 V supplies. Most behavior remains unchanged throughout the full operating voltage range. Parameters which vary significantly with operating voltage are shown in the Typical Characteristic curves.

PACKAGING INFORMATION

Orderable Device	Status ⁽¹⁾	Package Type	Package Drawing	Pins	Package Qty	Eco Plan ⁽²⁾	Lead/ Ball Finish	MSL Peak Temp ⁽³⁾	Samples (Requires Login)
OPA2234MDR	ACTIVE	SOIC	D	8	2500	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-3-260C-168 HR	

⁽¹⁾ The marketing status values are defined as follows:

ACTIVE: Product device recommended for new designs.

LIFEBUY: TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.

NRND: Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.

PREVIEW: Device has been announced but is not in production. Samples may or may not be available.

OBSOLETE: TI has discontinued the production of the device.

⁽²⁾ Eco Plan - The planned eco-friendly classification: Pb-Free (RoHS), Pb-Free (RoHS Exempt), or Green (RoHS & no Sb/Br) - please check <http://www.ti.com/productcontent> for the latest availability information and additional product content details.

TBD: The Pb-Free/Green conversion plan has not been defined.

Pb-Free (RoHS): TI's terms "Lead-Free" or "Pb-Free" mean semiconductor products that are compatible with the current RoHS requirements for all 6 substances, including the requirement that lead not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, TI Pb-Free products are suitable for use in specified lead-free processes.

Pb-Free (RoHS Exempt): This component has a RoHS exemption for either 1) lead-based flip-chip solder bumps used between the die and package, or 2) lead-based die adhesive used between the die and leadframe. The component is otherwise considered Pb-Free (RoHS compatible) as defined above.

Green (RoHS & no Sb/Br): TI defines "Green" to mean Pb-Free (RoHS compatible), and free of Bromine (Br) and Antimony (Sb) based flame retardants (Br or Sb do not exceed 0.1% by weight in homogeneous material)

⁽³⁾ MSL, Peak Temp. -- The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.

Important Information and Disclaimer: The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

OTHER QUALIFIED VERSIONS OF OPA2234M :

- Catalog: [OPA2234](#)

NOTE: Qualified Version Definitions:

- Catalog - TI's standard catalog product

TAPE AND REEL INFORMATION
REEL DIMENSIONS

TAPE DIMENSIONS


A0	Dimension designed to accommodate the component width
B0	Dimension designed to accommodate the component length
K0	Dimension designed to accommodate the component thickness
W	Overall width of the carrier tape
P1	Pitch between successive cavity centers

TAPE AND REEL INFORMATION

*All dimensions are nominal

Device	Package Type	Package Drawing	Pins	SPQ	Reel Diameter (mm)	Reel Width W1 (mm)	A0 (mm)	B0 (mm)	K0 (mm)	P1 (mm)	W (mm)	Pin1 Quadrant
OPA2234MDR	SOIC	D	8	2500	330.0	12.4	6.4	5.2	2.1	8.0	12.0	Q1

TAPE AND REEL BOX DIMENSIONS



*All dimensions are nominal

Device	Package Type	Package Drawing	Pins	SPQ	Length (mm)	Width (mm)	Height (mm)
OPA2234MDR	SOIC	D	8	2500	367.0	367.0	35.0

D (R-PDSO-G8)

PLASTIC SMALL OUTLINE



NOTES:

- A. All linear dimensions are in inches (millimeters).
- B. This drawing is subject to change without notice.
- $\triangle C$ Body length does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0.006 (0,15) each side.
- $\triangle D$ Body width does not include interlead flash. Interlead flash shall not exceed 0.017 (0,43) each side.
- E. Reference JEDEC MS-012 variation AA.

D (R-PDSO-G8)

PLASTIC SMALL OUTLINE



- NOTES:
- A. All linear dimensions are in millimeters.
 - B. This drawing is subject to change without notice.
 - C. Publication IPC-7351 is recommended for alternate designs.
 - D. Laser cutting apertures with trapezoidal walls and also rounding corners will offer better paste release. Customers should contact their board assembly site for stencil design recommendations. Refer to IPC-7525 for other stencil recommendations.
 - E. Customers should contact their board fabrication site for solder mask tolerances between and around signal pads.

IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, enhancements, improvements and other changes to its semiconductor products and services per JESD46, latest issue, and to discontinue any product or service per JESD48, latest issue. Buyers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All semiconductor products (also referred to herein as "components") are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its components to the specifications applicable at the time of sale, in accordance with the warranty in TI's terms and conditions of sale of semiconductor products. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by applicable law, testing of all parameters of each component is not necessarily performed.

TI assumes no liability for applications assistance or the design of Buyers' products. Buyers are responsible for their products and applications using TI components. To minimize the risks associated with Buyers' products and applications, Buyers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any patent right, copyright, mask work right, or other intellectual property right relating to any combination, machine, or process in which TI components or services are used. Information published by TI regarding third-party products or services does not constitute a license to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of significant portions of TI information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. TI is not responsible or liable for such altered documentation. Information of third parties may be subject to additional restrictions.

Resale of TI components or services with statements different from or beyond the parameters stated by TI for that component or service voids all express and any implied warranties for the associated TI component or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

Buyer acknowledges and agrees that it is solely responsible for compliance with all legal, regulatory and safety-related requirements concerning its products, and any use of TI components in its applications, notwithstanding any applications-related information or support that may be provided by TI. Buyer represents and agrees that it has all the necessary expertise to create and implement safeguards which anticipate dangerous consequences of failures, monitor failures and their consequences, lessen the likelihood of failures that might cause harm and take appropriate remedial actions. Buyer will fully indemnify TI and its representatives against any damages arising out of the use of any TI components in safety-critical applications.

In some cases, TI components may be promoted specifically to facilitate safety-related applications. With such components, TI's goal is to help enable customers to design and create their own end-product solutions that meet applicable functional safety standards and requirements. Nonetheless, such components are subject to these terms.

No TI components are authorized for use in FDA Class III (or similar life-critical medical equipment) unless authorized officers of the parties have executed a special agreement specifically governing such use.

Only those TI components which TI has specifically designated as military grade or "enhanced plastic" are designed and intended for use in military/aerospace applications or environments. Buyer acknowledges and agrees that any military or aerospace use of TI components which have **not** been so designated is solely at the Buyer's risk, and that Buyer is solely responsible for compliance with all legal and regulatory requirements in connection with such use.

TI has specifically designated certain components which meet ISO/TS16949 requirements, mainly for automotive use. Components which have not been so designated are neither designed nor intended for automotive use; and TI will not be responsible for any failure of such components to meet such requirements.

Products

Audio	www.ti.com/audio
Amplifiers	amplifier.ti.com
Data Converters	dataconverter.ti.com
DLP® Products	www.dlp.com
DSP	dsp.ti.com
Clocks and Timers	www.ti.com/clocks
Interface	interface.ti.com
Logic	logic.ti.com
Power Mgmt	power.ti.com
Microcontrollers	microcontroller.ti.com
RFID	www.ti-rfid.com
OMAP Applications Processors	www.ti.com/omap
Wireless Connectivity	www.ti.com/wirelessconnectivity

Applications

Automotive and Transportation	www.ti.com/automotive
Communications and Telecom	www.ti.com/communications
Computers and Peripherals	www.ti.com/computers
Consumer Electronics	www.ti.com/consumer-apps
Energy and Lighting	www.ti.com/energy
Industrial	www.ti.com/industrial
Medical	www.ti.com/medical
Security	www.ti.com/security
Space, Avionics and Defense	www.ti.com/space-avionics-defense
Video and Imaging	www.ti.com/video

TI E2E Community

e2e.ti.com