

# MC10EL07, MC100EL07

## 5.0 V ECL 2-Input XOR/XNOR

The MC10EL/100EL07 is a 2-input XOR/XNOR gate. The device is functionally equivalent to the E107 device with higher performance capabilities. With propagation delays and output transition times significantly faster than the E107, the EL07 is ideally suited for those applications which require the ultimate in AC performance.

The 100 Series contains temperature compensation.

### Features

- 260 ps Propagation Delay
- ESD Protection: Human Body Model; > 1.0 KV  
Machine Model; > 100 V
- PECL Mode Operating Range:  $V_{CC} = 4.2 \text{ V}$  to  $5.7 \text{ V}$   
with  $V_{EE} = 0 \text{ V}$
- NECL Mode Operating Range:  $V_{CC} = 0 \text{ V}$   
with  $V_{EE} = -4.2 \text{ V}$  to  $-5.7 \text{ V}$
- Internal Input Pulldown Resistors
- Meets or Exceeds JEDEC Spec EIA/JESD78 IC Latchup Test
- Moisture Sensitivity Level 1  
For Additional Information, see Application Note AND8003/D
- Flammability Rating: UL 94 V-0 @ 0.125 in,  
Oxygen Index: 28 to 34
- Transistor Count = 47 devices
- Pb-Free Packages are Available




Figure 1. Logic Diagram and Pinout Assignment

### PIN DESCRIPTION

| PIN          | FUNCTION         |
|--------------|------------------|
| D0, D1       | ECL Data Inputs  |
| Q, $\bar{Q}$ | ECL Data Outputs |
| $V_{CC}$     | Positive Supply  |
| $V_{EE}$     | Negative Supply  |
| NC           | No Connect       |




ON Semiconductor®


<http://onsemi.com>

### MARKING DIAGRAMS\*

8  
1  
SOIC-8  
D SUFFIX  
CASE 751



8  
1  
TSSOP-8  
DT SUFFIX  
CASE 948R



H = MC10  
K = MC100  
A = Assembly Location  
L = Wafer Lot  
Y = Year  
W = Work Week

\*For additional marking information, refer to Application Note AND8002/D.

### ORDERING INFORMATION

| Device        | Package          | Shipping <sup>†</sup> |
|---------------|------------------|-----------------------|
| MC10EL07D     | SOIC-8           | 98 Units / Rail       |
| MC10EL07DR2G  | SOIC-8 (Pb-Free) | 2500 Tape & Reel      |
| MC100EL07DG   | SOIC-8 (Pb-Free) | 98 Units / Rail       |
| MC100EL07DR2G | SOIC-8 (Pb-Free) | 2500 Tape & Reel      |
| MC10EL07DT    | TSSOP-8          | 98 Units / Rail       |
| MC10EL07DTR2  | TSSOP-8          | 2500 Tape & Reel      |
| MC100EL07DT   | TSSOP-8          | 98 Units / Rail       |
| MC100EL07DTR2 | TSSOP-8          | 2500 Tape & Reel      |

<sup>†</sup>For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

# MC10EL07, MC100EL07

## MAXIMUM RATINGS

| Symbol           | Parameter                                          | Condition 1                                    | Condition 2                                                          | Rating        | Units        |
|------------------|----------------------------------------------------|------------------------------------------------|----------------------------------------------------------------------|---------------|--------------|
| V <sub>CC</sub>  | PECL Mode Power Supply                             | V <sub>EE</sub> = 0 V                          |                                                                      | 8             | V            |
| V <sub>EE</sub>  | NECL Mode Power Supply                             | V <sub>CC</sub> = 0 V                          |                                                                      | -8            | V            |
| V <sub>I</sub>   | PECL Mode Input Voltage<br>NECL Mode Input Voltage | V <sub>EE</sub> = 0 V<br>V <sub>CC</sub> = 0 V | V <sub>I</sub> ≤ V <sub>CC</sub><br>V <sub>I</sub> ≥ V <sub>EE</sub> | 6<br>-6       | V<br>V       |
| I <sub>out</sub> | Output Current                                     | Continuous<br>Surge                            |                                                                      | 50<br>100     | mA<br>mA     |
| T <sub>A</sub>   | Operating Temperature Range                        |                                                |                                                                      | -40 to +85    | °C           |
| T <sub>stg</sub> | Storage Temperature Range                          |                                                |                                                                      | -65 to +150   | °C           |
| θ <sub>JA</sub>  | Thermal Resistance (Junction-to-Ambient)           | 0 lfpm<br>500 lfpm                             | SOIC-8<br>SOIC-8                                                     | 190<br>130    | °C/W<br>°C/W |
| θ <sub>JC</sub>  | Thermal Resistance (Junction-to-Case)              | Standard Board                                 | SOIC-8                                                               | 41 to 44      | °C/W         |
| θ <sub>JA</sub>  | Thermal Resistance (Junction-to-Ambient)           | 0 lfpm<br>500 lfpm                             | TSSOP-8<br>TSSOP-8                                                   | 185<br>140    | °C/W<br>°C/W |
| θ <sub>JC</sub>  | Thermal Resistance (Junction-to-Case)              | Standard Board                                 | TSSOP-8                                                              | 41 to 44 ± 5% | °C/W         |
| T <sub>sol</sub> | Wave Solder                                        | <2 to 3 sec @ 248°C                            |                                                                      | 265           | °C           |

Maximum ratings applied to the device are individual stress limit values (not normal operating conditions) and are not valid simultaneously. If stress limits are exceeded device functional operation is not implied, damage may occur and reliability may be affected. Functional operation should be restricted to the Recommended Operating Conditions.

## 10EL SERIES PECL DC CHARACTERISTICS V<sub>CC</sub>= 5.0 V; V<sub>EE</sub>= 0.0 V (Note 1)

| Symbol          | Characteristic                 | -40°C |      |            | 25°C |      |            | 85°C |      |            | Unit |
|-----------------|--------------------------------|-------|------|------------|------|------|------------|------|------|------------|------|
|                 |                                | Min   | Typ  | Max        | Min  | Typ  | Max        | Min  | Typ  | Max        |      |
| I <sub>EE</sub> | Power Supply Current           |       | 14   | 17         |      | 14   | 17         |      | 14   | 17         | mA   |
| V <sub>OH</sub> | Output HIGH Voltage (Note 4)   | 3920  | 4010 | 4110       | 4020 | 4105 | 4190       | 4090 | 4185 | 4280       | mV   |
| V <sub>OL</sub> | Output LOW Voltage (Note 2)    | 3050  | 3200 | 3350       | 3050 | 3210 | 3370       | 3050 | 3227 | 3405       | mV   |
| V <sub>IH</sub> | Input HIGH Voltage             | 3770  |      | 4110       | 3870 |      | 4190       | 3940 |      | 4280       | mV   |
| V <sub>IL</sub> | Input LOW Voltage              | 3050  |      | 3500       | 3050 |      | 3520       | 3050 |      | 3555       | mV   |
| I <sub>IH</sub> | Input HIGH Current<br>D0<br>D1 |       |      | 250<br>150 |      |      | 250<br>150 |      |      | 250<br>150 | μA   |
| I <sub>IL</sub> | Input LOW Current              | 0.5   |      |            | 0.5  |      |            | 0.3  |      |            | μA   |

NOTE: Device will meet the specifications after thermal equilibrium has been established when mounted in a test socket or printed circuit board with maintained transverse airflow greater than 500 lfpm. Electrical parameters are guaranteed only over the declared operating temperature range. Functional operation of the device exceeding these conditions is not implied. Device specification limit values are applied individually under normal operating conditions and not valid simultaneously.

- Input and output parameters vary 1:1 with V<sub>CC</sub>.  
V<sub>EE</sub> can vary +0.25 V / -0.5 V for +25°C and +85°C. or V<sub>EE</sub> can vary +0.06 V / -0.5 V for -40°C.
- Outputs are terminated through a 50 Ω resistor to V<sub>CC</sub> - 2 volts.

# MC10EL07, MC100EL07

## 10EL SERIES NECL DC CHARACTERISTICS $V_{CC}= 0.0\text{ V}$ ; $V_{EE}= -5.0\text{ V}$ (Note 3)

| Symbol   | Characteristic               | -40°C |       |            | 25°C  |       |            | 85°C  |       |            | Unit          |
|----------|------------------------------|-------|-------|------------|-------|-------|------------|-------|-------|------------|---------------|
|          |                              | Min   | Typ   | Max        | Min   | Typ   | Max        | Min   | Typ   | Max        |               |
| $I_{EE}$ | Power Supply Current         |       | 14    | 17         |       | 14    | 17         |       | 14    | 17         | mA            |
| $V_{OH}$ | Output HIGH Voltage (Note 4) | -1080 | -990  | -890       | -980  | -895  | -810       | -910  | -815  | -720       | mV            |
| $V_{OL}$ | Output LOW Voltage (Note 4)  | -1950 | -1800 | -1650      | -1950 | -1790 | -1630      | -1950 | -1773 | -1595      | mV            |
| $V_{IH}$ | Input HIGH Voltage           | -1230 |       | -890       | -1130 |       | -810       | -1060 |       | -720       | mV            |
| $V_{IL}$ | Input LOW Voltage            | -1950 |       | -1500      | -1950 |       | -1480      | -1950 |       | -1445      | mV            |
| $I_{IH}$ | Input HIGH Current           |       |       | 250<br>150 |       |       | 250<br>150 |       |       | 250<br>150 | $\mu\text{A}$ |
|          | D0<br>D1                     |       |       |            |       |       |            |       |       |            |               |
| $I_{IL}$ | Input LOW Current            | 0.5   |       |            | 0.5   |       |            | 0.3   |       |            | $\mu\text{A}$ |

NOTE: Device will meet the specifications after thermal equilibrium has been established when mounted in a test socket or printed circuit board with maintained transverse airflow greater than 500 lfm. Electrical parameters are guaranteed only over the declared operating temperature range. Functional operation of the device exceeding these conditions is not implied. Device specification limit values are applied individually under normal operating conditions and not valid simultaneously.

3. Input and output parameters vary 1:1 with  $V_{CC}$ .

$V_{EE}$  can vary +0.25 V / -0.5 V for +25°C and +85°C. or  $V_{EE}$  can vary +0.06 V / -0.5 V for -40°C.

4. Outputs are terminated through a 50  $\Omega$  resistor to  $V_{CC} - 2$  volts

## 100EL SERIES PECL DC CHARACTERISTICS $V_{CC}= 5.0\text{ V}$ ; $V_{EE}= 0.0\text{ V}$ (Note 5)

| Symbol   | Characteristic               | -40°C |      |            | 25°C |      |            | 85°C |      |            | Unit          |
|----------|------------------------------|-------|------|------------|------|------|------------|------|------|------------|---------------|
|          |                              | Min   | Typ  | Max        | Min  | Typ  | Max        | Min  | Typ  | Max        |               |
| $I_{EE}$ | Power Supply Current         |       | 14   | 17         |      | 14   | 17         |      | 16   | 20         | mA            |
| $V_{OH}$ | Output HIGH Voltage (Note 6) | 3915  | 3995 | 4120       | 3975 | 4045 | 4120       | 3975 | 4050 | 4120       | mV            |
| $V_{OL}$ | Output LOW Voltage (Note 6)  | 3170  | 3305 | 3445       | 3190 | 3295 | 3380       | 3190 | 3295 | 3380       | mV            |
| $V_{IH}$ | Input HIGH Voltage           | 3835  |      | 4120       | 3835 |      | 4120       | 3835 |      | 4120       | mV            |
| $V_{IL}$ | Input LOW Voltage            | 3190  |      | 3525       | 3190 |      | 3525       | 3190 |      | 3525       | mV            |
| $I_{IH}$ | Input HIGH Current           |       |      | 250<br>150 |      |      | 250<br>150 |      |      | 250<br>150 | $\mu\text{A}$ |
|          | D0<br>D1                     |       |      |            |      |      |            |      |      |            |               |
| $I_{IL}$ | Input LOW Current            | 0.5   |      |            | 0.5  |      |            | 0.5  |      |            | $\mu\text{A}$ |

NOTE: Device will meet the specifications after thermal equilibrium has been established when mounted in a test socket or printed circuit board with maintained transverse airflow greater than 500 lfm. Electrical parameters are guaranteed only over the declared operating temperature range. Functional operation of the device exceeding these conditions is not implied. Device specification limit values are applied individually under normal operating conditions and not valid simultaneously.

5. Input and output parameters vary 1:1 with  $V_{CC}$ .  $V_{EE}$  can vary +0.8 V / -0.5 V.

6. Outputs are terminated through a 50  $\Omega$  resistor to  $V_{CC} - 2$  volts

# MC10EL07, MC100EL07

## 100EL SERIES NECL DC CHARACTERISTICS $V_{CC}=0.0\text{ V}$ ; $V_{EE}=-5.0\text{ V}$ (Note 7)

| Symbol   | Characteristic                 | -40°C |       |            | 25°C  |       |            | 85°C  |       |            | Unit          |
|----------|--------------------------------|-------|-------|------------|-------|-------|------------|-------|-------|------------|---------------|
|          |                                | Min   | Typ   | Max        | Min   | Typ   | Max        | Min   | Typ   | Max        |               |
| $I_{EE}$ | Power Supply Current           |       | 14    | 17         |       | 14    | 17         |       | 16    | 20         | mA            |
| $V_{OH}$ | Output HIGH Voltage (Note 8)   | -1085 | -1005 | -880       | -1025 | -955  | -880       | -1025 | -955  | -880       | mV            |
| $V_{OL}$ | Output LOW Voltage (Note 8)    | -1830 | -1695 | -1555      | -1810 | -1705 | -1620      | -1810 | -1705 | -1620      | mV            |
| $V_{IH}$ | Input HIGH Voltage             | -1165 |       | -880       | -1165 |       | -880       | -1165 |       | -880       | mV            |
| $V_{IL}$ | Input LOW Voltage              | -1810 |       | -1475      | -1810 |       | -1475      | -1810 |       | -1475      | mV            |
| $I_{IH}$ | Input HIGH Current<br>D0<br>D1 |       |       | 250<br>150 |       |       | 250<br>150 |       |       | 250<br>150 | $\mu\text{A}$ |
| $I_{IL}$ | Input LOW Current              | 0.5   |       |            | 0.5   |       |            | 0.5   |       |            | $\mu\text{A}$ |

NOTE: Device will meet the specifications after thermal equilibrium has been established when mounted in a test socket or printed circuit board with maintained transverse airflow greater than 500 lfm. Electrical parameters are guaranteed only over the declared operating temperature range. Functional operation of the device exceeding these conditions is not implied. Device specification limit values are applied individually under normal operating conditions and not valid simultaneously.

7. Input and output parameters vary 1:1 with  $V_{CC}$ .  $V_{EE}$  can vary +0.8 V / -0.5 V.

8. Outputs are terminated through a 50  $\Omega$  resistor to  $V_{CC} - 2$  volts


## AC CHARACTERISTICS $V_{CC}=5.0\text{ V}$ ; $V_{EE}=0.0\text{ V}$ or $V_{CC}=0.0\text{ V}$ ; $V_{EE}=-5.0\text{ V}$ (Note 9)

| Symbol                 | Characteristic                          | -40°C |     |     | 25°C |     |     | 85°C |     |     | Unit |
|------------------------|-----------------------------------------|-------|-----|-----|------|-----|-----|------|-----|-----|------|
|                        |                                         | Min   | Typ | Max | Min  | Typ | Max | Min  | Typ | Max |      |
| $f_{\max}$             | Maximum Toggle Frequency                |       |     |     |      | > 2 |     |      |     |     | GHz  |
| $t_{PLH}$<br>$t_{PHL}$ | Propagation Delay to Output             | 90    | 250 | 435 | 150  | 260 | 395 | 170  | 280 | 415 | ps   |
| $t_{JITTER}$           | Random Clock Jitter                     |       | 0.5 |     |      | 0.5 |     |      | 0.5 |     | ps   |
| $t_r$<br>$t_f$         | Output Rise/Fall Times Q<br>(20% - 80%) | 100   | 225 | 350 | 100  | 225 | 350 | 100  | 225 | 350 | ps   |

9. 10 Series:  $V_{EE}$  can vary +0.25 V / -0.5 V for +25°C and +85°C. or  $V_{EE}$  can vary +0.06 V / -0.5 V for -40°C.

100 Series:  $V_{EE}$  can vary +0.8 V / -0.5 V.

## MC10EL07, MC100EL07



**Figure 2. Typical Termination for Output Driver and Device Evaluation**  
(See Application Note AND8020 – Termination of ECL Logic Devices.)


### Resource Reference of Application Notes

- |                |                                        |
|----------------|----------------------------------------|
| <b>AN1405</b>  | - ECL Clock Distribution Techniques    |
| <b>AN1406</b>  | - Designing with PECL (ECL at +5.0 V)  |
| <b>AN1503</b>  | - ECLinPS I/O SPICE Modeling Kit       |
| <b>AN1504</b>  | - Metastability and the ECLinPS Family |
| <b>AN1568</b>  | - Interfacing Between LVDS and ECL     |
| <b>AN1672</b>  | - The ECL Translator Guide             |
| <b>AND8001</b> | - Odd Number Counters Design           |
| <b>AND8002</b> | - Marking and Date Codes               |
| <b>AND8020</b> | - Termination of ECL Logic Devices     |
| <b>AND8066</b> | - Interfacing with ECLinPS             |
| <b>AND8090</b> | - AC Characteristics of ECL Devices    |

# MC10EL07, MC100EL07

## PACKAGE DIMENSIONS

### SOIC-8 D SUFFIX CASE 751-07 ISSUE AB




#### NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: MILLIMETER.
3. DIMENSION A AND B DO NOT INCLUDE MOLD PROTRUSION.
4. MAXIMUM MOLD PROTRUSION 0.15 (0.006) PER SIDE.
5. DIMENSION D DOES NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE DAMBAR PROTRUSION SHALL BE 0.127 (0.005) TOTAL IN EXCESS OF THE D DIMENSION AT MAXIMUM MATERIAL CONDITION.
6. 751-01 THRU 751-06 ARE OBSOLETE. NEW STANDARD IS 751-07.

| DIM | MILLIMETERS |      | INCHES    |       |
|-----|-------------|------|-----------|-------|
|     | MIN         | MAX  | MIN       | MAX   |
| A   | 4.80        | 5.00 | 0.189     | 0.197 |
| B   | 3.80        | 4.00 | 0.150     | 0.157 |
| C   | 1.35        | 1.75 | 0.053     | 0.069 |
| D   | 0.33        | 0.51 | 0.013     | 0.020 |
| G   | 1.27 BSC    |      | 0.050 BSC |       |
| H   | 0.10        | 0.25 | 0.004     | 0.010 |
| J   | 0.19        | 0.25 | 0.007     | 0.010 |
| K   | 0.40        | 1.27 | 0.016     | 0.050 |
| M   | 0°          | 8°   | 0°        | 8°    |
| N   | 0.25        | 0.50 | 0.010     | 0.020 |
| S   | 5.80        | 6.20 | 0.228     | 0.244 |

### SOLDERING FOOTPRINT\*



SCALE 6:1 (mm/inches)


### SOIC-8

\*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

# MC10EL07, MC100EL07

## PACKAGE DIMENSIONS

TSSOP-8  
DT SUFFIX  
CASE 948R-02  
ISSUE A



# MC10EL07, MC100EL07

ON Semiconductor and  are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## PUBLICATION ORDERING INFORMATION

### LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor  
P.O. Box 5163, Denver, Colorado 80217 USA

**Phone:** 303-675-2175 or 800-344-3860 Toll Free USA/Canada

**Fax:** 303-675-2176 or 800-344-3867 Toll Free USA/Canada

**Email:** [orderlit@onsemi.com](mailto:orderlit@onsemi.com)

**N. American Technical Support:** 800-282-9855 Toll Free  
USA/Canada

**Japan:** ON Semiconductor, Japan Customer Focus Center  
2-9-1 Kamimeguro, Meguro-ku, Tokyo, Japan 153-0051  
**Phone:** 81-3-5773-3850

**ON Semiconductor Website:** <http://onsemi.com>

**Order Literature:** <http://www.onsemi.com/litorder>

For additional information, please contact your  
local Sales Representative.