

Designer's™ Data Sheet

Insulated Gate Bipolar Transistor with Anti-Parallel Diode



N-Channel Enhancement-Mode Silicon Gate

MGP11N60ED

IGBT & DIODE IN TO-220
11 A @ 90°C
15 A @ 25°C
600 VOLTS
SHORT CIRCUIT RATED
LOW ON-VOLTAGE

This Insulated Gate Bipolar Transistor (IGBT) is co-packaged with a soft recovery ultra-fast rectifier and uses an advanced termination scheme to provide an enhanced and reliable high voltage-blocking capability. Its new 600 V IGBT technology is specifically suited for applications requiring both a high temperature short circuit capability and a low $V_{CE(on)}$. It also provides fast switching characteristics and results in efficient operation at high frequencies. Co-packaged IGBTs save space, reduce assembly time and cost. This new E-series introduces an energy efficient, ESD protected, and rugged short circuit device.

- Industry Standard TO-220 Package
- High Speed: $E_{off} = 60 \mu J$ per Amp typical at 125°C
- High Voltage Short Circuit Capability – 10 μs minimum at 125°C, 400 V
- Low On-Voltage — 2.0 V typical at 8.0 A
- Soft Recovery Free Wheeling Diode is included in the Package
- Robust High Voltage Termination
- ESD Protection Gate-Emitter Zener Diodes



CASE 221A-09
STYLE 9
TO-220AB

MAXIMUM RATINGS ($T_J = 25^\circ C$ unless otherwise noted)

Rating	Symbol	Value	Unit
Collector-Emitter Voltage	V_{CES}	600	Vdc
Collector-Gate Voltage ($R_{GE} = 1.0 M\Omega$)	V_{CGR}	600	Vdc
Gate-Emitter Voltage — Continuous	V_{GE}	± 20	Vdc
Collector Current — Continuous @ $T_C = 25^\circ C$ — Continuous @ $T_C = 90^\circ C$ — Repetitive Pulsed Current (1)	I_{C25} I_{C90} I_{CM}	15 11 22	Adc Apk
Total Power Dissipation @ $T_C = 25^\circ C$ Derate above 25°C	P_D	96 0.77	Watts W/°C
Operating and Storage Junction Temperature Range	T_J, T_{stg}	-55 to 150	°C
Short Circuit Withstand Time ($V_{CC} = 400$ Vdc, $V_{GE} = 15$ Vdc, $T_J = 125^\circ C$, $R_G = 20 \Omega$)	t_{sc}	10	μs
Thermal Resistance — Junction to Case – IGBT — Junction to Case – Diode — Junction to Ambient	$R_{\theta JC}$ $R_{\theta JC}$ $R_{\theta JA}$	1.3 2.3 65	°C/W
Maximum Lead Temperature for Soldering Purposes, 1/8" from case for 5 seconds	T_L	260	°C
Mounting Torque, 6-32 or M3 screw	10 lbf•in (1.13 N•m)		

(1) Pulse width is limited by maximum junction temperature. Repetitive rating.

Designer's Data for "Worst Case" Conditions — The Designer's Data Sheet permits the design of most circuits entirely from the information presented. SOA Limit curves — representing boundaries on device characteristics — are given to facilitate "worst case" design.

Designer's™ is a trademark of Motorola, Inc.



MGP11N60ED**ELECTRICAL CHARACTERISTICS** ($T_J = 25^\circ\text{C}$ unless otherwise noted)





Characteristic	Symbol	Min	Typ	Max	Unit	
OFF CHARACTERISTICS						
Collector-to-Emitter Breakdown Voltage ($V_{GE} = 0$ Vdc, $I_C = 250$ μ Adc) Temperature Coefficient (Positive)	$V_{(BR)CES}$	600 —	— 870	— —	Vdc mV/°C	
Zero Gate Voltage Collector Current ($V_{CE} = 600$ Vdc, $V_{GE} = 0$ Vdc) ($V_{CE} = 600$ Vdc, $V_{GE} = 0$ Vdc, $T_J = 125^\circ\text{C}$)	I_{CES}	— —	— —	10 200	μ Adc	
Gate-Body Leakage Current ($V_{GE} = \pm 20$ Vdc, $V_{CE} = 0$ Vdc)	I_{GES}	—	—	50	μ Adc	
ON CHARACTERISTICS (1)						
Collector-to-Emitter On-State Voltage ($V_{GE} = 15$ Vdc, $I_C = 4.0$ Adc) ($V_{GE} = 15$ Vdc, $I_C = 4.0$ Adc, $T_J = 125^\circ\text{C}$) ($V_{GE} = 15$ Vdc, $I_C = 8.0$ Adc)	$V_{CE(on)}$	— — —	1.6 1.5 2.0	1.9 — 2.4	Vdc	
Gate Threshold Voltage ($V_{CE} = V_{GE}$, $I_C = 1.0$ mAdc) Threshold Temperature Coefficient (Negative)	$V_{GE(th)}$	4.0 —	6.0 10	8.0 —	Vdc mV/°C	
Forward Transconductance ($V_{CE} = 10$ Vdc, $I_C = 8.0$ Adc)	g_{fe}	—	3.5	—	Mhos	
DYNAMIC CHARACTERISTICS						
Input Capacitance	$(V_{CE} = 25$ Vdc, $V_{GE} = 0$ Vdc, $f = 1.0$ MHz)	C_{ies}	—	779	pF	
Output Capacitance		C_{oes}	—	81		
Transfer Capacitance		C_{res}	—	13		
SWITCHING CHARACTERISTICS (1)						
Turn-On Delay Time	$(V_{CC} = 360$ Vdc, $I_C = 8.0$ Adc, $V_{GE} = 15$ Vdc, $L = 300$ μ H, $R_G = 20$ Ω) Energy losses include "tail"	$t_{d(on)}$	—	46	ns	
Rise Time		t_r	—	34		
Turn-Off Delay Time		$t_{d(off)}$	—	102		
Fall Time		t_f	—	226		
Turn-Off Switching Loss		E_{off}	—	0.32	0.40	mJ
Turn-On Switching Loss		E_{on}	—	0.11	—	
Total Switching Loss		E_{ts}	—	0.43	—	
Turn-On Delay Time	$(V_{CC} = 360$ Vdc, $I_C = 8.0$ Adc, $V_{GE} = 15$ Vdc, $L = 300$ μ H, $R_G = 20$ Ω , $T_J = 125^\circ\text{C}$) Energy losses include "tail"	$t_{d(on)}$	—	42	ns	
Rise Time		t_r	—	26		
Turn-Off Delay Time		$t_{d(off)}$	—	214		
Fall Time		t_f	—	228		
Turn-Off Switching Loss		E_{off}	—	0.48	—	mJ
Turn-On Switching Loss		E_{on}	—	0.16	—	
Total Switching Loss		E_{ts}	—	0.64	—	
Gate Charge	$(V_{CC} = 360$ Vdc, $I_C = 8.0$ Adc, $V_{GE} = 15$ Vdc)	Q_T	—	39.2	nC	
		Q_1	—	8.7		
		Q_2	—	17.4		
DIODE CHARACTERISTICS						
Diode Forward Voltage Drop ($I_{EC} = 3.25$ Adc) ($I_{EC} = 3.25$ Adc, $T_J = 125^\circ\text{C}$) ($I_{EC} = 6.5$ Adc)	V_{FEC}	— — 1.7	1.63 1.24 2.0	— — 2.3	Vdc	

(1) Pulse Test: Pulse Width $\leq 300\text{ }\mu\text{s}$, Duty Cycle $\leq 2\%$.

(continued)

ELECTRICAL CHARACTERISTICS — continued ($T_J = 25^\circ\text{C}$ unless otherwise noted)

Characteristic	Symbol	Min	Typ	Max	Unit
DIODE CHARACTERISTICS — continued					
Reverse Recovery Time	$(I_F = 8.0 \text{ Adc}, V_R = 360 \text{ Vdc}, dI_F/dt = 200 \text{ A}/\mu\text{s})$	t_{rr}	—	57	—
		t_a	—	18	—
		t_b	—	39	—
Reverse Recovery Stored Charge		Q_{RR}	—	107	μC
Reverse Recovery Time	$(I_F = 8.0 \text{ Adc}, V_R = 360 \text{ Vdc}, dI_F/dt = 200 \text{ A}/\mu\text{s}, T_J = 125^\circ\text{C})$	t_{rr}	—	91	—
		t_a	—	28	—
		t_b	—	63	—
Reverse Recovery Stored Charge		Q_{RR}	—	275	μC
INTERNAL PACKAGE INDUCTANCE					
Internal Emitter Inductance (Measured from the emitter lead 0.25" from package to emitter bond pad)	L_E	—	7.5	—	nH

**Figure 1. Output Characteristics****Figure 2. Output Characteristics****Figure 3. Transfer Characteristics****Figure 4. Collector-To-Emitter Saturation Voltage versus Junction Temperature**




Figure 5. Capacitance Variation




Figure 6. Gate-To-Emitter Voltage versus Total Charge




Figure 7. Total Energy Losses versus Gate Resistance




Figure 8. Total Energy Losses versus Junction Temperature




Figure 9. Total Energy Losses versus Collector Current




Figure 10. Turn-Off Losses versus Gate Resistance




Figure 11. Turn-Off Losses versus Junction Temperature




Figure 12. Turn-Off Losses versus Collector Current




Figure 13. Forward Characteristics versus Current





Figure 14. Reverse Biased Safe Operating Area

PACKAGE DIMENSIONS



NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.
3. DIMENSION Z DEFINES A ZONE WHERE ALL BODY AND LEAD IRREGULARITIES ARE ALLOWED.

DIM	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	0.570	0.620	14.48	15.75
B	0.380	0.405	9.66	10.28
C	0.160	0.190	4.07	4.82
D	0.025	0.035	0.64	0.88
F	0.142	0.147	3.61	3.73
G	0.095	0.105	2.42	2.66
H	0.110	0.155	2.80	3.93
J	0.018	0.025	0.46	0.64
K	0.500	0.562	12.70	14.27
L	0.045	0.060	1.15	1.52
N	0.190	0.210	4.83	5.33
Q	0.100	0.120	2.54	3.04
R	0.080	0.110	2.04	2.79
S	0.045	0.055	1.15	1.39
T	0.235	0.255	5.97	6.47
U	0.000	0.050	0.00	1.27
V	0.045	---	1.15	---
Z	---	0.080	---	2.04

CASE 221A-09
TO-220AB
ISSUE Z

STYLE 9:
PIN 1: GATE
2: COLLECTOR
3: EMITTER
4: COLLECTOR

Motorola reserves the right to make changes without further notice to any products herein. Motorola makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Motorola assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation consequential or incidental damages. "Typical" parameters which may be provided in Motorola data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. Motorola does not convey any license under its patent rights nor the rights of others. Motorola products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the Motorola product could create a situation where personal injury or death may occur. Should Buyer purchase or use Motorola products for any such unintended or unauthorized application, Buyer shall indemnify and hold Motorola and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that Motorola was negligent regarding the design or manufacture of the part. Motorola and  are registered trademarks of Motorola, Inc. Motorola, Inc. is an Equal Opportunity/Affirmative Action Employer.

Mfax is a trademark of Motorola, Inc.

How to reach us:

USA/EUROPE/Locations Not Listed: Motorola Literature Distribution;
P.O. Box 5405, Denver, Colorado 80217. 1-303-675-2140 or 1-800-441-2447

JAPAN: Nippon Motorola Ltd.: SPD, Strategic Planning Office, 141,
4-32-1 Nishi-Gotanda, Shagawa-ku, Tokyo, Japan. 03-5487-8488

Customer Focus Center: 1-800-521-6274

Mfax™: RMFAX0@email.sps.mot.com – TOUCHTONE 1-602-244-6609
Motorola Fax Back System – US & Canada ONLY 1-800-774-1848
– http://sps.motorola.com/mfax/

ASIA/PACIFIC: Motorola Semiconductors H.K. Ltd.; 8B Tai Ping Industrial Park,
51 Ting Kok Road, Tai Po, N.T., Hong Kong. 852-26629298

HOME PAGE: <http://motorola.com/sps/>



MOTOROLA