

NTGS3443T1

Power MOSFET 2 Amps, 20 Volts P-Channel TSOP-6

Features

- Ultra Low $R_{DS(on)}$
- Higher Efficiency Extending Battery Life
- Miniature TSOP6 Surface Mount Package

Applications

- Power Management in Portable and Battery-Powered Products, i.e.: Cellular and Cordless Telephones, and PCMCIA Cards

MAXIMUM RATINGS ($T_J = 25^\circ\text{C}$ unless otherwise noted)

Rating	Symbol	Value	Unit
Drain-to-Source Voltage	V_{DS}	-20	Volts
Gate-to-Source Voltage – Continuous	V_{GS}	± 12	Volts
Thermal Resistance Junction-to-Ambient (Note 1.) Total Power Dissipation @ $T_A = 25^\circ\text{C}$ Drain Current – Continuous @ $T_A = 25^\circ\text{C}$ – Pulsed Drain Current ($T_p < 10 \mu\text{s}$)	$R_{\theta JA}$ P_d I_D I_{DM}	244 0.5 -2.2 -10	$^\circ\text{C/W}$ Watts Amps Amps
Thermal Resistance Junction-to-Ambient (Note 2.) Total Power Dissipation @ $T_A = 25^\circ\text{C}$ Drain Current – Continuous @ $T_A = 25^\circ\text{C}$ – Pulsed Drain Current ($T_p < 10 \mu\text{s}$)	$R_{\theta JA}$ P_d I_D I_{DM}	128 1.0 -3.1 -14	$^\circ\text{C/W}$ Watts Amps Amps
Thermal Resistance Junction-to-Ambient (Note 3.) Total Power Dissipation @ $T_A = 25^\circ\text{C}$ Drain Current – Continuous @ $T_A = 25^\circ\text{C}$ – Pulsed Drain Current ($T_p < 10 \mu\text{s}$)	$R_{\theta JA}$ P_d I_D I_{DM}	62.5 2.0 -4.4 -20	$^\circ\text{C/W}$ Watts Amps Amps
Operating and Storage Temperature Range	T_J, T_{stg}	-55 to 150	$^\circ\text{C}$
Maximum Lead Temperature for Soldering Purposes for 10 Seconds	T_L	260	$^\circ\text{C}$

1. Minimum FR-4 or G-10PCB, operating to steady state.
2. Mounted onto a 2" square FR-4 board (1" sq. 2 oz. cu. 0.06" thick single sided), operating to steady state.
3. Mounted onto a 2" square FR-4 board (1" sq. 2 oz. cu. 0.06" thick single sided), $t < 5.0$ seconds.




ON Semiconductor™


<http://onsemi.com>

**2 AMPERES
20 VOLTS
 $R_{DS(on)} = 65 \text{ m}\Omega$**


P-Channel



MARKING DIAGRAM




**TSOP-6
CASE 318G
STYLE 1**



W = Work Week

PIN ASSIGNMENT



ORDERING INFORMATION

Device	Package	Shipping
NTGS3443T1	TSOP-6	3000 Tape & Reel

NTGS3443T1

ELECTRICAL CHARACTERISTICS (T_A = 25°C unless otherwise noted)*

Characteristic	Symbol	Min	Typ	Max	Unit
----------------	--------	-----	-----	-----	------

OFF CHARACTERISTICS

Drain–Source Breakdown Voltage (V _{GS} = 0 Vdc, I _D = –10 µA)	V _{(BR)DSS}	–20	–	–	Vdc
Zero Gate Voltage Drain Current (V _{GS} = 0 Vdc, V _{DS} = –20 Vdc, T _J = 25°C) (V _{GS} = 0 Vdc, V _{DS} = –20 Vdc, T _J = 70°C)	I _{DSS}	– –	– –	–1.0 –5.0	µAdc
Gate–Body Leakage Current (V _{GS} = –12 Vdc, V _{DS} = 0 Vdc)	I _{GSS}	–	–	–100	nAdc
Gate–Body Leakage Current (V _{GS} = +12 Vdc, V _{DS} = 0 Vdc)	I _{GSS}	–	–	100	nAdc

ON CHARACTERISTICS

Gate Threshold Voltage (V _{DS} = V _{GS} , I _D = –250 µAdc)	V _{GS(th)}	–0.60	–0.95	–1.50	Vdc
Static Drain–Source On–State Resistance (V _{GS} = –4.5 Vdc, I _D = –4.4 Adc) (V _{GS} = –2.7 Vdc, I _D = –3.7 Adc) (V _{GS} = –2.5 Vdc, I _D = –3.5 Adc)	R _{DS(on)}	– – –	0.058 0.082 0.092	0.065 0.090 0.100	Ω
Forward Transconductance (V _{DS} = –10 Vdc, I _D = –4.4 Adc)	g _{FS}	–	8.8	–	mhos

DYNAMIC CHARACTERISTICS

Input Capacitance	(V _{DS} = –5.0 Vdc, V _{GS} = 0 Vdc, f = 1.0 MHz)	C _{iss}	–	565	–	pF
Output Capacitance		C _{oss}	–	320	–	pF
Reverse Transfer Capacitance		C _{rss}	–	120	–	pF

SWITCHING CHARACTERISTICS

Turn–On Delay Time	(V _{DD} = –20 Vdc, I _D = –1.0 Adc, V _{GS} = –4.5 Vdc, R _g = 6.0 Ω)	t _{d(on)}	–	10	25	ns
Rise Time		t _r	–	18	45	ns
Turn–Off Delay Time		t _{d(off)}	–	30	50	ns
Fall Time		t _f	–	31	50	ns
Total Gate Charge	(V _{DS} = –10 Vdc, V _{GS} = –4.5 Vdc, I _D = –4.4 Adc)	Q _{tot}	–	7.5	15	nC
Gate–Source Charge		Q _{gs}	–	1.4	–	nC
Gate–Drain Charge		Q _{gd}	–	2.9	–	nC

BODY–DRAIN DIODE RATINGS

Diode Forward On–Voltage	(I _S = –1.7 Adc, V _{GS} = 0 Vdc)	V _{SD}	–	–0.83	–1.2	Vdc
Reverse Recovery Time	(I _S = –1.7 Adc, dI _S /dt = 100 A/µs)	t _{rr}	–	30	–	ns

*Indicates Pulse Test: P.W. = 300 µsec max, Duty Cycle = 2%.

*Handling precautions to protect against electrostatic discharge is mandatory.

TYPICAL ELECTRICAL CHARACTERISTICS




Figure 1. On-Region Characteristics




Figure 2. Transfer Characteristics




Figure 3. On-Resistance vs. Gate-to-Source Voltage




Figure 4. On-Resistance vs. Drain Current and Gate Voltage




Figure 5. On-Resistance Variation with Temperature




Figure 6. Drain-to-Source Leakage Current vs. Voltage

TYPICAL ELECTRICAL CHARACTERISTICS




Figure 7. Capacitance Variation




Figure 8. Gate-to-Source and Drain-to-Source Voltage vs. Total Charge




Figure 9. Gate Threshold Voltage Variation with Temperature




Figure 10. Diode Forward Voltage vs. Current

NTGS3443T1

TYPICAL ELECTRICAL CHARACTERISTICS




Figure 11. Single Pulse Power





Figure 12. Normalized Thermal Transient Impedance, Junction-to-Ambient

INFORMATION FOR USING THE TSOP-6 SURFACE MOUNT PACKAGE

MINIMUM RECOMMENDED FOOTPRINT FOR SURFACE MOUNTED APPLICATIONS

Surface mount board layout is a critical portion of the total design. The footprint for the semiconductor packages must be the correct size to insure proper solder connection

interface between the board and the package. With the correct pad geometry, the packages will self align when subjected to a solder reflow process.



SOLDERING PRECAUTIONS

The melting temperature of solder is higher than the rated temperature of the device. When the entire device is heated to a high temperature, failure to complete soldering within a short time could result in device failure. Therefore, the following items should always be observed in order to minimize the thermal stress to which the devices are subjected.

- Always preheat the device.
- The delta temperature between the preheat and soldering should be 100°C or less.*
- When preheating and soldering, the temperature of the leads and the case must not exceed the maximum temperature ratings as shown on the data sheet. When using infrared heating with the reflow soldering method, the difference shall be a maximum of 10°C.


- The soldering temperature and time shall not exceed 260°C for more than 10 seconds.
- When shifting from preheating to soldering, the maximum temperature gradient shall be 5°C or less.
- After soldering has been completed, the device should be allowed to cool naturally for at least three minutes. Gradual cooling should be used as the use of forced cooling will increase the temperature gradient and result in latent failure due to mechanical stress.
- Mechanical stress or shock should not be applied during cooling.

* Soldering a device without preheating can cause excessive thermal shock and stress which can result in damage to the device.

NTGS3443T1

PACKAGE DIMENSIONS

TSOP-6
CASE 318G-02
ISSUE G



NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: MILLIMETER.
3. MAXIMUM LEAD THICKNESS INCLUDES LEAD FINISH THICKNESS. MINIMUM LEAD THICKNESS IS THE MINIMUM THICKNESS OF BASE MATERIAL.

DIM	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	2.90	3.10	0.1142	0.1220
B	1.30	1.70	0.0512	0.0669
C	0.90	1.10	0.0354	0.0433
D	0.25	0.50	0.0098	0.0197
G	0.85	1.05	0.0335	0.0413
H	0.013	0.100	0.0005	0.0040
J	0.10	0.26	0.0040	0.0102
K	0.20	0.60	0.0079	0.0236
L	1.25	1.55	0.0493	0.0610
M	0°	10°	0°	10°
S	2.50	3.00	0.0985	0.1181

STYLE 1:

- PIN 1: DRAIN
2: DRAIN
3: GATE
4: SOURCE
5: DRAIN
6: DRAIN

ON Semiconductor and  are trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer.

PUBLICATION ORDERING INFORMATION

NORTH AMERICA Literature Fulfillment:

Literature Distribution Center for ON Semiconductor
P.O. Box 5163, Denver, Colorado 80217 USA
Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada
Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada
Email: ONlit@hibbertco.com
Fax Response Line: 303-675-2167 or 800-344-3810 Toll Free USA/Canada

N. American Technical Support: 800-282-9855 Toll Free USA/Canada

EUROPE: LDC for ON Semiconductor – European Support

German Phone: (+1) 303-308-7140 (Mon-Fri 2:30pm to 7:00pm CET)
Email: ONlit-german@hibbertco.com
French Phone: (+1) 303-308-7141 (Mon-Fri 2:00pm to 7:00pm CET)
Email: ONlit-french@hibbertco.com
English Phone: (+1) 303-308-7142 (Mon-Fri 12:00pm to 5:00pm GMT)
Email: ONlit@hibbertco.com

EUROPEAN TOLL-FREE ACCESS*: 00-800-4422-3781

*Available from Germany, France, Italy, UK, Ireland

CENTRAL/SOUTH AMERICA:

Spanish Phone: 303-308-7143 (Mon-Fri 8:00am to 5:00pm MST)
Email: ONlit-spanish@hibbertco.com
Toll-Free from Mexico: Dial 01-800-288-2872 for Access –
then Dial 866-297-9322

ASIA/PACIFIC: LDC for ON Semiconductor – Asia Support

Phone: 303-675-2121 (Tue-Fri 9:00am to 1:00pm, Hong Kong Time)
Toll Free from Hong Kong & Singapore:
001-800-4422-3781
Email: ONlit-asia@hibbertco.com

JAPAN: ON Semiconductor, Japan Customer Focus Center

4-32-1 Nishi-Gotanda, Shinagawa-ku, Tokyo, Japan 141-0031
Phone: 81-3-5740-2700
Email: r14525@onsemi.com

ON Semiconductor Website: <http://onsemi.com>

For additional information, please contact your local Sales Representative.