


# 4-Bit AND/OR Selector or Quad 2-Channel Data Selector or Quad Exclusive "NOR" Gate

The MC14519B is constructed with MOS P-channel and N-channel enhancement mode devices in a monolithic structure. These complementary MOS logic gates find primary use where low power dissipation and/or high noise immunity is desired.


This device provides three functions in one package; a 4-Bit AND/OR Selector, a Quad 2-Channel Data Selector, or a Quad Exclusive NOR Gate.

- Diode Protection on All Inputs
- Supply Voltage Range = 3.0 Vdc to 18 Vdc
- Capable of Driving Two Low-power TTL Loads or One Low-power Schottky TTL Load Over the Rated Temperature Range
- Plug-in Replacement for CD4019 in Most Applications


LOGIC DIAGRAM




## MC14519B



**L SUFFIX**  
CERAMIC  
CASE 620



**P SUFFIX**  
PLASTIC  
CASE 648



**D SUFFIX**  
SOIC  
CASE 751B

### ORDERING INFORMATION

|            |         |
|------------|---------|
| MC14XXXBCP | Plastic |
| MC14XXXBCL | Ceramic |
| MC14XXXBD  | SOIC    |

$T_A = -55^\circ$  to  $125^\circ\text{C}$  for all packages.

TRUTH TABLE

| Control Inputs |   | Output<br>$Z_n$ |
|----------------|---|-----------------|
| A              | B |                 |
| 0              | 0 | 0               |
| 0              | 1 | $Y_n$           |
| 1              | 0 | $X_n$           |
| 1              | 1 | $X_n \odot Y_n$ |

NOTE:  $X_n \odot Y_n$  means  $X_n$   
(Exclusive-NOR)  $Y_n$

**MAXIMUM RATINGS\*** (Voltages Referenced to V<sub>SS</sub>)

| Symbol                             | Parameter                                          | Value                          | Unit |
|------------------------------------|----------------------------------------------------|--------------------------------|------|
| V <sub>DD</sub>                    | DC Supply Voltage                                  | – 0.5 to + 18.0                | V    |
| V <sub>in</sub> , V <sub>out</sub> | Input or Output Voltage (DC or Transient)          | – 0.5 to V <sub>DD</sub> + 0.5 | V    |
| I <sub>in</sub> , I <sub>out</sub> | Input or Output Current (DC or Transient), per Pin | ± 10                           | mA   |
| P <sub>D</sub>                     | Power Dissipation, per Package†                    | 500                            | mW   |
| T <sub>stg</sub>                   | Storage Temperature                                | – 65 to + 150                  | °C   |
| T <sub>L</sub>                     | Lead Temperature (8–Second Soldering)              | 260                            | °C   |

\* Maximum Ratings are those values beyond which damage to the device may occur.

† Temperature Derating:

Plastic “P and D/DW” Packages: – 7.0 mW/°C From 65°C To 125°C

Ceramic “L” Packages: – 12 mW/°C From 100°C To 125°C

**PIN ASSIGNMENT**

|                 |   |    |                 |
|-----------------|---|----|-----------------|
| Y3              | 1 | 16 | V <sub>DD</sub> |
| X2              | 2 | 15 | X3              |
| Y2              | 3 | 14 | B               |
| X1              | 4 | 13 | Z3              |
| Y1              | 5 | 12 | Z2              |
| X0              | 6 | 11 | Z1              |
| Y0              | 7 | 10 | Z0              |
| V <sub>SS</sub> | 8 | 9  | A               |

**ELECTRICAL CHARACTERISTICS** (Voltages Referenced to V<sub>SS</sub>)

| Characteristic                                                                                                                                                                                                                                                              | Symbol                    | V <sub>DD</sub><br>Vdc | – 55°C                                                                                                                                                      |       | 25°C   |           |       | 125°C  |       | Unit |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------|------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------|-------|--------|-----------|-------|--------|-------|------|
|                                                                                                                                                                                                                                                                             |                           |                        | Min                                                                                                                                                         | Max   | Min    | Typ #     | Max   | Min    | Max   |      |
| Output Voltage<br>“0” Level<br>V <sub>in</sub> = V <sub>DD</sub> or 0<br><br>“1” Level<br>V <sub>in</sub> = 0 or V <sub>DD</sub>                                                                                                                                            | V <sub>OL</sub>           | 5.0                    | —                                                                                                                                                           | 0.05  | —      | 0         | 0.05  | —      | 0.05  | Vdc  |
|                                                                                                                                                                                                                                                                             |                           | 10                     | —                                                                                                                                                           | 0.05  | —      | 0         | 0.05  | —      | 0.05  |      |
|                                                                                                                                                                                                                                                                             |                           | 15                     | —                                                                                                                                                           | 0.05  | —      | 0         | 0.05  | —      | 0.05  |      |
|                                                                                                                                                                                                                                                                             | V <sub>OH</sub>           | 5.0                    | 4.95                                                                                                                                                        | —     | 4.95   | 5.0       | —     | 4.95   | —     | Vdc  |
|                                                                                                                                                                                                                                                                             |                           | 10                     | 9.95                                                                                                                                                        | —     | 9.95   | 10        | —     | 9.95   | —     |      |
|                                                                                                                                                                                                                                                                             |                           | 15                     | 14.95                                                                                                                                                       | —     | 14.95  | 15        | —     | 14.95  | —     |      |
| Input Voltage<br>“0” Level<br>(V <sub>O</sub> = 4.5 or 0.5 Vdc)<br>(V <sub>O</sub> = 9.0 or 1.0 Vdc)<br>(V <sub>O</sub> = 13.5 or 1.5 Vdc)<br><br>“1” Level<br>(V <sub>O</sub> = 0.5 or 4.5 Vdc)<br>(V <sub>O</sub> = 1.0 or 9.0 Vdc)<br>(V <sub>O</sub> = 1.5 or 13.5 Vdc) | V <sub>IL</sub>           | 5.0                    | —                                                                                                                                                           | 1.5   | —      | 2.25      | 1.5   | —      | 1.5   | Vdc  |
|                                                                                                                                                                                                                                                                             |                           | 10                     | —                                                                                                                                                           | 3.0   | —      | 4.50      | 3.0   | —      | 3.0   |      |
|                                                                                                                                                                                                                                                                             |                           | 15                     | —                                                                                                                                                           | 4.0   | —      | 6.75      | 4.0   | —      | 4.0   |      |
|                                                                                                                                                                                                                                                                             | V <sub>IH</sub>           | 5.0                    | 3.5                                                                                                                                                         | —     | 3.5    | 2.75      | —     | 3.5    | —     | Vdc  |
|                                                                                                                                                                                                                                                                             |                           | 10                     | 7.0                                                                                                                                                         | —     | 7.0    | 5.50      | —     | 7.0    | —     |      |
|                                                                                                                                                                                                                                                                             |                           | 15                     | 11                                                                                                                                                          | —     | 11     | 8.25      | —     | 11     | —     |      |
| Output Drive Current<br>(V <sub>OH</sub> = 2.5 Vdc)<br>(V <sub>OH</sub> = 4.6 Vdc)<br>(V <sub>OH</sub> = 9.5 Vdc)<br>(V <sub>OH</sub> = 13.5 Vdc)<br><br>(V <sub>OL</sub> = 0.4 Vdc)<br>(V <sub>OL</sub> = 0.5 Vdc)<br>(V <sub>OL</sub> = 1.5 Vdc)                          | Source<br>I <sub>OH</sub> | 5.0                    | – 3.0                                                                                                                                                       | —     | – 2.4  | – 4.2     | —     | – 1.7  | —     | mAdc |
|                                                                                                                                                                                                                                                                             |                           | 5.0                    | – 0.64                                                                                                                                                      | —     | – 0.51 | – 0.88    | —     | – 0.36 | —     |      |
|                                                                                                                                                                                                                                                                             |                           | 10                     | – 1.6                                                                                                                                                       | —     | – 1.3  | – 2.25    | —     | – 0.9  | —     |      |
|                                                                                                                                                                                                                                                                             |                           | 15                     | – 4.2                                                                                                                                                       | —     | – 3.4  | – 8.8     | —     | – 2.4  | —     |      |
|                                                                                                                                                                                                                                                                             | Sink<br>I <sub>OL</sub>   | 5.0                    | 0.64                                                                                                                                                        | —     | 0.51   | 0.88      | —     | 0.36   | —     | mAdc |
|                                                                                                                                                                                                                                                                             |                           | 10                     | 1.6                                                                                                                                                         | —     | 1.3    | 2.25      | —     | 0.9    | —     |      |
|                                                                                                                                                                                                                                                                             |                           | 15                     | 4.2                                                                                                                                                         | —     | 3.4    | 8.8       | —     | 2.4    | —     |      |
| Input Current                                                                                                                                                                                                                                                               | I <sub>in</sub>           | 15                     | —                                                                                                                                                           | ± 0.1 | —      | ± 0.00001 | ± 0.1 | —      | ± 1.0 | μAdc |
| Input Capacitance<br>(V <sub>in</sub> = 0)                                                                                                                                                                                                                                  | C <sub>in</sub>           | —                      | —                                                                                                                                                           | —     | —      | 5.0       | 7.5   | —      | —     | pF   |
| Quiescent Current<br>(Per Package)                                                                                                                                                                                                                                          | I <sub>DD</sub>           | 5.0                    | —                                                                                                                                                           | 5.0   | —      | 0.005     | 5.0   | —      | 150   | μAdc |
|                                                                                                                                                                                                                                                                             |                           | 10                     | —                                                                                                                                                           | 10    | —      | 0.010     | 10    | —      | 300   |      |
|                                                                                                                                                                                                                                                                             |                           | 15                     | —                                                                                                                                                           | 20    | —      | 0.015     | 20    | —      | 600   |      |
| Total Supply Current***†<br>(Dynamic plus Quiescent,<br>Per Package)<br>(C <sub>L</sub> = 50 pF on all outputs, all<br>buffers switching)                                                                                                                                   | I <sub>T</sub>            | 5.0<br>10<br>15        | I <sub>T</sub> = (1.2 μA/kHz) f + I <sub>DD</sub><br>I <sub>T</sub> = (2.4 μA/kHz) f + I <sub>DD</sub><br>I <sub>T</sub> = (3.6 μA/kHz) f + I <sub>DD</sub> |       |        |           |       |        |       | μAdc |

#Data labelled “Typ” is not to be used for design purposes but is intended as an indication of the IC’s potential performance.

\*\*The formulas given are for the typical characteristics only at 25°C.

†To calculate total supply current at loads other than 50 pF:

$$I_T(C_L) = I_T(50 \text{ pF}) + (C_L - 50) V_{fk}$$


where: I<sub>T</sub> is in μA (per package), C<sub>L</sub> in pF, V = (V<sub>DD</sub> – V<sub>SS</sub>) in volts, f in kHz is input frequency, and k = 0.004.

**SWITCHING CHARACTERISTICS\*** ( $C_L = 50 \text{ pF}$ ,  $T_A = 25^\circ\text{C}$ )


| Characteristic                                                                                                                                                                                                                 | Symbol             | $V_{DD}$        | Min         | Typ #            | Max               | Unit |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------|-----------------|-------------|------------------|-------------------|------|
| Output Rise and Fall Time<br>$t_{TLH}, t_{THL} = (1.5 \text{ ns/pF}) C_L + 25 \text{ ns}$<br>$t_{TLH}, t_{THL} = (0.75 \text{ ns/pF}) C_L + 12.5 \text{ ns}$<br>$t_{TLH}, t_{THL} = (0.55 \text{ ns/pF}) C_L + 9.5 \text{ ns}$ | $t_{TLH}, t_{THL}$ | 5.0<br>10<br>15 | —<br>—<br>— | 100<br>50<br>40  | 200<br>100<br>80  | ns   |
| Propagation Delay Time<br>$t_{PLH}, t_{PHL} = (1.7 \text{ ns/pF}) C_L + 165 \text{ ns}$<br>$t_{PLH}, t_{PHL} = (0.66 \text{ ns/pF}) C_L + 82$<br>$t_{PLH}, t_{PHL} = (0.5 \text{ ns/pF}) C_L + 65 \text{ ns}$                  | $t_{PLH}, t_{PHL}$ | 5.0<br>10<br>15 | —<br>—<br>— | 250<br>115<br>90 | 500<br>225<br>165 | ns   |

\* The formulas given are for the typical characteristics only at  $25^\circ\text{C}$ .

#Data labelled "Typ" is not to be used for design purposes but is intended as an indication of the IC's potential performance.




**Figure 1. Dynamic Power Dissipation Test Circuit and Waveform**



**Figure 2. Switching Time Test Circuit and Waveforms**

## TYPICAL CIRCUIT APPLICATIONS

### DATA REGISTER SELECTION COMPARISON



CONVERSION TABLE


| Operation Code |   |     | Output          |                 |                 |                 | Function             |
|----------------|---|-----|-----------------|-----------------|-----------------|-----------------|----------------------|
| A              | B | INV | Q0              | Q1              | Q2              | Q3              |                      |
| 0              | 0 | 0   | 0               | 0               | 0               | 0               | Inhibit, all zeros   |
| 0              | 0 | 1   | 1               | 1               | 1               | 1               | Inhibit, all ones    |
| 1              | 0 | 0   | X0              | X1              | X2              | X3              | Control A            |
| 1              | 0 | 1   | $\overline{X0}$ | $\overline{X1}$ | $\overline{X2}$ | $\overline{X3}$ | Control A and Invert |
| 0              | 1 | 0   | Y0              | Y1              | Y2              | Y3              | Control B            |
| 0              | 1 | 1   | $\overline{Y0}$ | $\overline{Y1}$ | $\overline{Y2}$ | $\overline{Y3}$ | Control B and Invert |
| 1              | 1 | 0   | $X0 \odot Y0$   | $X1 \odot Y1$   | $X2 \odot Y2$   | $X3 \odot Y3$   | Exclusive NOR        |
| 1              | 1 | 1   | $X0 \oplus Y0$  | $X1 \oplus Y1$  | $X2 \oplus Y2$  | $X3 \oplus Y3$  | Exclusive OR         |

This device contains protection circuitry to guard against damage due to high static voltages or electric fields. However, precautions must be taken to avoid applications of any voltage higher than maximum rated voltages to this high-impedance circuit. For proper operation,  $V_{IN}$  and  $V_{OUT}$  should be constrained to the range  $V_{SS} \leq (V_{IN} \text{ or } V_{OUT}) \leq V_{DD}$ .

Unused inputs must always be tied to an appropriate logic voltage level (e.g., either  $V_{SS}$  or  $V_{DD}$ ). Unused outputs must be left open.

## OUTLINE DIMENSIONS

### L SUFFIX CERAMIC DIP PACKAGE CASE 620-10 ISSUE V




#### NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.
3. DIMENSION L TO CENTER OF LEAD WHEN FORMED PARALLEL.
4. DIMENSION F MAY NARROW TO 0.76 (0.030) WHERE THE LEAD ENTERS THE CERAMIC BODY.

| DIM | INCHES |       | MILLIMETERS |       |
|-----|--------|-------|-------------|-------|
|     | MIN    | MAX   | MIN         | MAX   |
| A   | 0.750  | 0.785 | 19.05       | 19.93 |
| B   | 0.240  | 0.295 | 6.10        | 7.49  |
| C   | —      | 0.200 | —           | 5.08  |
| D   | 0.015  | 0.020 | 0.39        | 0.50  |
| E   | 0.050  | BSC   | 1.27        | BSC   |
| F   | 0.055  | 0.065 | 1.40        | 1.65  |
| G   | 0.100  | BSC   | 2.54        | BSC   |
| H   | 0.008  | 0.015 | 0.21        | 0.38  |
| K   | 0.125  | 0.170 | 3.18        | 4.31  |
| L   | 0.300  | BSC   | 7.62        | BSC   |
| M   | 0°     | 15°   | 0°          | 15°   |
| N   | 0.020  | 0.040 | 0.51        | 1.01  |

### P SUFFIX PLASTIC DIP PACKAGE CASE 648-08 ISSUE R




#### NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.
3. DIMENSION L TO CENTER OF LEADS WHEN FORMED PARALLEL.
4. DIMENSION B DOES NOT INCLUDE MOLD FLASH.
5. ROUNDED CORNERS OPTIONAL.

| DIM | INCHES |       | MILLIMETERS |       |
|-----|--------|-------|-------------|-------|
|     | MIN    | MAX   | MIN         | MAX   |
| A   | 0.740  | 0.770 | 18.80       | 19.55 |
| B   | 0.250  | 0.270 | 6.35        | 6.85  |
| C   | 0.145  | 0.175 | 3.69        | 4.44  |
| D   | 0.015  | 0.021 | 0.39        | 0.53  |
| F   | 0.040  | 0.70  | 1.02        | 1.77  |
| G   | 0.100  | BSC   | 2.54        | BSC   |
| H   | 0.050  | BSC   | 1.27        | BSC   |
| J   | 0.008  | 0.015 | 0.21        | 0.38  |
| K   | 0.110  | 0.130 | 2.80        | 3.30  |
| L   | 0.295  | 0.305 | 7.50        | 7.74  |
| M   | 0°     | 10°   | 0°          | 10°   |
| S   | 0.020  | 0.040 | 0.51        | 1.01  |

## OUTLINE DIMENSIONS

### D SUFFIX PLASTIC SOIC PACKAGE CASE 751B-05 ISSUE J



Motorola reserves the right to make changes without further notice to any products herein. Motorola makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Motorola assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation consequential or incidental damages. "Typical" parameters which may be provided in Motorola data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. Motorola does not convey any license under its patent rights nor the rights of others. Motorola products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the Motorola product could create a situation where personal injury or death may occur. Should Buyer purchase or use Motorola products for any such unintended or unauthorized application, Buyer shall indemnify and hold Motorola and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that Motorola was negligent regarding the design or manufacture of the part. Motorola and  are registered trademarks of Motorola, Inc. Motorola, Inc. is an Equal Opportunity/Affirmative Action Employer.

#### How to reach us:

**USA/EUROPE/Locations Not Listed:** Motorola Literature Distribution;  
P.O. Box 20912; Phoenix, Arizona 85036. 1-800-441-2447 or 602-303-5454

**MFAX:** RMFAX0@email.sps.mot.com – TOUCHTONE 602-244-6609  
**INTERNET:** <http://Design-NET.com>

**JAPAN:** Nippon Motorola Ltd.; Tatsumi-SPD-JLDC, 6F Seibu-Butsuryu-Center,  
3-14-2 Tatsumi Koto-Ku, Tokyo 135, Japan. 03-81-3521-8315

**ASIA/PACIFIC:** Motorola Semiconductors H.K. Ltd.; 8B Tai Ping Industrial Park,  
51 Ting Kok Road, Tai Po, N.T., Hong Kong. 852-26629298



**MOTOROLA**

MC14519B/D

