

MN54AC540-X REV 1B0

 Original Creation Date: 07/01/96
 Last Update Date: 03/31/97
 Last Major Revision Date: 07/01/96

Octal Buffers/Line Drivers With TRI -State Outputs

General Description

The AC540 is similar in function to the AC240, except that the inputs and outputs are on opposite sides of the package (see Connection Diagrams). This pinout arrangement makes this device especially useful as an output port formicroprocessors, allowing ease of layout and greater PC board density.

The AC540 is an octal buffer/line driver designed to be employed as a memoryand address driver, clock driver and bus oriented transmitter/receiver.

Industry Part Number

54AC540

NS Part Numbers

 54AC540DMQB
 54AC540FMQB
 54AC540LMQB

Prime Die

Z540

Processing

MIL-STD-883, Method 5004

Quality Conformance Inspection

MIL-STD-883 5005

Subgrp	Description	Temp (°C)
1	Static tests at	+25
2	Static tests at	+125
3	Static tests at	-55
4	Dynamic tests at	+25
5	Dynamic tests at	+125
6	Dynamic tests at	-55
7	Functional tests at	+25
8A	Functional tests at	+125
8B	Functional tests at	-55
9	Switching tests at	+25
10	Switching tests at	+125
11	Switching tests at	-55

Features

- I_{cc} and I_{oz} reduced by 50%
- TRI-STATE inverting outputs
- Inputs and outputs opposite side of package, allowing easier interface to microprocessors
- Output source/sink 24mA
- Standard Military Drawing 54AC540: 5962-8769501

(Absolute Maximum Ratings)

(Note 1)

Supply Voltage (Vcc)	-0.5V to +7.0V
DC Input Diode Current (Iik)	
Vi = -0.5V	-20 mA
Vi = Vcc +0.5V	+20 mA
DC Input Voltage (Vi)	-0.5V to Vcc + 0.5V
DC Output Diode Current (Iok)	
Vo = -0.5V	-20 mA
Vo = Vcc +0.5	+20 mA
DC Output Voltage (Vo)	-0.5V to Vcc +0.5V
DC Output Source or Sink Current (Io)	±50 mA
DC Vcc or Ground Current per Output Pin (Icc or Ignd)	±50 mA
Storage Temperature (Tstg)	-65 C to +150 C
Junction Temperature (Tj)	
CDIP	175 C

Note 1: Absolute maximum ratings are those values beyond which damage to the device may occur. The databook specifications should be met, without exception, to ensure that the system design is reliable over its power supply, temperature, and output/input loading variables. National does not recommend operation of FACT TM circuits outside databook specifications.

Recommended Operating Conditions

Supply Voltage (Vcc)	2.0V to 6.0V
Input Voltage (Vi)	0V to Vcc
Output Voltage (Vo)	0V to Vcc
Operating Temperature (Ta)	-55 C to +125 C
Minimum Input Edge Rate (Delta v/Delta t)	
AC devices	
Vin from 30% to 70% of Vcc	
Vcc @ 3.0V, 4.5V, 5.5V	125mV/ns

Electrical Characteristics

DC PARAMETERS

(The following conditions apply to all the following parameters, unless otherwise specified.)

DC: VCC 3.0V to 5.5V, Temp. Range: -55C to 125C. NOTE: -55C TEMPERATURE, SUBGROUP 3 IS GUARANTEED BUT NOT TESTED.

SYMBOL	PARAMETER	CONDITIONS	NOTES	PIN-NAME	MIN	MAX	UNIT	SUB-GROUPS
IIH	High Level Input Current	VCC=5.5V, VM=5.5V	1, 2	INPUTS		0.1	uA	1
			1, 2	INPUTS		1.0	uA	2, 3
IIL	Low Level Input Current	VCC=5.5V, VM=0.0V	1, 2	INPUTS		-0.1	uA	1
			1, 2	INPUTS		-1.0	uA	2, 3
VOL	Low Level Output Voltage	VCC=3.0V, VIH=2.1V, VIL=0.9V, IOL=50.0uA	1, 2	OUTPUTS		.10	V	1, 2, 3
		VCC=4.5V, VIH=3.15V, VIL=1.35V, IOL=50.0uA	1, 2	OUTPUTS		.10	V	1, 2, 3
		VCC=5.5V, VIH=3.85V, VIL=1.65V, IOL=50.0uA	1, 2	OUTPUTS		.10	V	1, 2, 3
		VCC=3.0V, VIH=2.1V, VIL=0.9V, IOL=12.0mA	1, 2	OUTPUTS		.50	V	2, 3
		VCC=3.0V, VIH=2.1V, VIL=0.9V, IOL=12.0mA	1, 2	OUTPUTS		.36	V	1
			1, 2	OUTPUTS		.50	V	2, 3
		VCC=4.5V, VIH=3.15V, VIL=1.35V, IOL=24.0mA	1, 2	OUTPUTS		.36	V	1
		VCC=5.5V, VIH=3.85V, VIL=1.65V, IOL=24.0mA	1, 2	OUTPUTS		.50	V	2, 3
VIOL	Dynamic Output Current LOW	VCC=5.5V, VIH=3.85, VIL=1.65V, IOL=50.0mA	1, 2, 5	OUTPUTS		1.65	V	1, 2, 3
			1, 2	OUTPUTS	2.90		V	1, 2, 3
VOH	High Level Output Voltage	VCC=3.0V, VIL=0.9V, IOH=-50.0uA	1, 2	OUTPUTS	2.90		V	1, 2, 3
		VCC=4.5V, VIL=1.35V, IOH=-50.0uA	1, 2	OUTPUTS	4.40		V	1, 2, 3
		VCC=5.5V, VIL=1.65V, IOH=-50.0uA	1, 2	OUTPUTS	5.40		V	1, 2, 3
		VCC=3.0V, VIL=0.9V, IOH=-12.0mA	1, 2	OUTPUTS	2.40		V	2, 3
		VCC=3.0V, VIL=0.9V, IOH=-12.0mA	1, 2	OUTPUTS	2.56		V	1
			1, 2	OUTPUTS	3.70		V	2, 3
		VCC=4.5V, VIL=1.35V, IOH=-24.0mA	1, 2	OUTPUTS	3.86		V	1
		VCC=5.5V, VIL=1.65V, IOH=-24.0mA	1, 2	OUTPUTS	4.70		V	2, 3
VIOH	Dynamic Output Current HIGH	VCC=5.5V, VIL=1.65V, IOH=-50.0mA	1, 2, 5	OUTPUTS	3.85		V	1, 2, 3
			1, 2	OUTPUTS	4.86		V	1

Electrical Characteristics

DC PARAMETERS(Continued)

(The following conditions apply to all the following parameters, unless otherwise specified.)

DC: VCC 3.0V to 5.5V, Temp. Range: -55C to 125C. NOTE: -55C TEMPERATURE, SUBGROUP 3 IS GUARANTEED BUT NOT TESTED.

SYMBOL	PARAMETER	CONDITIONS	NOTES	PIN-NAME	MIN	MAX	UNIT	SUB-GROUPS
IOZH	Maximum TRI-STATE Current	VCC=3.0V, VM=3.0V, VINH=3.0V, VIH=2.1V	1, 2	OUTPUTS		5.00	uA	2, 3
			1, 2	OUTPUTS		0.25	uA	1
		VCC=4.5V, VM=4.5V, VINH=4.5V, VIH=3.15V	1, 2	OUTPUTS		5.00	uA	2, 3
			1, 2	OUTPUTS		0.25	uA	1
		VCC=5.5V, VM=5.5V, VINH=5.5V, VIH=3.85V	1, 2	OUTPUTS		5.00	uA	2, 3
			1, 2	OUTPUTS		0.25	uA	1
IOZL	Maximum TRI-STATE Current	VCC=3.0V, VM=0.0V, VINL=0.0V, VIH=2.1V	1, 2	OUTPUTS		-5.00	uA	2, 3
			1, 2	OUTPUTS		-0.25	uA	1
		VCC=4.5V, VM=0.0V, VINL=0.0V, VIH=3.15V	1, 2	OUTPUTS		-5.00	uA	2, 3
			1, 2	OUTPUTS		-0.25	uA	1
		VCC=5.5V, VM=0.0V, VINL=0.0V, VIH=3.85V	1, 2	OUTPUTS		-5.00	uA	2, 3
			1, 2	OUTPUTS		-0.25	uA	1
ICCH	Supply Current Outputs HIGH	VCC=5.5V, VINL=0.0V	1, 2	VCC		4.0	uA	1
			1, 2	VCC		80	uA	2, 3
ICCL	Supply Current Outputs LOW	VCC=5.5V, VINH=5.5V, VINL=0.0V	1, 2	VCC		4.0	uA	1
			1, 2	VCC		80	uA	2, 3
ICCZ	Supply Current Outputs Tri-State	VCC=5.5V, VINH=5.5V, VINL=0.0V	1, 2	VCC		4.0	uA	1
			1, 2	VCC		80	uA	2, 3

AC PARAMETERS

(The following conditions apply to all the following parameters, unless otherwise specified.)

AC: CL=50pf, RL=500 OHMS, TR=3.0ns, TF=3.0ns, Temp Range: -55C to 125C. NOTE: -55C TEMPERATURE, SUBGROUP 11 IS GUARANTEED BUT NOT TESTED.

tpLH(1)	Propagation Delay	VCC=4.5V	3, 4, 7	In to On	1.5	6.0	ns	9
			3, 4, 7	In to On	1.5	7.0	ns	10, 11
tpHL(1)	Propagation Delay	VCC=4.5V	3, 4, 7	In to On	1.5	5.5	ns	9
			3, 4, 7	In to On	1.5	6.5	ns	10, 11

Electrical Characteristics

AC PARAMETERS(Continued)

(The following conditions apply to all the following parameters, unless otherwise specified.)

AC: CL=50pf, RL=500 OHMS, TR=3.0ns, TF=3.0ns, Temp Range: -55C to 125C. NOTE: -55C TEMPERATURE, SUBGROUP 11 IS GUARANTEED BUT NOT TESTED.

SYMBOL	PARAMETER	CONDITIONS	NOTES	PIN-NAME	MIN	MAX	UNIT	SUB-GROUPS
tpZL(1)	Output Enable Time	VCC=4.5V	3, 4, 7	OE to On	1.5	7.5	ns	9
			3, 4, 7	OE to On	1.5	9.0	ns	10, 11
tpZH(1)	Output Enable Time	VCC=4.5V	3, 4, 7	OE to On	1.5	8.5	ns	9
			3, 4, 7	OE to On	1.5	10.0	ns	10, 11
tpHZ(1)	Output Disable Time	VCC=4.5V	3, 4, 7	OE to On	1.5	10.5	ns	9
			3, 4, 7	OE to On	1.5	12.0	ns	10, 11
tpLZ(1)	Output Disable Time	VCC=4.5V	3, 4, 7	OE to On	1.5	8.0	ns	9
			3, 4, 7	OE to On	1.5	10.0	ns	10, 11
tpLH(2)	Propagation Delay	VCC=3.0V	3, 4	In to On	1.0	7.5	ns	9
			3, 4	In to On	1.0	9.0	ns	10, 11
tpHL(2)	Propagation Delay	VCC=3.0V	3, 4	In to On	1.0	7.0	ns	9
			3, 4	In to On	1.0	8.0	ns	10, 11
tpZL(2)	Output Enable Time	VCC=3.0V	3, 4	OE to On	1.0	10.0	ns	9
			3, 4	OE to On	1.0	12.0	ns	10, 11
tpZH(2)	Output Enable Time	VCC=3.0V	3, 4	OE to On	1.0	11.0	ns	9
			3, 4	OE to On	1.0	13.0	ns	10, 11
tpHZ(2)	Output Disable Time	VCC=3.0V	3, 4	OE to On	1.0	13.0	ns	9
			3, 4	OE to On	1.0	15.5	ns	10, 11
tpLZ(2)	Output Disable Time	VCC=3.0V	3, 4	OE to On	1.0	10.0	ns	9
			3, 4	OE to On	1.0	12.0	ns	10, 11

- Note 1: SCREEN TESTED 100% ON EACH DEVICE AT +25C & +125C TEMPERATURE, SUBGROUPS 1, 2, 7, & 8.
- Note 2: SAMPLE TESTED (METHOD 5005, TABLE 1) ON EACH MFG. LOT AT +25C & +125C TEMPERATURE, SUBGROUPS A1, 2, 7, & 8.
- Note 3: SCREEN TESTED 100% ON EACH DEVICE AT +25C TEMPERATURE ONLY SUBGROUP A9.
- Note 4: SAMPLE TESTED (METHOD 5005, TABLE 1) ON EACH MFG. LOT AT +25C & +125C TEMPERATURE, SUBGROUPS A9 & 10.
- Note 5: TRANSMISSION LINE DRIVING TEST, GUARDBAND LIMITS SET FOR +25C, 2 MSEC DURATION MAX.
- Note 6: NOT TESTED AT +125C & -55C TEMPERATURE (DESIGN CHARACTERIZATION DATA).
- Note 7: +25C & +125C MIN LIMITS GUARANTEED FOR 5.5V BY GUARDBANDING 4.5V MIN. LIMITS.