



## MICROCIRCUIT DATA SHEET

**MJLM137-H REV 0A0**

Original Creation Date: 07/12/95  
Last Update Date: 04/29/99  
Last Major Revision Date: 04/21/99

### **3-TERMINAL VOLTAGE REGULATOR, -37 VOLTS $\leq$ VO $\leq$ -1.25 VOLTS AT 0.5A**

#### **General Description**

The LM137H is an adjustable 3-terminal negative voltage regulator capable of supplying in excess of -0.5A over an output voltage range of -1.2V to -37V. This regulator is exceptionally easy to apply, requiring only 2 external resistors to set the output voltage and 1 output capacitor for frequency compensation. The circuit design has been optimized for excellent regulation and low thermal transients. Further, the LM137H features internal current limiting, thermal shutdown and safe-area compensation, making it virtually blowout-proof against overloads.

The LM137H serve a wide variety of applications including local on-card regulation, programmable-output voltage regulation or precision current regulation. The LM137H is an ideal complement to the LM117H adjustable positive regulator.

#### **Industry Part Number**

LM137

#### **NS Part Numbers**

JL137BXA  
JL137SXA

#### **Prime Die**

LM137

#### **Controlling Document**

38510/11803,AMEND. 4

#### **Processing**

MIL-STD-883, Method 5004

#### **Quality Conformance Inspection**

MIL-STD-883, Method 5005

<b>Subgrp</b>	<b>Description</b>	<b>Temp ( °C)</b>
1	Static tests at	+25
2	Static tests at	+125
3	Static tests at	-55
4	Dynamic tests at	+25
5	Dynamic tests at	+125
6	Dynamic tests at	-55
7	Functional tests at	+25
8A	Functional tests at	+125
8B	Functional tests at	-55
9	Switching tests at	+25
10	Switching tests at	+125
11	Switching tests at	-55

**Features**

- Output voltage adjustable from -1.2V to -37V
- 0.5A output current guaranteed, -55 C to +150 C
- Line regulation typically 0.01%/V
- Load regulation typically 0.3%
- Excellent thermal regulation, 0.002%/W
- 50 ppm/ C temperature coefficient
- Temperature-independent current limit
- Internal thermal overload protection
- Standard 3-lead transistor package
- Output short circuit protected

**(Absolute Maximum Ratings)**

(Note 1)

Power Dissipation (Note 2)	Internally Limited
Input-Output Voltage Differential	40V
Operating Junction Temperature	-55 C to +150 C
Maximum Junction Temperature (Note 2)	150 C
Maximum Power Dissipation (@ 25 C)	2.5 Watts
Minimum Input Voltage	-41.25V
Storage Temperature	-65 C to +150 C
Lead Temperature (Soldering, 10 seconds)	300 C
Thermal Resistance	
ThetaJA	
H-Pkg (Still Air @ 0.5W)	140 C/W
H-Pkg (500LF/Min Air Flow @ 0.5W)	64 C/W
ThetaJC	
H-Pkg (@ 1.0W)	15 C/W
Package Weight (Typical)	955mg
ESD Rating (Note 3)	4000V

Note 1: Absolute Maximum Ratings indicate limits beyond which damage to the device may occur. Operating Rating indicate conditions for which the device is functional, but do not guarantee specific performance limits. For guaranteed specifications and test conditions, see the Electrical Characteristics. The guaranteed specifications apply only for the test conditions listed. Some performance characteristics may degrade when the device is not operated under the listed test conditions.

Note 2: The maximum power dissipation must be derated at elevated temperatures and is dictated by Tjmax (maximum junction temperature), ThetaJA (package junction to ambient thermal resistance), and TA (ambient temperature). The maximum allowable power dissipation at any temperature is  $P_{dmax} = (T_{jmax} - TA) / \Theta_{JA}$  or the number given in the Absolute Maximum Ratings, whichever is lower.

Note 3: Human body model, 100pF discharged through 1.5K Ohms

## Recommended Operating Conditions

Ta	-55 C to +125 C
Input Voltage Range	-41.25V to -4.25V

## Electrical Characteristics

### DC PARAMETERS

SYMBOL	PARAMETER	CONDITIONS	NOTES	PIN-NAME	MIN	MAX	UNIT	SUB-GROUPS
Vout	Output Voltage	Vin = -4.25V, I <sub>l</sub> = 5mA			-1.275	-1.225	V	1
					-1.3	-1.2	V	2, 3
		Vin = -4.25V, I <sub>l</sub> = 500mA			-1.275	-1.225	V	1
					-1.3	-1.2	V	2, 3
		Vin = -41.25V, I <sub>l</sub> = 5mA			-1.275	-1.225	V	1
					-1.3	-1.2	V	2, 3
Vin = -41.25V, I <sub>l</sub> = 50mA			-1.275	-1.225	V	1		
			-1.3	-1.2	V	2, 3		
Vrline	Line Regulation	Vin = -41.25V to -4.25V, I <sub>l</sub> = 5mA			-9	9	mV	1
					-23	23	mV	2, 3
Vrload	Load Regulation	Vin = -6.25V, I <sub>l</sub> = 5mA to 500mA			-12	12	mV	1
					-24	24	mV	2, 3
		Vin = -41.25V, I <sub>l</sub> = 5mA to 50mA			-6	6	mV	1
					-12	12	mV	2, 3
		Vin = -6.25V, I <sub>l</sub> = 5mA to 200mA			-6	6	mV	1
					-12	12	mV	2, 3
Vrth	Thermal Regulation	Vin = -14.6V, I <sub>l</sub> = 500mA			-5	5	mV	1
Iadj	Adjust Pin Current	Vin = -4.25V, I <sub>l</sub> = 5mA			25	100	uA	1, 2, 3
		Vin = -41.25V, I <sub>l</sub> = 5mA			25	100	uA	1, 2, 3
Delta Iadj(line)	Adjust Pin Current Change vs. Line Voltage	Vin = -41.25V to -4.25V, I <sub>l</sub> = 5mA			-5	5	uA	1, 2, 3
Delta Iadj(load)	Adjust Pin Current Change vs. Load Current	Vin = -6.25V, I <sub>l</sub> = 5mA to 500mA			-5	5	uA	1, 2, 3
Ios	Output Short Circuit Current	Vin = -4.25V			0.5	1.8	A	1, 2, 3
		Vin = -40V			0.05	0.5	A	1, 2, 3
Vout (Recovery)	Output Voltage Recovery After Output Short Circuit Current	Vin = -4.25V			-1.275	-1.225	V	1
					-1.3	-1.2	V	2, 3
		Vin = -40V			-1.275	-1.225	V	1
					-1.3	-1.2	V	2, 3

## Electrical Characteristics

### DC PARAMETERS (Continued)

SYMBOL	PARAMETER	CONDITIONS	NOTES	PIN-NAME	MIN	MAX	UNIT	SUB-GROUPS
Iq	Minimum Load Current	Vin = -4.25V			0.2	3	mA	1, 2, 3
		Vin = -14.25V			0.2	3	mA	1, 2, 3
		Vin = -41.25V			1	5	mA	1, 2, 3
Vstart	Voltage Start-up	Vin = -4.25V, I1 = 500mA			-1.275	-1.225	V	1
					-1.3	-1.2	V	2, 3
Vout	Output Voltage	Vin = -6.25V, I1 = 5mA (No Subgroup)	1		-1.3	-1.2	V	

### AC PARAMETERS

Delta Vin/Delta Vout	Ripple Rejection	Vin = -6.25V, I1 = 125mA, ei = 1Vrms at 2400Hz			48		dB	4
Vno	Output Noise Voltage	Vin = -6.25V, I1 = 50mA				120	uVrms	
Delta Vout/Delta Vin	Line Transient Response	Vin = -6.25V, Vpulse = -1V, I1 = 50mA				80	mV/V	7
Delta Vout/Delta I1	Load Transient Response	Vin = -6.25V, I1 = 50mA, Delta I1 = 200mA	2			60	mV	7

### DC PARAMETERS: DRIFT VALUES

(The following conditions apply to all the following parameters, unless otherwise specified.)  
 DC: "Delta calculations performed on JAN S and QMLV devices at group B, subgroup 5 only".

Vout	Output Voltage	Vin = -4.25V, I1 = 5mA			-0.01	0.01	V	1
		Vin = -4.25V, I1 = 500mA			-0.01	0.01	V	1
		Vin = -41.25V, I1 = 5mA			-0.01	0.01	V	1
		Vin = -41.25V, I1 = 50mA			-0.01	0.01	V	1
Vrline	Line Regulation				-4	4	mV	1
Iadj	Adjust Pin Current	Vin = -4.25V, I1 = 5mA			-10	10	uA	1
		Vin = -41.25V, I1 = 5mA			-10	10	uA	1

Note 1: Tested at +125 C; correlated to 150 C.

Note 2: Limit is equivalent to S/S limit of 0.3mV/mA.


## Graphics and Diagrams

GRAPHICS#	DESCRIPTION
05192HRB2	METAL CAN (H), TO-39, 3LD, .200 DIA P.C. (P/P DWG)
H03ARD	METAL CAN (H), TO-39, 3LD, .200 DIA P.C. (P/P DWG)
P000199A	METAL CAN (H), TO-39, 3 LEAD (PINOUT)

See attached graphics following this page.

REVISIONS

LTR	DESCRIPTION	E.C. N.	DATE	BY/APP'D
C	REVISE & REDRAW PER NEW STANDARD	10403	05/24/94	TL/GM
D	UPDATE MILAERO STAMP: Ø .325 WAS Ø .326; REVISE TOLERANCES	10798	02/28/95	TL/L



CONTROLLING DIMENSION IS INCH  
VALUES IN [ ] ARE MILLIMETERS

NOTES: UNLESS OTHERWISE SPECIFIED


- LEADS TO BE LOCATED WITHIN .010 IN/ 0.25 mm OF THEIR TRUE POSITIONS RELATIVE TO A MAXIMUM WIDTH TAB.
- STANDARD METAL CAN TYPE: SOLID BASE, KOVAR.
- APPLIES TO MIL-AERO AND LINEAR PRODUCTS.
- REFERENCE JEDEC REGISTRATION TO-39, JEDEC PUBLICATION No. 95.

MIL-I-38535  
CONFIGURATION CONTROL

APPROVALS	DATE		
DRW: T. LEQUANG	05/24/94		
DATE: 05/24/94			
DRG. CHK.			
ENGR. CHK.			
PROJECTION			
SCALE	SIZE	DRAWING NUMBER	REV
N/A	C	MKT-H03A	D
DO NOT SCALE DRAWING SHEET 1 of 1			

**National Semiconductor**  
2500 Semiconductor Dr., Santa Clara, CA 95052-8090

METAL CAN,  
TO-39, 3 LEAD,  
.200 DIA P.C.



LM137H, LM137HVH  
3 - LEAD TO-39  
CONNECTION DIAGRAM  
BOTTOM VIEW  
P000199A



National Semiconductor™  
MIL/AEROSPACE OPERATIONS  
2900 SEMICONDUCTOR DRIVE  
SANTA CLARA, CA 95050

### Revision History

Rev	ECN #	Rel Date	Originator	Changes
0A0	M0003393	04/29/99	Rose Malone	Update MDS from MJLM137-H, Rev. 0BL to Fully Released MDS MJLM137-H, Rev. 0A0.