

LMH6628

Dual Wideband, Low Noise, Voltage Feedback Op Amp

General Description

The National LMH6628 is a high speed dual op amp that offers a traditional voltage feedback topology featuring unity gain stability and slew enhanced circuitry. The LMH6628's low noise and very low harmonic distortion combine to form a wide dynamic range op amp that operates from a single (5V to 12V) or dual ($\pm 5V$) power supply.

Each of the LMH6628's closely matched channels provides a 300MHz unity gain bandwidth and low input voltage noise density ($2nV/\sqrt{Hz}$). Low 2nd/3rd harmonic distortion ($-65/-74dBc$ at 10MHz) make the LMH6628 a perfect wide dynamic range amplifier for matched I/Q channels.

With its fast and accurate settling (12ns to 0.1%), the LMH6628 is also an excellent choice for wide dynamic range, anti-aliasing filters to buffer the inputs of hi resolution analog-to-digital converters. Combining the LMH6628's two tightly matched amplifiers in a single 8-pin SOIC package reduces cost and board space for many composite amplifier applications such as active filters, differential line drivers/receivers, fast peak detectors and instrumentation amplifiers.

The LMH6628 is fabricated using National's VIP10™ complementary bipolar process.

To reduce design times and assist in board layout, the LMH6628 is supported by an evaluation board (CLC730036).


Features

- Wide unity gain bandwidth: 300MHz
- Low noise: $2nV/\sqrt{Hz}$
- Low Distortion: $-65/-74dBc$ (10MHz)
- Settling time: 12ns to 0.1%
- Wide supply voltage range: $\pm 2.5V$ to $\pm 6V$
- High output current: $\pm 85mA$
- Improved replacement for CLC428


Applications

- High speed dual op amp
- Low noise integrators
- Low noise active filters
- Driver/receiver for transmission systems
- High speed detectors
- I/Q channel amplifiers

Connection Diagram



Inverting Frequency Response



Absolute Maximum Ratings (Note 1)

If Military/Aerospace specified devices are required, please contact the National Semiconductor Sales Office/Distributors for availability and specifications.

| | |
|------------------------------|--------------|
| ESD Tolerance (Note 4) | |
| Human Body Model | 2kV |
| Machine Model | 200V |
| Supply Voltage | 13.5 |
| Short Circuit Current | (Note 3) |
| Common-Mode Input Voltage | $\pm V_{CC}$ |
| Differential Input Voltage | 6V |
| Maximum Junction Temperature | +150°C |

| | |
|-------------------------------------|-----------------|
| Storage Temperature Range | -65°C to +150°C |
| Lead Temperature (soldering 10 sec) | +300°C |

Operating Ratings (Note 1)

| | | |
|-----------------------------|------------------------|-------------------|
| Thermal Resistance (Note 5) | | |
| Package | (θ_{JC}) | (θ_{JA}) |
| SOIC | 65°C/W | 145°C/W |
| Temperature Range | -40°C to +85°C | |
| Nominal Supply Voltage | $\pm 2.5V$ to $\pm 6V$ | |

Electrical Characteristics (Note 2)

$V_{CC} = \pm 5V$, $A_V = +2V/V$, $R_F = 100\Omega$, $R_G = 100\Omega$, $R_L = 100\Omega$; unless otherwise specified. **Boldface** limits apply at the temperature extremes.

| Symbol | Parameter | Conditions | Min | Typ | Max | Units |
|--------------------------------------|------------------------------|-----------------------|-----------------|---------|--|-----------------|
| Frequency Domain Response | | | | | | |
| GB | Gain Bandwidth Product | $V_O < 0.5V_{PP}$ | | 200 | | MHz |
| SSBW | -3dB Bandwidth, $A_V = +1$ | $V_O < 0.5V_{PP}$ | 180 | 300 | | MHz |
| SSBW | -3dB Bandwidth, $A_V = +2$ | $V_O < 0.5V_{PP}$ | | 100 | | MHz |
| GFL | Gain Flatness | $V_O < 0.5V_{PP}$ | | | | |
| GFP | Peaking | DC to 200MHz | | 0.0 | | dB |
| GFR | Rolloff | DC to 20MHz | | .1 | | dB |
| LPD | Linear Phase Deviation | DC to 20MHz | | .1 | | deg |
| Time Domain Response | | | | | | |
| TR | Rise and Fall Time | 1V Step | | 4 | | ns |
| TS | Settling Time | 2V Step to 0.1% | | 12 | | ns |
| OS | Overshoot | 1V Step | | 1 | | % |
| SR | Slew Rate | 4V Step | 300 | 550 | | V/ μ s |
| Distortion And Noise Response | | | | | | |
| HD2 | 2nd Harmonic Distortion | $1V_{PP}$, 10MHz | | -65 | | dBc |
| HD3 | 3rd Harmonic Distortion | $1V_{PP}$, 10MHz | | -74 | | dBc |
| V_N | Equivalent Input Noise | | | | | |
| | Voltage | 1MHz to 100MHz | | 2 | | nV/ \sqrt{Hz} |
| I_N | Current | 1MHz to 100MHz | | 2 | | pA/ \sqrt{Hz} |
| XTLKA | Crosstalk | Input Referred, 10MHz | | -62 | | dB |
| Static, DC Performance | | | | | | |
| G_{OL} | Open-Loop Gain | | 56 53 | 63 | | dB |
| V_{IO} | Input Offset Voltage | | | ± 5 | ± 2 ± 2.6 | mV |
| DV_{IO} | Average Drift | | | 5 | | μ V/°C |
| I_{BN} | Input Bias Current | | | ± 7 | ± 20 ± 30 | μ A |
| DI_{BN} | Average Drift | | | 150 | | nA/°C |
| I_{OS} | Input Offset Current | | | 0.3 | | μ A |
| I_{OSD} | Average Drift | | | 5 | | nA/°C |
| PSRR | Power Supply Rejection Ratio | | 60 46 | 70 | | dB |
| CMRR | Common-Mode Rejection Ratio | | 57 54 | 62 | | dB |

Electrical Characteristics (Note 2) (Continued)

$V_{CC} = \pm 5V$, $A_V = +2V/V$, $R_F = 100\Omega$, $R_G = 100\Omega$, $R_L = 100\Omega$; unless otherwise specified. **Boldface** limits apply at the temperature extremes.

| Symbol | Parameter | Conditions | Min | Typ | Max | Units |
|----------------------------------|----------------------|-----------------------------|--|-----------|-------------------|------------|
| I_{CC} | Supply Current | Per Channel, $R_L = \infty$ | 8 7.5 | 9 | 12 12.5 | mA |
| Miscellaneous Performance | | | | | | |
| R_{IN} | Input Resistance | Common-Mode | | 500 | | k Ω |
| | | Differential-Mode | | 200 | | k Ω |
| C_{IN} | Input Capacitance | Common-Mode | | 1.5 | | pF |
| | | Differential-Mode | | 1.5 | | pF |
| R_{OUT} | Output Resistance | Closed-Loop | | .1 | | Ω |
| V_O | Output Voltage Range | $R_L = \infty$ | | ± 3.8 | | V |
| V_{OL} | | $R_L = 100\Omega$ | ± 3.2 ± 3.1 | ± 3.5 | | V |
| CMIR | Input Voltage Range | Common- Mode | | ± 3.7 | | V |
| I_O | Output Current | | ± 50 | ± 85 | | mA |

Note 1: Absolute Maximum Ratings indicate limits beyond which damage to the device may occur. Operating Ratings indicate conditions for which the device is intended to be functional, but specific performance is not guaranteed. For guaranteed specifications, see the Electrical Characteristics tables.

Note 2: Electrical Table values apply only for factory testing conditions at the temperature indicated. Factory testing conditions result in very limited self-heating of the device such that $T_J = T_A$. No guarantee of parametric performance is indicated in the electrical tables under conditions of internal self heating where $T_J > T_A$. See Note 6 for information on temperature de-rating of this device. Min/Max ratings are based on product characterization and simulation. Individual parameters are tested as noted.

Note 3: Output is short circuit protected to ground, however maximum reliability is obtained if output current does not exceed 160mA.

Note 4: Human body model, 1.5k Ω in series with 100pF. Machine model, 0 Ω in series with 200pF.


Note 5: The maximum power dissipation is a function of $T_{J(MAX)}$, θ_{JA} and T_A . The maximum allowable power dissipation at any ambient temperature is $P_D = (T_{J(MAX)} - T_A) / \theta_{JA}$. All numbers apply for packages soldered directly onto a PC board.

Ordering Information

| Package | Part Number | Package Marking | Transport Media | NSC Drawing |
|------------|-------------|-----------------|--------------------------|-------------|
| 8-pin SOIC | LMH6628MA | LMH6628MA | Rails | M08A |
| | LMH6628MAX | | 2.5k Units Tape and Reel | |


Typical Performance Characteristics ($T_A = +25^\circ$, $A_V = +2$, $V_{CC} = \pm 5V$, $R_f = 100\Omega$, $R_L = 100\Omega$, unless specified)

Non-Inverting Frequency Response




20038513

Inverting Frequency Response




20038515

Frequency Response vs. Load Resistance




20038525

Frequency Response vs. Output Amplitude




20038510

Frequency Response vs. Capacitive Load




20038516

Gain Flatness & Linear Phase




20038524


Typical Performance Characteristics ($T_A = +25^\circ$, $A_V = +2$, $V_{CC} = \pm 5V$, $R_f = 100\Omega$, $R_L = 100\Omega$, unless specified) (Continued)




20038514




20038509




20038511



20038512




20038507



20038508


Typical Performance Characteristics ($T_A = +25^\circ$, $A_V = +2$, $V_{CC} = \pm 5V$, $R_f = 100\Omega$, $R_L = 100\Omega$, unless specified) (Continued)

2nd & 3rd Harmonic Distortion vs. Frequency




20038517

PSRR and CMRR ($\pm 5V$)




20038522

PSRR and CMRR ($\pm 2.5V$)




20038523

Closed Loop Output Resistance ($\pm 2.5V$)




20038518

Closed Loop Output Resistance ($\pm 5V$)









20038519

Open Loop Gain & Phase ($\pm 2.5V$)




20038521

Typical Performance Characteristics ($T_A = +25^\circ$, $A_V = +2$, $V_{CC} = \pm 5V$, $R_f = 100\Omega$, $R_L = 100\Omega$, unless specified) (Continued)



Typical Performance Characteristics

($T_A = +25^\circ$, $A_V = +2$, $V_{CC} = \pm 5V$, $R_F = 100\Omega$, $R_L = 100\Omega$, unless specified) (Continued)



Application Section

Low Noise Design

Ultimate low noise performance from circuit designs using the LMH6628 requires the proper selection of external resistors. By selecting appropriate low valued resistors for R_F and R_G , amplifier circuits using the LMH6628 can achieve output noise that is approximately the equivalent voltage input noise of $2nV/\sqrt{Hz}$ multiplied by the desired gain (A_V).

DC Bias Currents and Offset Voltages

Cancellation of the output offset voltage due to input bias currents is possible with the LMH6628. This is done by making the resistance seen from the inverting and non-inverting inputs equal. Once done, the residual output offset voltage will be the input offset voltage (V_{OS}) multiplied by the desired gain (A_V). National Application Note OA-7 offers several solutions to further reduce the output offset.

Output and Supply Considerations

With $\pm 5V$ supplies, the LMH6628 is capable of a typical output swing of $\pm 3.8V$ under a no-load condition. Additional output swing is possible with slightly higher supply voltages. For loads of less than 50Ω , the output swing will be limited by the LMH6628's output current capability, typically 85mA.

Output settling time when driving capacitive loads can be improved by the use of a series output resistor. See the plot labeled 'R_S vs. C_L' in the Typical Performance section.

Layout

Proper power supply bypassing is critical to insure good high frequency performance and low noise. De-coupling capacitors of $0.1\mu F$ should be placed as close as possible to the power supply pins. The use of surface mounted capacitors is recommended due to their low series inductance.

A good high frequency layout will keep power supply and ground traces away from the inverting input and output pins. Parasitic capacitance from these nodes to ground causes frequency response peaking and possible circuit oscillation. See OA-15 for more information. National suggests the 730036 (SOIC) dual op amp evaluation board as a guide for high frequency layout and as an aid in device evaluation.

Analog Delay Circuit (All-Pass Network)

The circuit in Figure 1 implements an all-pass network using the LMH6628. A wide bandwidth buffer (LM7121) drives the circuit and provides a high input impedance for the source. As shown in Figure 2, the circuit provides a 13.1ns delay (with $R = 40.2\Omega$, $C = 47pF$). R_F and R_G should be of equal and low value for parasitic insensitive operation.




FIGURE 1.




FIGURE 2. Delay Circuit Response to 0.5V Pulse

The circuit gain is +1 and the delay is determined by the following equations.

$$\tau_{\text{delay}} = 2(2RC + T_d) \tag{1}$$

$$T_d = \frac{1}{360} \frac{d\phi}{df}; \tag{2}$$

where T_d is the delay of the op amp at $A_v = +1$.

The LMH6628 provides a typical delay of 2.8ns at its -3dB point.

Full Duplex Digital or Analog Transmission

Simultaneous transmission and reception of analog or digital signals over a single coaxial cable or twisted-pair line can reduce cabling requirements. The LMH6628's wide bandwidth and high common-mode rejection in a differential amplifier configuration allows full duplex transmission of video, telephone, control and audio signals.

In the circuit shown in Figure 3, one of the LMH6628's amps is used as a 'driver' and the other as a difference 'receiver' amplifier. The output impedance of the 'driver' is essentially zero. The two R's are chosen to match the characteristic impedance of the transmission line. The 'driver' op amp gain can be selected for unity or greater.

Receiver amplifier A_2 (B_2) is connected across R and forms differential amplifier for the signals transmitted by driver A_2 (B_2). If R_f equals R_g , receiver A_2 (B_1) will then reject the signals from driver A_1 (B_1) and pass the signals from B_1 (A_1).




FIGURE 3.

The output of the receiver amplifier will be:

$$V_{\text{out}_{A(B)}} = \frac{1}{2} V_{\text{in}_{A(B)}} \left[1 - \frac{R_f}{R_g} \right] + \frac{1}{2} V_{\text{in}_{B(A)}} \left[1 + \frac{R_f}{R_g} \right] \tag{3}$$

Care must be given to layout and component placement to maintain a high frequency common-mode rejection. The plot of Figure 4 shows the simultaneous reception of signals transmitted at 1MHz and 10MHz.




FIGURE 4.

Positive Peak Detector

The LMH6628's dual amplifiers can be used to implement a unity-gain peak detector circuit as shown in Figure 5.




FIGURE 5.

The acquisition speed of this circuit is limited by the dynamic resistance of the diode when charging C_{hold} . A plot of the circuit's performance is shown in Figure 6 with a 1MHz sinusoidal input.




FIGURE 6.

A current source, built around Q1, provides the necessary bias current for the second amplifier and prevents saturation when power is applied. The resistor, R, closes the loop while diode D2 prevents negative saturation when V_{IN} is less than V_C . A MOS-type switch (not shown) can be used to reset the capacitor's voltage.

The maximum speed of detection is limited by the delay of the op amps and the diodes. The use of Schottky diodes will provide faster response.

Adjustable or Bandpass Equalizer

A 'boost' equalizer can be made with the LMH6628 by summing a bandpass response with the input signal, as shown in Figure 7.




FIGURE 7.

The overall transfer function is shown in Eq. 5.

$$\frac{V_{out}}{V_{in}} = \left[\frac{R_b}{K(R_a + R_b)} \right] \frac{s2Q\omega_o}{s^2 + s \frac{\omega_o}{Q} + \omega_o^2} - 1 \tag{4}$$

To build a boost circuit, use the design equations Eq. 6 and Eq. 7.

$$\frac{R_2 C}{2} = \frac{Q}{\omega_o} \tag{5}$$

$$2C (R_a \parallel R_b) = \frac{1}{Q\omega_o} \tag{6}$$

Select R_2 and C using Eq. 6. Use reasonable values for high frequency circuits - R_2 between 10Ω and $5k\Omega$, C between $10pF$ and $2000pF$. Use Eq. 7 to determine the parallel combination of R_a and R_b . Select R_a and R_b by either the 10Ω to $5k\Omega$ criteria or by other requirements based on the impedance V_{in} is capable of driving. Finish the design by determining the value of K from Eq. 8.

$$\text{Peak Gain} = \frac{V_{out}}{V_{in}} (\omega_o) = \frac{R_2}{2KR_a} \tag{7}$$

Figure 8 shows an example of the response of the circuit of Figure 9, where f_o is 2.3MHz. The component values are as follows: $R_a=2.1k\Omega$, $R_b = 68.5\Omega$, $R_2 = 4.22k\Omega$, $R = 500\Omega$, $KR = 50\Omega$, $C = 120pF$.





FIGURE 8.

Physical Dimensions inches (millimeters)

unless otherwise noted



**8-Pin SOIC
NS Package Number M08A**

LIFE SUPPORT POLICY

NATIONAL'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT AND GENERAL COUNSEL OF NATIONAL SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.



National Semiconductor Corporation
Americas
Email: support@nsc.com

National Semiconductor Europe
Fax: +49 (0) 180-530 85 86
Email: europe.support@nsc.com
Deutsch Tel: +49 (0) 69 9508 6208
English Tel: +44 (0) 870 24 0 2171
Français Tel: +33 (0) 1 41 91 8790

National Semiconductor Asia Pacific Customer Response Group
Tel: 65-2544466
Fax: 65-2504466
Email: ap.support@nsc.com

National Semiconductor Japan Ltd.
Tel: 81-3-5639-7560
Fax: 81-3-5639-7507

www.national.com