



**33A, 100V, 0.040 Ohm, N-Channel,  
UltraFET Power MOSFET**

**Packaging**

JEDEC TO-220AB



**Symbol**



**Features**

- Ultra Low On-Resistance
  - $r_{DS(ON)} = 0.040\Omega$ ,  $V_{GS} = 10V$
- Simulation Models
  - Temperature Compensated PSPICE® and SABER® Electrical Models
  - Spice and SABER® Thermal Impedance Models
  - [www.semi.Intersil.com](http://www.semi.Intersil.com)
- Peak Current vs Pulse Width Curve
- UIS Rating Curve

**Ordering Information**

| PART NUMBER | PACKAGE  | BRAND  |
|-------------|----------|--------|
| HUF75631P3  | TO-220AB | 75631P |

**Absolute Maximum Ratings**  $T_C = 25^\circ C$ , Unless Otherwise Specified

|                                                                          | HUF75631P3        | UNITS         |
|--------------------------------------------------------------------------|-------------------|---------------|
| Drain to Source Voltage (Note 1) . . . . .                               | 100               | V             |
| Drain to Gate Voltage ( $R_{GS} = 20k\Omega$ ) (Note 1) . . . . .        | 100               | V             |
| Gate to Source Voltage . . . . .                                         | $\pm 20$          | V             |
| Drain Current                                                            |                   |               |
| Continuous ( $T_C = 25^\circ C$ , $V_{GS} = 10V$ ) (Figure 2) . . . . .  | 33                | A             |
| Continuous ( $T_C = 100^\circ C$ , $V_{GS} = 10V$ ) (Figure 2) . . . . . | 23                | A             |
| Pulsed Drain Current . . . . .                                           | Figure 4          |               |
| Pulsed Avalanche Rating . . . . .                                        | Figures 6, 14, 15 |               |
| Power Dissipation . . . . .                                              | 120               | W             |
| Derate Above $25^\circ C$ . . . . .                                      | 0.80              | W/ $^\circ C$ |
| Operating and Storage Temperature . . . . .                              | -55 to 175        | $^\circ C$    |
| Maximum Temperature for Soldering                                        |                   |               |
| Leads at 0.063in (1.6mm) from Case for 10s. . . . .                      | 300               | $^\circ C$    |
| Package Body for 10s, See Techbrief TB334. . . . .                       | 260               | $^\circ C$    |

**NOTE:**

1.  $T_J = 25^\circ C$  to  $150^\circ C$ .

**CAUTION:** Stresses above those listed in "Absolute Maximum Ratings" may cause permanent damage to the device. This is a stress only rating and operation of the device at these or any other conditions above those indicated in the operational sections of this specification is not implied.

# HUF75631P3

## Electrical Specifications $T_C = 25^\circ\text{C}$ , Unless Otherwise Specified

| PARAMETER                                        | SYMBOL              | TEST CONDITIONS                                                                                                     | MIN                                                                                                    | TYP   | MAX   | UNITS |    |
|--------------------------------------------------|---------------------|---------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------|-------|-------|-------|----|
| OFF STATE SPECIFICATIONS                         |                     |                                                                                                                     |                                                                                                        |       |       |       |    |
| Drain to Source Breakdown Voltage                | BV <sub>DSS</sub>   | I <sub>D</sub> = 250μA, V <sub>GS</sub> = 0V (Figure 11)                                                            | 100                                                                                                    | -     | -     | V     |    |
| Zero Gate Voltage Drain Current                  | I <sub>DSS</sub>    | V <sub>DS</sub> = 95V, V <sub>GS</sub> = 0V                                                                         | -                                                                                                      | -     | 1     | μA    |    |
|                                                  |                     | V <sub>DS</sub> = 90V, V <sub>GS</sub> = 0V, T <sub>C</sub> = 150°C                                                 | -                                                                                                      | -     | 250   | μA    |    |
| Gate to Source Leakage Current                   | I <sub>GSS</sub>    | V <sub>GS</sub> = ±20V                                                                                              | -                                                                                                      | -     | ±100  | nA    |    |
| ON STATE SPECIFICATIONS                          |                     |                                                                                                                     |                                                                                                        |       |       |       |    |
| Gate to Source Threshold Voltage                 | V <sub>GS(TH)</sub> | V <sub>GS</sub> = V <sub>DS</sub> , I <sub>D</sub> = 250μA (Figure 10)                                              | 2                                                                                                      | -     | 4     | V     |    |
| Drain to Source On Resistance                    | r <sub>DS(ON)</sub> | I <sub>D</sub> = 33A, V <sub>GS</sub> = 10V (Figure 9)                                                              | -                                                                                                      | 0.033 | 0.040 | Ω     |    |
| THERMAL SPECIFICATIONS                           |                     |                                                                                                                     |                                                                                                        |       |       |       |    |
| Thermal Resistance Junction to Case              | R <sub>θJC</sub>    | TO-220                                                                                                              | -                                                                                                      | -     | 1.25  | °C/W  |    |
| Thermal Resistance Junction to Ambient           | R <sub>θJA</sub>    |                                                                                                                     | -                                                                                                      | -     | 62    | °C/W  |    |
| SWITCHING SPECIFICATIONS (V <sub>GS</sub> = 10V) |                     |                                                                                                                     |                                                                                                        |       |       |       |    |
| Turn-On Time                                     | t <sub>ON</sub>     | V <sub>DD</sub> = 50V, I <sub>D</sub> = 33A<br>V <sub>GS</sub> = 10V,<br>R <sub>GS</sub> = 9.1Ω<br>(Figures 18, 19) | -                                                                                                      | -     | 100   | ns    |    |
| Turn-On Delay Time                               | t <sub>d(ON)</sub>  |                                                                                                                     | -                                                                                                      | 9.5   | -     | ns    |    |
| Rise Time                                        | t <sub>r</sub>      |                                                                                                                     | -                                                                                                      | 57    | -     | ns    |    |
| Turn-Off Delay Time                              | t <sub>d(OFF)</sub> |                                                                                                                     | -                                                                                                      | 40    | -     | ns    |    |
| Fall Time                                        | t <sub>f</sub>      |                                                                                                                     | -                                                                                                      | 55    | -     | ns    |    |
| Turn-Off Time                                    | t <sub>OFF</sub>    |                                                                                                                     | -                                                                                                      | -     | 145   | ns    |    |
| GATE CHARGE SPECIFICATIONS                       |                     |                                                                                                                     |                                                                                                        |       |       |       |    |
| Total Gate Charge                                | Q <sub>g(TOT)</sub> | V <sub>GS</sub> = 0V to 20V                                                                                         | V <sub>DD</sub> = 50V,<br>I <sub>D</sub> = 33A,<br>I <sub>g(REF)</sub> = 1.0mA<br>(Figures 13, 16, 17) | -     | 66    | 79    | nC |
| Gate Charge at 10V                               | Q <sub>g(10)</sub>  | V <sub>GS</sub> = 0V to 10V                                                                                         |                                                                                                        | -     | 35    | 42    | nC |
| Threshold Gate Charge                            | Q <sub>g(TH)</sub>  | V <sub>GS</sub> = 0V to 2V                                                                                          |                                                                                                        | -     | 2.4   | 2.9   | nC |
| Gate to Source Gate Charge                       | Q <sub>gs</sub>     |                                                                                                                     |                                                                                                        | -     | 5.4   | -     | nC |
| Gate to Drain "Miller" Charge                    | Q <sub>gd</sub>     |                                                                                                                     |                                                                                                        | -     | 13    | -     | nC |
| CAPACITANCE SPECIFICATIONS                       |                     |                                                                                                                     |                                                                                                        |       |       |       |    |
| Input Capacitance                                | C <sub>ISS</sub>    | V <sub>DS</sub> = 25V, V <sub>GS</sub> = 0V,<br>f = 1MHz<br>(Figure 12)                                             | -                                                                                                      | 1220  | -     | pF    |    |
| Output Capacitance                               | C <sub>OSS</sub>    |                                                                                                                     | -                                                                                                      | 295   | -     | pF    |    |
| Reverse Transfer Capacitance                     | C <sub>RSS</sub>    |                                                                                                                     | -                                                                                                      | 100   | -     | pF    |    |

## Source to Drain Diode Specifications

| PARAMETER                     | SYMBOL   | TEST CONDITIONS                                                | MIN | TYP | MAX  | UNITS |
|-------------------------------|----------|----------------------------------------------------------------|-----|-----|------|-------|
| Source to Drain Diode Voltage | $V_{SD}$ | $I_{SD} = 33\text{A}$                                          | -   | -   | 1.25 | V     |
|                               |          | $I_{SD} = 17\text{A}$                                          | -   | -   | 1.00 | V     |
| Reverse Recovery Time         | $t_{rr}$ | $I_{SD} = 33\text{A}$ , $dI_{SD}/dt = 100\text{A}/\mu\text{s}$ | -   | -   | 112  | ns    |
| Reverse Recovered Charge      | $Q_{RR}$ | $I_{SD} = 33\text{A}$ , $dI_{SD}/dt = 100\text{A}/\mu\text{s}$ | -   | -   | 400  | nC    |

# Typical Performance Curves




FIGURE 1. NORMALIZED POWER DISSIPATION vs CASE TEMPERATURE




FIGURE 2. MAXIMUM CONTINUOUS DRAIN CURRENT vs CASE TEMPERATURE




FIGURE 3. NORMALIZED MAXIMUM TRANSIENT THERMAL IMPEDANCE




FIGURE 4. PEAK CURRENT CAPABILITY

# Typical Performance Curves (Continued)





FIGURE 5. FORWARD BIAS SAFE OPERATING AREA



NOTE: Refer to Intersil Application Notes AN9321 and AN9322.

FIGURE 6. UNCLAMPED INDUCTIVE SWITCHING CAPABILITY




FIGURE 7. TRANSFER CHARACTERISTICS




FIGURE 8. SATURATION CHARACTERISTICS




FIGURE 9. NORMALIZED DRAIN TO SOURCE ON RESISTANCE vs JUNCTION TEMPERATURE




FIGURE 10. NORMALIZED GATE THRESHOLD VOLTAGE vs JUNCTION TEMPERATURE

## Typical Performance Curves (Continued)




FIGURE 11. NORMALIZED DRAIN TO SOURCE BREAKDOWN VOLTAGE vs JUNCTION TEMPERATURE





FIGURE 12. CAPACITANCE vs DRAIN TO SOURCE VOLTAGE



NOTE: Refer to Intersil Application Notes AN7254 and AN7260.

FIGURE 13. GATE CHARGE WAVEFORMS FOR CONSTANT GATE CURRENT

## Test Circuits and Waveforms




FIGURE 14. UNCLAMPED ENERGY TEST CIRCUIT




FIGURE 15. UNCLAMPED ENERGY WAVEFORMS

Test Circuits and Waveforms (Continued)




FIGURE 16. GATE CHARGE TEST CIRCUIT




FIGURE 17. GATE CHARGE WAVEFORMS




FIGURE 18. SWITCHING TIME TEST CIRCUIT




FIGURE 19. SWITCHING TIME WAVEFORM



**SABER Electrical Model**

REV 19 July 1999

template huf75631 n2,n1,n3

electrical n2,n1,n3

```

{
var i iscl
d..model dbodymod = (is = 1.20e-12, cjo = 1.50e-9, tt = 7.47e-8, xti = 5, m = 0.63)
d..model dbreakmod = ()
d..model dplcapmod = (cjo = 1.45e-9, is = 1e-30, m = 0.82)
m..model mmedmod = (type=_n, vto = 3.11, kp = 5, is = 1e-30, tox = 1)
m..model mstrongmod = (type=_n, vto = 3.57, kp = 33.5, is = 1e-30, tox = 1)
m..model mweakmod = (type=_n, vto = 2.68, kp = 0.09, is = 1e-30, tox = 1)
sw_vcsp..model s1amod = (ron = 1e-5, roff = 0.1, von = -6.2, voff = -3.1)
sw_vcsp..model s1bmod = (ron = 1e-5, roff = 0.1, von = -3.1, voff = -6.2)
sw_vcsp..model s2amod = (ron = 1e-5, roff = 0.1, von = -1.0, voff = 0.5)
sw_vcsp..model s2bmod = (ron = 1e-5, roff = 0.1, von = 0.5, voff = -1.0)

```

```

c.ca n12 n8 = 1.95e-9
c.cb n15 n14 = 1.90e-9
c.cin n6 n8 = 1.12e-9

```

```

d.dbody n7 n71 = model=dbodymod
d.dbreak n72 n11 = model=dbreakmod
d.dplcap n10 n5 = model=dplcapmod

```

i.it n8 n17 = 1

```

l.ldrain n2 n5 = 1e-9
l.lgate n1 n9 = 6.19e-9
l.lsource n3 n7 = 2.18e-9

```

```

m.mmed n16 n6 n8 n8 = model=mmedmod, l=1u, w=1u
m.mstrong n16 n6 n8 n8 = model=mstrongmod, l=1u, w=1u
m.mweak n16 n21 n8 n8 = model=mweakmod, l=1u, w=1u

```

```

res.rbreak n17 n18 = 1, tc1 = 1.05e-3, tc2 = -5.0e-7
res.rbody n71 n5 = 4.2e-3, tc1 = 1.30e-3, tc2 = 8.0e-6
res.rdbreak n72 n5 = 4.2e-1, tc1 = 8.0e-4, tc2 = 3.0e-6
res.rdrain n50 n16 = 2.00e-2, tc1 = 9.40e-3, tc2 = 2.93e-5
res.rgate n9 n20 = 1.77
res.rldrain n2 n5 = 10
res.rlgate n1 n9 = 26
res.rlsource n3 n7 = 11
res.rslc1 n5 n51 = 1e-6, tc1 = 3.5e-3, tc2 = 2.0e-6
res.rslc2 n5 n50 = 1e3
res.rsource n8 n7 = 6.5e-3, tc1 = 1e-3, tc2 = 1e-6
res.rvtemp n18 n19 = 1, tc1 = -3.0e-3, tc2 = 1.5e-7
res.rvthres n22 n8 = 1, tc1 = -1.8e-3, tc2 = -8.6e-6

```

```

spe.ebreak n11 n7 n17 n18 = 112.8
spe.eds n14 n8 n5 n8 = 1
spe.egs n13 n8 n6 n8 = 1
spe.esg n6 n10 n6 n8 = 1
spe.evtemp n20 n6 n18 n22 = 1
spe.evthres n6 n21 n19 n8 = 1

```

```

sw_vcsp.s1a n6 n12 n13 n8 = model=s1amod
sw_vcsp.s1b n13 n12 n13 n8 = model=s1bmod
sw_vcsp.s2a n6 n15 n14 n13 = model=s2amod
sw_vcsp.s2b n13 n15 n14 n13 = model=s2bmod


```

v.vbat n22 n19 = dc=1

```

equations {
i (n51->n50) +=iscl
iscl: v(n51,n50) = (((v(n5,n51))/(1e-9+abs(v(n5,n51)))))*((abs(v(n5,n51)*1e6/71))** 3.5))
}
}

```



## SPICE Thermal Model

REV 26 July 1999

HUF75631T

CTHERM1 th 6 2.60e-3  
CTHERM2 6 5 8.85e-3  
CTHERM3 5 4 7.60e-3  
CTHERM4 4 3 7.65e-3  
CTHERM5 3 2 1.22e-2  
CTHERM6 2 tl 8.70e-2


RTHERM1 th 6 9.00e-3  
RTHERM2 6 5 1.80e-2  
RTHERM3 5 4 9.15e-2  
RTHERM4 4 3 2.43e-1  
RTHERM5 3 2 3.10e-1  
RTHERM6 2 tl 3.21e-1

## SABER Thermal Model

SABER thermal model HUF75631T

```
template thermal_model th tl
thermal_c th, tl
{
  ctherm.ctherm1 th 6 = 2.60e-3
  ctherm.ctherm2 6 5 = 8.85e-3
  ctherm.ctherm3 5 4 = 7.60e-3
  ctherm.ctherm4 4 3 = 7.65e-3
  ctherm.ctherm5 3 2 = 1.22e-2
  ctherm.ctherm6 2 tl = 8.70e-2

  rtherm.rtherm1 th 6 = 9.00e-3
  rtherm.rtherm2 6 5 = 1.80e-2
  rtherm.rtherm3 5 4 = 9.15e-2
  rtherm.rtherm4 4 3 = 2.43e-1
  rtherm.rtherm5 3 2 = 3.10e-1
  rtherm.rtherm6 2 tl = 3.21e-1
}
```



All Intersil semiconductor products are manufactured, assembled and tested under **ISO9000** quality systems certification.

*Intersil semiconductor products are sold by description only. Intersil Corporation reserves the right to make changes in circuit design and/or specifications at any time without notice. Accordingly, the reader is cautioned to verify that data sheets are current before placing orders. Information furnished by Intersil is believed to be accurate and reliable. However, no responsibility is assumed by Intersil or its subsidiaries for its use; nor for any infringements of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Intersil or its subsidiaries.*

For information regarding Intersil Corporation and its products, see web site [www.intersil.com](http://www.intersil.com)

## Sales Office Headquarters

### NORTH AMERICA

Intersil Corporation  
P. O. Box 883, Mail Stop 53-204  
Melbourne, FL 32902  
TEL: (407) 724-7000  
FAX: (407) 724-7240

### EUROPE

Intersil SA  
Mercure Center  
100, Rue de la Fusee  
1130 Brussels, Belgium  
TEL: (32) 2.724.2111  
FAX: (32) 2.724.22.05

### ASIA

Intersil (Taiwan) Ltd.  
7F-6, No. 101 Fu Hsing North Road  
Taipei, Taiwan  
Republic of China  
TEL: (886) 2 2716 9310  
FAX: (886) 2 2715 3029