

## 15A, 1000V Hyperfast Diode

The RHRP15100 is a hyperfast diode with soft recovery characteristics ( $t_{rr} < 60\text{ns}$ ). It has half the recovery time of ultrafast diodes and is of silicon nitride passivated ion-implanted epitaxial planar construction.

This device is intended for use as a freewheeling/clamping diode and rectifier in a variety of switching power supplies and other power switching applications. Its low stored charge and hyperfast soft recovery minimize ringing and electrical noise in many power switching circuits, thus reducing power loss in the switching transistors.

Formerly developmental type TA49062.

## Ordering Information

| PART NUMBER | PACKAGE  | BRAND    |
|-------------|----------|----------|
| RHRP15100   | TO-220AC | RHR15100 |

NOTE: When ordering, use the entire part number.

## Symbol




## Features

- Hyperfast with Soft Recovery . . . . . <60ns
- Operating Temperature . . . . . 175°C
- Reverse Voltage . . . . . 1000V
- Avalanche Energy Rated
- Planar Construction

## Applications

- Switching Power Supplies
- Power Switching Circuits
- General Purpose

## Packaging



## Absolute Maximum Ratings $T_C = 25^\circ\text{C}$ , Unless Otherwise Specified

|                                                                                          | RHRP15100  | UNITS |
|------------------------------------------------------------------------------------------|------------|-------|
| Peak Repetitive Reverse Voltage . . . . . $V_{RRM}$                                      | 1000       | V     |
| Working Peak Reverse Voltage . . . . . $V_{RWM}$                                         | 1000       | V     |
| DC Blocking Voltage . . . . . $V_R$                                                      | 1000       | V     |
| Average Rectified Forward Current . . . . . $I_{F(AV)}$<br>( $T_C = 130^\circ\text{C}$ ) | 15         | A     |
| Repetitive Peak Surge Current . . . . . $I_{FRM}$<br>(Square Wave, 20kHz)                | 30         | A     |
| Nonrepetitive Peak Surge Current . . . . . $I_{FSM}$<br>(Halfwave, 1 Phase, 60Hz)        | 200        | A     |
| Maximum Power Dissipation . . . . . $P_D$                                                | 100        | W     |
| Avalanche Energy (See Figures 10 and 11) . . . . . $E_{AVL}$                             | 20         | mJ    |
| Operating and Storage Temperature . . . . . $T_{STG}, T_J$                               | -65 to 175 | °C    |

**Electrical Specifications**  $T_C = 25^\circ\text{C}$ , Unless Otherwise Specified

| SYMBOL          | TEST CONDITION                                        | MIN | TYP | MAX | UNITS                     |
|-----------------|-------------------------------------------------------|-----|-----|-----|---------------------------|
| $V_F$           | $I_F = 15\text{A}$                                    | -   | -   | 3.0 | V                         |
|                 | $I_F = 15\text{A}, T_C = 150^\circ\text{C}$           | -   | -   | 2.5 | V                         |
| $I_R$           | $V_R = 1000\text{V}$                                  | -   | -   | 100 | $\mu\text{A}$             |
|                 | $V_R = 1000\text{V}, T_C = 150^\circ\text{C}$         | -   | -   | 500 | $\mu\text{A}$             |
| $t_{rr}$        | $I_F = 1\text{A}, dI_F/dt = 100\text{A}/\mu\text{s}$  | -   | -   | 60  | ns                        |
|                 | $I_F = 15\text{A}, dI_F/dt = 100\text{A}/\mu\text{s}$ | -   | -   | 70  | ns                        |
| $t_a$           | $I_F = 15\text{A}, dI_F/dt = 100\text{A}/\mu\text{s}$ | -   | 40  | -   | ns                        |
| $t_b$           | $I_F = 15\text{A}, dI_F/dt = 100\text{A}/\mu\text{s}$ | -   | 25  | -   | ns                        |
| $Q_{RR}$        | $I_F = 15\text{A}, dI_F/dt = 100\text{A}/\mu\text{s}$ | -   | 160 | -   | nC                        |
| $C_J$           | $V_R = 10\text{V}, I_F = 0\text{A}$                   | -   | 66  | -   | pF                        |
| $R_{\theta JC}$ |                                                       | -   | -   | 1.5 | $^\circ\text{C}/\text{W}$ |

**DEFINITIONS**

$V_F$  = Instantaneous forward voltage (pw = 300 $\mu\text{s}$ , D = 2%).

$I_R$  = Instantaneous reverse current.

$t_{rr}$  = Reverse recovery time (Figure 9), summation of  $t_a + t_b$ .

$t_a$  = Time to reach peak reverse current (See Figure 9).

$t_b$  = Time from peak  $I_{RM}$  to projected zero crossing of  $I_{RM}$  based on a straight line from peak  $I_{RM}$  through 25% of  $I_{RM}$  (See Figure 9).

$Q_{RR}$  = Reverse recovery charge.

$C_J$  = Junction capacitance.

$R_{\theta JC}$  = Thermal resistance junction to case.

pw = pulse width.

D = duty cycle.

**Typical Performance Curves**




FIGURE 1. FORWARD CURRENT vs FORWARD VOLTAGE




FIGURE 2. REVERSE CURRENT vs REVERSE VOLTAGE

## Typical Performance Curves (Continued)





FIGURE 3.  $t_{rr}$ ,  $t_a$  AND  $t_b$  CURVES vs FORWARD CURRENTFIGURE 4.  $t_{rr}$ ,  $t_a$  AND  $t_b$  CURVES vs FORWARD CURRENTFIGURE 5.  $t_{rr}$ ,  $t_a$  AND  $t_b$  CURVES vs FORWARD CURRENT

FIGURE 6. CURRENT DERATING CURVE




FIGURE 7. JUNCTION CAPACITANCE vs REVERSE VOLTAGE

## Test Circuits and Waveforms




FIGURE 8.  $t_{rr}$  TEST CIRCUITFIGURE 9.  $t_{rr}$  WAVEFORMS AND DEFINITIONS

FIGURE 10. AVALANCHE ENERGY TEST CIRCUIT




FIGURE 11. AVALANCHE CURRENT AND VOLTAGE WAVEFORMS

All Intersil semiconductor products are manufactured, assembled and tested under **ISO9000** quality systems certification.

*Intersil semiconductor products are sold by description only. Intersil Corporation reserves the right to make changes in circuit design and/or specifications at any time without notice. Accordingly, the reader is cautioned to verify that data sheets are current before placing orders. Information furnished by Intersil is believed to be accurate and reliable. However, no responsibility is assumed by Intersil or its subsidiaries for its use; nor for any infringements of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Intersil or its subsidiaries.*

For information regarding Intersil Corporation and its products, see web site [www.intersil.com](http://www.intersil.com)