

NPN SILICON RF POWER TRANSISTOR

DESCRIPTION:

The ASI TVV030 is Designed for


FEATURES:

-
-
- **Omnigold™** Metalization System

MAXIMUM RATINGS

I_C	16 A
V_{CBO}	60 V
V_{CEO}	30 V
V_{EBO}	4.0 V
P_{DISS}	150 W @ $T_C = 25\text{ }^{\circ}\text{C}$
T_J	$-65\text{ }^{\circ}\text{C}$ to $+200\text{ }^{\circ}\text{C}$
T_{STG}	$-65\text{ }^{\circ}\text{C}$ to $+150\text{ }^{\circ}\text{C}$
θ_{JC}	$1.2\text{ }^{\circ}\text{C/W}$

PACKAGE STYLE .500 6L FLG



DIM	MINIMUM inches / mm	MAXIMUM inches / mm
A	.150 / 3.43	.160 / 4.06
B	.045 / 1.14	
C	.210 / 5.33	.220 / 5.59
D	.835 / 21.21	.865 / 21.97
E	.200 / 5.08	.210 / 5.33
F	.490 / 12.45	.510 / 12.95
G	.003 / 0.08	.007 / 0.18
H	.125 / 3.18	
I	.725 / 18.42	
J	.970 / 24.64	.980 / 24.89
K	.090 / 2.29	.105 / 2.67
L	.150 / 3.81	.170 / 4.32
M	.285 / 7.24	
N	.120 / 3.05	.135 / 3.43

ORDER CODE: ASI10660

CHARACTERISTICS $T_C = 25\text{ }^{\circ}\text{C}$

SYMBOL	TEST CONDITIONS	MINIMUM	TYPICAL	MAXIMUM	UNITS
BV_{CBO}	$I_C = 100\text{ mA}$	60			V
BV_{CER}	$I_C = 100\text{ mA}$ $R_{BE} = 10\text{ }\Omega$	60			V
BV_{CEO}	$I_C = 100\text{ mA}$	30			V
BV_{EBO}	$I_E = 10\text{ mA}$	4.0			V
I_{CES}	$V_{CB} = 50\text{ V}$			5.0	mA
h_{FE}	$V_{CE} = 5.0\text{ V}$ $I_C = 1.0\text{ A}$	10		120	---
C_{OB}	$V_{CB} = 30\text{ V}$ $f = 1.0\text{ MHz}$			150	pF
P_G	$V_{CE} = 28\text{ V}$ $I_C = 3.5\text{ A}$ $f = 225\text{ MHz}$	7.5			dB
IMD_1	$P_{OUT} = 30\text{ W}$	-53			dB