


FXO-37F

Miniature Clock Crystal Oscillator

■Features

- It is a compact and thin ceramic package with a metalized lead for surface mounting that is able to be automatically loaded.
- Reflow soldering is possible.
- CMOS, TTL IC direct drive is possible. Depending upon the frequency band, there is also a crystal oscillator with a CMOS IC with a tri-state function built in.
- Use in the broad frequency band from 50MHz to 125MHz is possible. (PLL circuit is built in).



■Specifications

Item	Type	FXO-37F	FXO-37FL
Application		C-MOS Output	Low Voltage Type
Frequency Range		50~100MHz	100~125MHz
Standard Frequency		Table 1	
Frequency Stability		$\pm 100 \times 10^{-6}$	
Operating Temperature Range		0 ~ +70°C	
Storage Temperature Range		-20 ~ +80°C	
Supply Voltage		5 $\pm$ 0.25V	3.3 $\pm$ 0.15V
Current		50mA MAX.	25mA MAX.
Load		25pF(10TTL)	15pF(5TTL)
Output Level		V _{OH} : 4.0V MIN./V _{OL} : 0.5V MAX.	V _{OH} : 2.8V MIN. V _{OL} : 0.5V MAX.
Output Symmetry		40~60% (V _T =1/2V _{DD})	
Rise Time/Fall Time		7ns MAX.	
Start-up Time		10ms MAX.	15ms MAX.
Vibration		10~55Hz Amplitude 1.5mm, Cycle 2 minute, 3 direction, 2 hour each	
Shock		1000G	
Weight		0.2g	


*Taping item packaging : one unit 3,000 pcs or 1,000 pcs

■Table 1


Standard Frequencies

Frequency (MHz)
50.000
60.000
64.000
65.000
66.667
67.700
70.000
75.000
75.525
80.000
90.3168
94.410
100.000
106.250
120.000

■Outline



■Land Pattern(reference)



Dimensions(mm)