


AC08DGM to AC08FGM

8 A MOLD TRIAC

PACKAGE DIMENSIONS (Unit: mm)



The AC08DGM to AC08FGM are all diffused mold type triac granted RMS On-state current 8 Amps, with rated voltages up to 600 volts.

FEATURES

- 80 A Surge Current
- TO-220AB mold package
- Low-cost

APPLICATIONS

- Motor speed control
- Lamp dimmer, Temperature controllers
- Various solid state switches, etc.

MAXIMUM RATINGS

CHARACTERISTIC	SYMBOL	AC08DGM	AC08EGM	AC08FGM	UNIT	NOTE
Repetitive Peak off Voltage	V_{DRM}	400	500	600	V	
Non-repetitive Peak off Voltage	V_{DSM}	500	600	700	V	
RMS On-State Current	I_T (RMS)	8 ($T_c = 107^\circ\text{C}$)			A	See Fig. 11, 12
Peak Surge On-State Current	I_{TSM}	80 (50Hz, Non-repetitive)			A	See Fig. 2
Fusing Current	$\int i_T^2 dt$	28 ($1\text{ ms} \leq t \leq 10\text{ ms}$)			A^2s	
Peak Gate Power Dissipation	P_{GM}	5.0			W	
Average Gate Power Dissipation	P_G (AV)	0.5			W	
Peak Gate Current	I_{FGM}	± 3			A	
Junction Temperature	T_j	-40 to $+125$			$^\circ\text{C}$	
Storage Temperature	T_{stg}	-40 to $+125$			$^\circ\text{C}$	

ELECTRICAL CHARACTERISTICS ($T_j = 25^\circ\text{C}$)

CHARACTERISTIC		SYMBOL	TEST CONDITIONS	MIN.	TYP.	MAX.	UNIT	NOTE
Peak off-State Current		I_{DRM}	$T_j = 125^\circ\text{C}$, $V_{\text{DM}} = V_{\text{DRM}}$	—	—	2	mA	
On-State Voltage		V_{TM}	$I_{\text{TM}} = 10\text{ A}$	—	—	1.6	V	See Fig. 1
Gate Trigger Current	Trigger Mode I	I_{GT}	$V_{\text{DM}} = 12\text{ V}$ $R_L = 30\ \Omega$	—	—	30	mA	See Fig. 4
	II			—	—	80		
	III			—	—	30		
	IV			—	—	30		
Gate Trigger Voltage	Trigger Mode I	V_{GT}	$V_{\text{DM}} = 12\text{ V}$ $R_L = 30\ \Omega$	—	—	1.5	V	See Fig. 4
	II			—	—	2.0		
	III			—	—	1.5		
	IV			—	—	1.5		
Gate Non-Trigger. Voltage		V_{GD}	$T_j = 125^\circ\text{C}$ $V_{\text{DM}} = 1/2 V_{\text{DRM}}$	0.3	—	—	V	
Commutating dv/dt		(dv/dt) C	$T_j = 125^\circ\text{C}$ (di _T /dt) C = -4 A/ms $V_D = 400\text{ V}$	10	—	—	V/ μs	
Holding Current		I_{H}	$V_D = 24\text{ V}$	—	30	—	mA	
Thermal Resistance		R_{th} (j-c)	Junction to Case	—	—	1.8	$^\circ\text{C/W}$	See Fig. 13

Trigger Mode & Test Circuit




Fig. 1 $i_T - v_T$ CHARACTERISTICFig. 2 I_{TSM} RATING

Fig. 3 $V_G - I_G$ RATING




Fig. 4 $V_{GT} - I_{GT}$ CHARACTERISTIC




Fig. 5 $I_{GT} - T_a$ TYPICAL DISTRIBUTION




Fig. 6 $V_{GT} - T_a$ TYPICAL DISTRIBUTION




Fig. 7 $i_{GT} - \tau$ TYPICAL DISTRIBUTION




Fig. 8 $v_{GT} - \tau$ TYPICAL DISTRIBUTION









Fig. 9 $I_H - T_a$ TYPICAL DISTRIBUTIONFig. 10 $P_{T(AV)} - I_{T(RMS)}$ CHARACTERISTICFig. 11 $T_c - I_{T(RMS)}$ RATINGFig. 12 $T_a - I_{T(RMS)}$ RATING

Fig. 13 Z_{th} CHARACTERISTIC



NEC Corporation

INTERNATIONAL ELECTRON DEVICES DIV.

SUMITOMO MITA Building, 37-8,
Shiba Gochome, Minato-ku, Tokyo 108, Japan
Tel: Tokyo 456-3111

Telex Address: NECTOK J22686
Cable Address: NEC TOKYO

SC-1033
APR. - 25-85M
Printed in Japan