




SINGLE PHASE SILICON BRIDGE RECTIFIER

TECHNICAL SPECIFICATION

VOLTAGE: 50 TO 1000V CURRENT: 3.0A

- Ideal for printed circuit board
- Surge overload rating: 50 A peak
- High case dielectric strength
- High temperature soldering guaranteed:
250°C/10sec/0.375"(9.5mm) lead length
at 5 lbs tension

- Terminal: Plated leads solderable per MIL-STD 202E, method 208C
- Case: UL-94 Class V-O recognized flame retardant epoxy
- Polarity: Polarity symbol marked on body
- Mounting position: Hole thru for #6 screw



Dimensions in inches and (millimeters)

(Single-phase, half-wave, 60Hz, resistive or inductive load rating at 25°C, unless otherwise stated, for capacitive load, derate current by 20%)

RATINGS	SYMBOL	KBPC 1005	KBPC 101	KBPC 102	KBPC 104	KBPC 106	KBPC 108	KBPC 110	UNITS
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	50	100	200	400	600	800	1000	V
Maximum RMS Voltage	V_{RMS}	35	70	140	280	420	560	700	V
Maximum DC Blocking Voltage	V_{DC}	50	100	200	400	600	800	1000	V
Maximum Average Forward Rectified Current ($T_c=50^{\circ}C$)	$I_{F(AV)}$	3.0							A
Peak Forward Surge Current (8.3ms single half sine-wave superimposed on rated load)	I_{FSM}	50							A
Maximum Instantaneous Forward Voltage (at forward current 1.5A DC)	V_F	1.1							V
Maximum DC Reverse Current $T_a=25^{\circ}C$ (at rated DC blocking voltage) $T_a=100^{\circ}C$	I_R	10.0 500							μA μA
Operating Temperature Range	T_J	-55 to +125							$^{\circ}C$
Storage Temperature	T_{STG}	-55 to +150							$^{\circ}C$