


NPN SILICON PLANAR EPITAXIAL TRANSISTOR

2N5172



**TO-92
Plastic Package**

ABSOLUTE MAXIMUM RATINGS(Ta=25°C unless specified otherwise)

DESCRIPTION	SYMBOL	VALUE	UNITS
Collector Emitter Voltage	V_{CEO}	25	V
Collector Base Voltage	V_{CBO}	25	V
Emitter Base Voltage	V_{EBO}	5	V
Collector Current Continuous	I_C	100	mA
Power Dissipation @ Ta=25°C	P_D	625	mW
Derate Above 25°C		5	mW/°C
Power Dissipation @ Tc=25°C	P_D	1.5	W
Derate Above 25°C		12	mW/°C
Operating And Storage Junction Temperature Range	T_j, T_{stg}	- 55 to +150	°C

THERMAL RESISTANCE

Junction to Ambient	$R_{th(j-a)}$	200	°C/W
Junction to Case	$R_{th(j-c)}$	83.3	°C/W

ELECTRICAL CHARACTERISTICS (Ta=25°C unless specified otherwise)

DESCRIPTION	SYMBOL	TEST CONDITION	MIN	TYP	MAX	UNITS
Collector Emitter Voltage	V_{CEO}	$I_C=10mA, I_B=0$	25			
Collector Cut Off Current	I_{CBO}	$V_{CB}=25V, I_E=0$ $V_{CB}=25V, I_E=0, T_a=100°C$			100 10	nA μA
Collector Cut Off Current	I_{CES}	$V_{CE}=25V, V_{BE}=0V$			100	nA
Emitter Cut Off Current	I_{EBO}	$V_{EB}=5V, I_C=0$			100	nA
DC Current Gain	h_{FE}	$V_{CE}=10V, I_C=10mA$	100		500	
Collector Emitter Saturation Voltage	$V_{CE(sat)}$	$I_C=10mA, I_B=1mA$			0.25	V
Base Emitter Saturation Voltage	$V_{BE(sat)}$	$I_C=10mA, I_B=1mA$		0.75		V
Base Emitter On Voltage	$V_{BE(on)}$	$V_{CE}=10V, I_C=10mA$	0.5		1.2	V

DYNAMIC CHARACTERISTICS

Current Gain-Bandwidth Product	f_T	$I_C=2mA, V_{CE}=5V$		120		MHz
Collector Base Capacitance	C_{Cb}	$I_E=0, V_{CB}=0V, f=1MHz$	1.6		10	pF
Small Signal Current Gain	h_{fe}	$V_{CE}=10V, I_C=10mA$ $f=1kHz$	100		750	

Disclaimer

The product information and the selection guides facilitate selection of the CDIL's Discrete Semiconductor Device(s) best suited for application in your product(s) as per your requirement. It is recommended that you completely review our Data Sheet(s) so as to confirm that the Device(s) meet functionality parameters for your application. The information furnished in the Data Sheet and on the CDIL Web Site/CD is believed to be accurate and reliable. CDIL however, does not assume responsibility for inaccuracies or incomplete information. Furthermore, CDIL does not assume liability whatsoever, arising out of the application or use of any CDIL product; neither does it convey any license under its patent rights nor rights of others. These products are not designed for use in life saving/support appliances or systems. CDIL customers selling these products (either as individual Discrete Semiconductor Devices or incorporated in their end products), in any life saving/support appliances or systems or applications do so at their own risk and CDIL will not be responsible for any damages resulting from such sale(s).

CDIL strives for continuous improvement and reserves the right to change the specifications of its products without prior notice.



CDIL is a registered Trademark of
Continental Device India Limited

C-120 Naraina Industrial Area, New Delhi 110 028, India.
Telephone + 91-11-2579 6150, 5141 1112 Fax + 91-11-2579 5290, 5141 1119
email@cdil.com www.cdilsemi.com