

File Number 414

2N5754-2N5757


2.5-A Silicon Triacs

Features:

- Gate sensitivity - 25 mA
- di/dt capability - 100 A/ μ s
- Low switching losses
- Low-on-state voltage at high current levels

Voltage Package	100 V Types	200 V Types	400 V Types	600 V Types
Modified TO-205	2N5754	2N5755	2N5756	2N5757

TERMINAL DESIGNATIONS



MODIFIED TO-205

These RCA triacs are gate-controlled full-wave silicon ac switches that are designed to switch from an off-state to an on-state for either polarity of applied voltage with positive or negative gate triggering voltages.

The gate sensitivity of these triacs permits the use of economical transistorized control circuits and enhances their use in low-power phase control and load-switching applications.

MAXIMUM RATINGS, Absolute-Maximum Values:

For operation with sinusoidal supply voltage at frequencies up to 50/60 Hz and with resistive or inductive load

	2N5754	2N5755	2N5756	2N5757	
* V_{DROM} Δ Gate open, $T_J = -65$ to 100°C	100	200	400	600	V
$I_{T(RMS)}$ ($\theta = 360^\circ\text{C}$)	2.5				A
$T_C = 70^\circ\text{C}$	See Figs. 2, 3, 4				
For other conditions					
I_{TSM} For one cycle of applied principal voltage, at current and temperature shown above for $I_{T(RMS)}$	25				A
60 Hz (sinusoidal)	21				A
50 Hz (sinusoidal)	See Figs. 5, 6				
For more than one cycle of applied principal voltage					
di/dt $V_D = V_{DROM}$, $I_{GT} = 50$ mA, $t_r = 0.1$ μ s	100				A/ μ s
i^2t [At T_C shown for $I_{T(RMS)}$]	4.3				A ² s
$t = 20$ ms	2				A ² s
$t = 2.5$ ms	1				A ² s
$t = 0.5$ ms	See Fig. 6				
For other time values					
* I_{OTM} * For 1 μ s max.	1				A
P_{GM} Peak (For 1 μ s max., $I_{GT} \leq 1$ A (peak)	10				W
* $P_{G(AV)}$ - $T_C = 70^\circ\text{C}$	0.15				W
$T_A = 25^\circ\text{C}$	0.05				W
* T_{JG}	-65 to 150				$^\circ\text{C}$
* T_C	-65 to 100				$^\circ\text{C}$
T_T During soldering for 10 s maximum at distance $\geq 1/16$ in. (1.58 mm) from seating plane	225				$^\circ\text{C}$

For Notes See Electrical Characteristic Chart

3875081 G E SOLID STATE

01E 17754

DT-25-13

Triacs

2N5754-2N5757




Fig. 1 - Power dissipation vs. on-state current.




Fig. 2 - Maximum allowable case temperature vs. on-state current.




Fig. 3 - Maximum allowable ambient temperature vs. on-state current.




Fig. 4 - Maximum allowable heat-sink temperature vs. on-state current.




Fig. 5 - Peak surge on-state current vs. surge-current duration.




Fig. 6 - Peak surge on-state current and fusing current vs. time.

3875081 G E SOLID STATE

01E 17755 D T-25-13

Triacs

2N5754-2N5757




Fig. 7 - On-state current vs. on-state voltage.




Fig. 8 - DC holding current (positive or negative) vs. case temperature.




Fig. 9 - DC gate-trigger current vs. case temperature.




Fig. 10 - DC gate-trigger voltage vs. case temperature.