

3875081 G E SOLID STATE
Ultra-Fast-Recovery Rectifiers

01E 17649 D T-03-17

RUR-D1610, RUR-D1615, RUR-D1620


File Number 1383

**Dual 16-A, High-Speed, High Efficiency
Epitaxial Silicon Rectifiers****Features:**

- Ultra fast recovery time (< 35 ns)
- Low forward voltage
- Low thermal resistance
- Planar design
- Wire-bonded construction

Applications:

- General purpose
- Power switching circuits to 100 kHz
- Full-wave rectification

TERMINAL DESIGNATIONS

The RCA RUR-D1610, RUR-D1615 and RUR-D1620^{*} are low forward voltage drop, ultra fast-recovery rectifiers ($t_{rr} < 35$ ns). They use an ion-implanted planar epitaxial construction.

These devices are intended for use as output rectifiers and fly wheel diodes in a variety of high-frequency pulse-width modulated power supplies, amplifiers and switching regulators. Their low stored charge and attendant fast

reverse recovery behavior minimize electrical noise generation and, in many circuits, markedly reduce the turn-on dissipation of the associated power switching transistors.

All are supplied in steel JEDEC TO-204AA hermetic packages.

^{*}Formerly RCA Developmental Nos. TA9226A, B and C respectively.

MAXIMUM RATINGS, Absolute-Maximum Values, per Junction:

	RUR-D1610	RUR-D1615	RUR-D1620	V
VRM	100	150	200	
If (Average)				
TA = 25°C (No Heat Sink)	6			A
TA = 25°C (With Heat Sink) ■	16			A
TC = 125°C	16			A
IfSM (surge)				
8.3 ms, 1/2 cycle, non-repetitive	275			A
Thermal Resistance (J-C)		1.5		°C/W
Thermal Resistance (J-C) Total		1.2		°C/W
Thermal Resistance (J-A)	30			°C/W
T _{stg} , T _J		-55 to 150		°C
T _L (Lead temperature during soldering)			260	°C
At distance > 1/8 in. (3.17 mm) from case for 10 s max.				

■ Wakefield type 621 heat sink with convection cooling

3875081 G E SOLID STATE

01E 17650 D T-03-17

Ultra-Fast-Recovery Rectifiers

RUR-D1610, RUR-D1615, RUR-D1620

ELECTRICAL CHARACTERISTICS, per Junction

CHARACTERISTICS	TEST CONDITIONS			LIMITS						UNITS	
	T _J °C	Voltage V _H V	Current I _f A	RUR-D1610		RUR-D1615		RUR-D1620			
				Min.	Max.	Min.	Max.	Min.	Max.		
I _R	25	100		—	15	—	—	—	—	μA	
		150		—	—	—	15	—	—		
	100	200		—	—	—	—	—	15		
		100		—	1.5	—	—	—	—		
V _F	25		16	—	0.95	—	0.95	—	1	V	
	125		16	—	0.83	—	0.83	—	0.88		
I _{RR}	25		4(a)	—	35	—	35	—	35	ns	
R _{θJC} R _{θJA}				—	1.5	—	1.5	—	1.5	°C/W	
C _J	25	10	0	80 Typ.		80 Typ.		80 Typ.		pF	

(a) dI/dt > 40A/μs, I_{RM}(rec) < 1A, I_{RR} = 0.25A