



SURFACE MOUNT SWITCHING DIODES

Case: SOT – 23 Molded Plastic

Operating Temperature: – 65°C to 150°C

Part No.	Cross-Reference	Marking	Min. Repetitive Rev. Voltage	Max. Fwrd Current	Max. Cont. Reverse Current	Max. forward Voltage	Maximum Capacitance	Reverse Recovery Time	Pin – out Diagram
			V _{rrm} (V)	I _F (mA)	I _r (nA) @ V _r (V)	V _F (V) @ I _F (mA)	C (pF)	T _{rr} (nS)	
BAS21	–	JS	200	–	100@200	1.00@100	–	50.00	1
MMBD1401	–	29		–		1.00@200	–		1
MMBD1402	–	31		–		1.00@200	–		2
MMBD1403	–	32		–		1.00@200	–		3
MMBD1404	–	33		–		1.00@200	–		4
MMBD1405	–	34		–		1.00@200	–		5
MMBD1501A	–	11A	200	–	–	1.00@200	–	–	1
MMBD1503A	–	13A	200	–	–	1.00@200	–	–	3
BAS20	–	A81	150	–	100@150	1.00@100	–	50.00	1
BAS19	–	A8	120	–	100@120	1.00@100	–	50.00	1
BAS29	–	L20		–		0.84@50	–		1
BAS31	–	L21		–		0.84@50	–		3
BAS35	–	L22		–		0.84@50	–		5
TMPD7000	MMBD7000	5D	100	200	500@100	0.75@100	1.5	4.00	3
TMPD914	MMBD914			–	5000@75	1.00@10	4.0		1
MMBD914	SMD4148			–	5000@75	1.00@10	4.0		1
MMBD914B	SMD4448			–	5000@75	1.00@100	4.0		1
MMBD1201	–			–	25@100	1.00@200	–		1
MMBD1202	–			–	25@100	1.00@200	–		2
MMBD1203	–			–	25@100	1.00@200	–		3
MMBD1204	–			–	25@100	1.00@200	–		4
MMBD1205	–			–	25@100	1.00@200	–		5
MMBD4148	SMD914			–	5000@75	1.00@10	4.0		1
TMPD4148	MMBD4148			–	5000@75	1.00@10	4.0		1
MMBD4448	SMD914B			–	5000@75	1.00@100	4.0		1
TMPD2836	MMBD2836	A6	75	100	100@50	1.00@50	4.0	15.00	5
BAS16	–			250	1000@75	1.00@50	2.0	6.00	5
TMPD6050	MMBD6050	JA	50	200	100@50	1.1@100	2.5	4.00	1
BAV70	–			250	5000@70	1.00@50	1.5	6.00	4
BAV99	–				2500@70		1.5		3
BAW56	–				2500@70		2.0		5
BAV74	–			–	100@50	1.00@100	–	0.70	4
TMPD2835	MMBD2835	85	35	100		1.00@50	4.0	15.00	5
MMBD1701	–		30	–	50@30	1.10@50	–	0.70	1
MMBD1702	–			–			–		2
MMBD1703	–			–			–		3
MMBD1704	–			–			–		4
MMBD1705	–			–			–		5
BA779	–	–	20	50	20@16	1.00@20	0.5	–	1
BA779S	–							–	1
BA779 – 2	–							–	3
BB804	–	–	20	50	20@16	–	47.5	–	4
BB814	–					–	46.5	–	4
BB824	–					–	45.0	–	4

